

# iGen4500

## 4500 Watt Digital Inverter Gasoline Portable Generator

3700 Running Watts | 4500 Peak Watts



50 State and  
Canada Model



Fuel efficient, 3.4 gallon  
fuel tank that runs 18 hrs  
at 25% load

Two 5V USB ports for charging  
sensitive electronics such as  
phones or tablets

RV and camper ready with  
TT-30R outlet

Push button electric start

Telescoping handle for easy  
transportation

Remote start key fob included for  
starting and stopping generator

<3% THD  
SINE WAVE OUTPUT

Parallel capable with another iGen  
using a Westinghouse parallel cord  
(additional iGen and cord sold separate)

Double-insulated acoustic  
enclosure and low tone mufflers  
to reduce operating noise




Dependable 7.3 HP 224cc OHV  
4-Stroke Westinghouse engine

### What Comes in the Box



### LED Data Center



### AUTOMATIC ROTATING DIGITAL DISPLAY



# iGen4500

## Inverter Generator Specifications



Gasoline Peak Watts	4500
Gasoline Running Watts	3700
Peak Amps at 120V	37.5 amps
Running Amps at 120V	30.8 amps
AC Voltage	120 Volts
DC Voltage	5 Volts
AC Frequency	60 Hz
Parallel Capable with 50A Westinghouse Cord (sold separate)	Yes
Engine Horse Power (HP)	7.3 HP
Total Harmonic Distortion (THD)	<3%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Electric, Remote, Recoil
Battery Included	Yes
Battery Charger Included	Yes
Remote Start Fob Included	Yes (paired at factory)
Remote Start Distance (yards/meters)	109 yd. (100 m.)
Engine Displacement	224cc
Engine Brand	Westinghouse
Engine Type	OHV 4 Stroke
Engine Speed	Variable
Engine RPM	Max 3600
Operational Volume	As low as 52 dBA
Spark Plug (included)	Torch E6RTC
Carburetor Kit Required to Operate at Altitude	Yes
Altitude Carburetor Kit Number (sold separate)	140540
Economy Mode Switch	Yes
Built-in Inverter	Yes
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	.6 qt. (20.3 oz.)
Oil Capacity (Quarts/Ounces)	.6 qt. (20.3 oz.)
Low Oil Shutdown	Automatic
Fuel Type	Unleaded Gasoline, 10% Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Material	Steel

Fuel Tank Capacity (Gallons/Liters)	3.4 gal. (12.8 L)
Run Time at %25 Load (hrs.)	18 hrs.
Run Time at %50 Load (hrs.)	15 hrs.
Gasoline Fuel Gauge	Yes
Choke type	Automatic
AC Outlets	(1) 120V 30A (TT-30R) (1) Duplex 120V 20A (5-20R)
DC Outlets	(2) 5V USB ports
Ground	Floating Neutral
Covered Outlets	Yes
Transfer Switch Ready	No
Westinghouse Portable Transfer Switch Ready	No
Volt Meter	No
GFCI Outlets	No
LED Data Center	Yes
RV Ready Outlet	Yes
Overload Protection (circuit breaker)	Yes
Handle Style	Telescoping Handle
Emissions	EPA, CARB
Canada CSA Compliant	Yes
Wheel Kit Included	Yes (assembled)
Wheel Size	5.5 in. Diameter, 1.5 in. Thick
Muffler	Pulse-Flo™
Spark Arrestor	Yes
Residential Warranty	3 Years or 1000 hrs.
Commercial Warranty	6 Months or 1000 hrs.
Assembled Length in. (mm)	24.5 in. (622 mm)
Assembled Width in. (mm)	17.5 in. (445 mm)
Assembled Height in. (mm)	20 in. (508 mm)
Carton Length in. (mm)	30 in. (762 mm)
Carton Width in. (mm)	19.5 in. (495 mm)
Carton Height in. (mm)	21 in. (533 mm)
Dry Unit Weight lb. (kg)	98 lb. (44 kg)
Shipping Weight lb. (kg)	104 lb. (47 kg)
UPC	855464003902
GTIN	00855464003902