



# Air Seeder Hose



## Clear with White or Black Helix Bulk Hose

Air Seeder/PVC suction and discharge hose for water, light chemicals, and pumping services in the agricultural, rental, construction, marine and irrigation industries.

### Features:

- Construction: A smooth bore hose made of flexible abrasion resistant extruded clear PVC with a rigid PVC helix.
- Temp Range: -10°F to 130°F (under static conditions)  
WP and MBR (continuous service): Applicable @ 68°F
- Standard Length: 100'

Part No.	Colour	ID x OD	Length	MBR	Working Pressure (PSI)
HOS73050	White	3/4" x 1.00"	100'	2"	90#
HOS73051	White	1" x 1.25"	100'	3"	85#
HOS73051BLK	Black	1" x 1.25"	100'	3"	85#
HOS73052	White	1 1/4" x 1.51"	100'	3"	80#
HOS73053	White	1 1/2" x 1.81"	100'	4"	70#
HOS73054	White	2" x 2.34"	100'	5"	65#
HOS73055	White	2 1/2" x 2.88"	100'	6"	60#
HOS73055BLK	Black	2 1/2" x 2.88"	100'	6"	60#
HOS73056	White	3" x 3.42"	100'	8"	55#
HOS73057	White	4" x 4.49"	100'	10"	50#
HOS73058	White	5" x 5.58"	100'	21"	45#
HOS73059	White	6" x 6.80"	100'	24"	40#

## Urethane - Bulk Hose (Kanaflex)

Dry material pneumatic conveying systems and plastic pellet and powder transfer when static is not a concern. Agricultural applications, such as air seeders, abrasive material vacuum systems, and industrial vac equipment.

Construction: Flexible polyurethane lined PVC tube, rigid PVC helix, smooth bore, PVC corrugated O.D.

### Features:

- Temp. Range: -13°F to 140°F
- Lightweight and flexible in sub-zero temperatures.
- Clear polyurethane lined PVC tube provides abrasion resistance, permits visual check of material flow, prevents material build up, and provides quiet operation.
- Corrugated PVC O.D. with raised PVC helix for increased flexibility and easy drag.



Part No.	Colour	ID x OD	Length	MBR	Working Pressure (PSI)
HOSK100URD-BK-250	Black	2-1/2" x 2.87"	100'	5.0	35
HOSK100URD-RD-250	Red	2-1/2" x 2.87"	100'	5.0	35



Find a local dealer