




# 2025 ESTATE EQUIPMENT CATALOGUE


 WESTWARD PARTS



# *Westward has the part!*

**Westward has the part!** That's our commitment to you, and that's what sets us apart. Westward Parts has over 52 years of expertise with all makes of agricultural parts, sprayer parts, sprayers, as well as ground maintenance and estate equipment. Our Canadian dealers are served from three different warehouse locations across the country. Westward Parts offers our dealers the most comprehensive product portfolio and exclusive product offerings. And it will all be delivered on time, with an enjoyable customer service experience that won't let you down.

## **Westward Parts Distribution:**



**RED DEER**  
6517 - 67 Street  
Red Deer, AB T4P 1A3  
Fax: 1-800-661-4508

**REGINA**  
201 Henderson Drive  
Regina, SK S4N 7E2  
Fax: 1-800-721-2977

**WINNIPEG**  
1435 St. James Street  
Winnipeg, MB R3H 0W9  
Fax: 1-800-257-8338

**1-888-937-7278**

**WWW.WESTWARDPARTS.COM**



# ESTATE EQUIPMENT

## Index

### POWER EQUIPMENT

Generators	5-8
Inverter Generators	2-4
Pressure Washers	9-10
T&T Cleaner & Foam Kits	11-12

### FENCING EQUIPMENT

Augers & Options	18
Hydraulic Post Hole Diggers	19-20
Post Hole Diggers	14-17

### HAY & BALE HANDLING EQUIPMENT

3 Point Bale Spears	23
3 Point Hay Rakes	31
Bale Clamps	28-29
Bale Spears	22-26
Bale Spin Off	28
Bale Unroller	29
Fine Twine Cutter	27
Front Loader Bale Spears	24
Hay Rakes	31
Hay Turning Spreader	30
Pull-Type Wheel Rakes	32
Replacement Bale Spears	27
Replacement Tines and Rake Wheels	30

### LAWN & GARDEN

3 Point Fertilizer Spreaders	38
ATV Spreaders	35-37
Discs	39
Fertilizer Spreaders	34-38
Lawn Fertilizer	39
Spreaders	34-38
Wood Chippers	40

### MATERIAL MOVEMENT

ATV Grader Blade	54
Box Scrapers	60
Bucket Forks	49
Bucket Tooth Bar	44
Cement Mixer	61
Clamp-on Bucket Forks	49
Grapples	42-43
Heavy Duty Rear Blades	56-57
Manure Forks	48
Mini Skid Steer Pallet Forks	45
Pallet Forks	44-48
Quick Hitches	62
Rear Blades	54-56
Rotary Brooms	63-64
Skid Steer Attachments	49-53
Snow Blades	58-59
Snow Pushers	59
Trailer Movers	52-53

### TILLAGE

3 in 1 Soil Conditioner	68
Arena Groomers	69-70
ArenaVator III	69
Harrows - Diamond	67
Harrows - Flexible	66
Heavy Duty Core Aerators	71
Heavy Duty Disc Harrows	68
Landscape Rakes	72
Rakes	72
Rototillers - 3 Pt. Hitch	73-74
Single Shank Ripper	71
Soil Conditioner	68

# ESTATE EQUIPMENT

## Index



### SPRAYERS & ACCESSORIES

3 Pt. Hitch Sprayer Pump .....	88
ATV Sprayer .....	83
Backpack & Handheld Sprayers .....	81
Backpack Sprayers - Battery Powered .....	82-83
Backpack Sprayers - Manual .....	78-81
Calibrator .....	87
Compression Sprayers .....	76-77
Digital Pressure Tester .....	86
H2O Fire Pro Sprayer .....	84
Hand-Held Sprayers .....	76-77, 81
Industrial Concrete Sprayer .....	81
Nozzle Cleaner & Tip Tool .....	86
Sprayer Calibrator .....	87
Sprayer Pump .....	88
Sprayer Tools & Meters .....	86-87
Super Sponge Weed Wipers .....	85
Westward Parts & FIMCO Catalogue .....	88

### STORAGE TANKS & CHEMICAL HANDLERS

Black Vertical Water Tanks .....	92
Chembine .....	95-96
Chemical Handlers .....	93-96
Flat Bottom Utility Tanks .....	91
Horizontal Leg Tanks .....	92
Indoor Freestanding Potable Water Tanks .....	91
Low Profile Tanks .....	91
Pickup Truck Tanks .....	90
Polyethylene Horizontal Tanks .....	93
Specialty Water Transport Tanks .....	92
Vertical Storage Tanks .....	90

### WATER, TRANSFER, TRASH & FUEL PUMPS

AC Fuel Transfer Pumps .....	114-115
Ag Chemical Pumps .....	120
Chemical Transfer Pumps .....	105-106
DC Fuel Transfer Pumps .....	116-119
Firefighting Water Pumps .....	111
Fuel Nozzles .....	124-126
Fuel Transfer Pumps .....	114-117
Hose .....	127
Hose Reels .....	130
Hydraulic Pumps .....	100
Meters .....	121-123
Mini-Bulk Flow Meters .....	99
Mini-Bulk Pumps .....	99
Nozzles .....	124-126
Pedestal Pumps .....	101
Poly Centrifugal Pumps .....	102-103
Pressure Washer Hose Reels .....	130
Transfer Pump System .....	98
Transfer Pumps .....	104
Trash Pumps .....	112-113
Water Transfer Pumps .....	107-110

# POWER EQUIPMENT

- INVERTER GENERATORS
- GENERATORS
- PRESSURE WASHERS
- T&T CLEANER & FOAM KITS



**WESTWARD PARTS**

# Generators

## 2,100 Watt Inverter Generator


**PURE POWER<sup>®</sup>**
**NEW!**

### FEATURES

- Quiet inverter generator that is easy to transport to bring power to the remotest locations.
- Produces clean power that is needed for sensitive electronics like cell phones and computers.
- Rugged and reliable engine with automatic low oil-shutdown that keeps it safe.
- Copper alternator windings increases efficiency and reduces heat build up to extend lifespan.
- Easy access outlets are protected by waterproof circuit breakers for safety.
- Sound dampening shell lowers volume and protects internals.



Part No.	Description	Weight
PURPP2100R	2,100 Watt Inverter	45 lbs.



### ENGINE

**MODEL:** PURE POWER  
**TYPE:** AIR COOLED, 4-STROKE OHV  
**CC:** 79CC  
**NOISE LEVEL:** 68dB  
**ECONOMY MODE:** YES  
**START TYPE:** PULL/RECOIL START  
**FUEL TYPE:** 86 OCTANE, UP TO 10% ETHANOL  
**FUEL TANK SIZE:** 4L  
**APPROX RUN TIME:** 5HR @ 1/2 LOAD  
**OIL TYPE:** SAE 10W30  
**CERTIFICATIONS:** EPA III, CSA AND CALI CARB

### FRAME

**TYPE:** ENCLOSED PLASTIC SHELL  
**PORTABILITY:** CARRY HANDLE

### ALTERNATOR

**MAX WATT:** 2,100 W  
**RUNNING WATT:** 1,600 W  
**MASTER CIRCUIT BREAKER:** 15A  
**VOLTAGES:** 120V  
**WINDINGS:** COPPER  
**GROUNDING:** NEUTRAL FLOATING

### OUTLETS

2x USB PORTS  
 1x DC 12V@8.3A LOCKPOINT  
 2x AC 120V 20A HOUSEHOLD, NEMA 5-20R  
 PARALLEL CAPABILITY

### BOXED SIZE

**LxWxH:** 20" x 12" x 19"  
**WEIGHT:** 45 LBS

### UNIT SIZE



**UNIT WEIGHT:** 40 LBS

### WARRANTY

**ENGINE:** 2 YEAR  
**ELECTRONICS:** 1 YEAR  
**UPC:** 777987332447

# Generators




## 3,000 Watt Inverter Generator

**FEATURES**

- Quiet inverter generator that is easy to transport to bring power to the remotest locations.
- Produces clean power that is needed for sensitive electronics like cell phones and computers.
- Rugged and reliable engine with automatic low oil-shutdown that keeps it safe.
- Copper alternator windings increases efficiency and reduces heat build up to extend lifespan.
- Easy access outlets are protected by waterproof circuit breakers for safety.
- Sound dampening shell lowers volume and protects internals.



Part No.	Description	Weight
PURPP3000R	3,000 Watt Inverter	59 lbs.



**ENGINE**

MODEL: **PURE POWER**  
 TYPE: **AIR COOLED, 4-STROKE OHV**  
 CC: **120CC**  
 NOISE LEVEL: **67dB**  
 ECONOMY MODE: **YES**  
 START TYPE: **PULL/RECOIL START**  
 FUEL TYPE: **86 OCTANE, UP TO 10% ETHANOL**  
 FUEL TANK SIZE: **4L**  
 APPROX RUN TIME: **5HR @ 1/2 LOAD**  
 OIL TYPE: **SAE 10W30**  
 CERTIFICATIONS: **EPA III, CSA AND CALI CARB**

**FRAME**

TYPE: **ENCLOSED PLASTIC SHELL**  
 PORTABILITY: **CARRY HANDLE**

**ALTERNATOR**

MAX WATT: **3,000 W**  
 RUNNING WATT: **2,300 W**  
 MASTER CIRCUIT BREAKER: **20A**  
 VOLTAGES: **120V**  
 WINDINGS: **COPPER**  
 GROUNDING: **NEUTRAL FLOATING**

**OUTLETS**

2x USB PORTS  
 1x DC 12V@8.3A LOCKPOINT  
 2x AC 120V 20A HOUSEHOLD, NEMA 5-20R  
 PARALLEL CAPABILITY

**BOXED SIZE**

LxWxH: **22" x 13" x 20"**  
 WEIGHT: **59 LBS**

**UNIT SIZE**



UNIT WEIGHT: **54 LBS**

**WARRANTY**

ENGINE: **2 YEAR**  
 ELECTRONICS: **1 YEAR**  
 UPC: **77987332454**

# Generators

## 3,500 Watt Inverter Generator


**PURE POWER<sup>®</sup>**
**NEW!**

### FEATURES

- Quiet inverter generator that is easy to transport to bring power to the remotest locations.
- Produces clean power that is needed for sensitive electronics like cell phones and computers.
- Rugged and reliable engine with automatic low oil-shutdown that keeps it safe.
- Copper alternator windings increases efficiency and reduces heat build up to extend lifespan.
- Easy access outlets are protected by waterproof circuit breakers for safety.
- Sound dampening shell lowers volume and protects internals.
- Folding handle and wheels makes it easier to transport.



Part No.	Description	Weight
PURPP3500R	3,500 Watt Inverter	95 lbs.



### ENGINE

MODEL:	<b>PURE POWER</b>
TYPE:	<b>AIR COOLED, 4-STROKE OHV</b>
CC:	<b>212CC</b>
NOISE LEVEL:	<b>69dB</b>
ECONOMY MODE:	<b>YES</b>
START TYPE:	<b>PULL/RECOIL START</b>
FUEL TYPE:	<b>86 OCTANE, UP TO 10% ETHANOL</b>
FUEL TANK SIZE:	<b>7L</b>
APPROX RUN TIME:	<b>8HR @ 1/2 LOAD</b>
OIL TYPE:	<b>SAE 10W30</b>
CERTIFICATIONS:	<b>EPA III AND CSA</b>

### FRAME

TYPE:	<b>ENCLOSED PLASTIC SHELL</b>
PORTABILITY:	<b>FOLDING HANDLEBARS</b>
WHEELS:	<b>5" PLASTIC</b>

### ALTERNATOR

MAX WATT:	<b>3,500 W</b>
RUNNING WATT:	<b>2,800 W</b>
MASTER CIRCUIT BREAKER:	<b>26A</b>
VOLTAGES:	<b>120V</b>
WINDINGS:	<b>COPPER</b>
GROUNDING:	<b>NEUTRAL FLOATING</b>

### OUTLETS

2x USB PORTS
1x DC 12V@8.3A LOCKPOINT
2x AC 120V 20A HOUSEHOLD, NEMA 5-20R
1x AC 120V 30A TWISTLOCK, NEMA L5-30R

### BOXED SIZE

LxWxH:	<b>25" x 24" x 30"</b>
WEIGHT:	<b>95 LBS</b>

### UNIT SIZE


 UNIT WEIGHT: **85 LBS**

### WARRANTY

ENGINE:	<b>2 YEAR</b>
ELECTRONICS:	<b>1 YEAR</b>
UPC:	<b>777987332461</b>





# Generators

**PURE POWER**<sup>®</sup>

## 3,600 Watt Generator

**NEW!**

**FEATURES**

- Portable generator that can bring power to remote worksites and emergency situations.
- Rugged and reliable engine with automatic low oil-shutdown that keeps it safe.
- Easy access outlets are protected by waterproof circuit breakers for safety.
- Durable powder coated steel roll cage protects the generator and allows easy access for maintenance.
- Folding handle and wheels makes it easier to transport.



Part No.	Description	Weight
PURPP3600PR	3,600 Watt Generator	109 lbs.



**ENGINE**

MODEL: **PURE POWER**  
 TYPE: **AIR COOLED, 4-STROKE OHV**  
 CC: **212CC**  
 NOISE LEVEL: **72dB**  
 ECONOMY MODE: **YES**  
 START TYPE: **PULL/RECOIL START**  
 FUEL TYPE: **86 OCTANE, UP TO 10% ETHANOL**  
 FUEL TANK SIZE: **12L**  
 APPROX RUN TIME: **10HR @ 1/2 LOAD**  
 OIL TYPE: **SAE 10W30**  
 CERTIFICATIONS: **EPA III AND CSA**

**FRAME**

TYPE: **POWDER COATED STEEL ROLL CAGE**  
 PORTABILITY: **FOLDING HANDLES WITH WHEELS**  
 WHEELS: **6" FLAT FREE**

**ALTERNATOR**

MAX WATT: **3,600 W**  
 RUNNING WATT: **2,800 W**  
 MASTER CIRCUIT BREAKER: **24A**  
 VOLTAGES: **120V**  
 GROUNDING: **NEUTRAL BONDED**

**OUTLETS**

4x AC 120V 20A HOUSEHOLD, NEMA 5-20R  
 1x AC 120V 30A TWISTLOCK, NEMA L5-30R

**BOXED SIZE**

LxWxH: **27" x 19" x 19"**  
 WEIGHT: **109 LBS**

**UNIT SIZE**



UNIT WEIGHT: **101 LBS**

**WARRANTY**

ENGINE: **2 YEAR**  
 ELECTRONICS: **1 YEAR**  
 UPC: **777987332492**

# Generators

## 6,800 Watt Generator

**PURE POWER<sup>®</sup>**
**NEW!**

### FEATURES

- Powerful Portable generator ideal for remote worksites and emergency power.
- Rugged and reliable engine with automatic low oil-shutdown that keeps it safe.
- Easy access outlets are protected by waterproof circuit breakers for safety.
- Durable powder coated steel roll cage protects the generator and allows easy access for maintenance.
- Folding handle and wheels makes it easier to transport.



Part No.	Description	Weight
PURPP6800PR	6,800 Watt Generator	195 lbs.



### ENGINE

**MODEL:** PURE POWER  
**TYPE:** AIR COOLED, 4-STROKE OHV  
**CC:** 389CC  
**NOISE LEVEL:** 76dB  
**ECONOMY MODE:** YES  
**START TYPE:** PULL/RECOIL START  
**FUEL TYPE:** 86 OCTANE, UP TO 10% ETHANOL  
**FUEL TANK SIZE:** 25L  
**APPROX RUN TIME:** 11HR @ 1/2 LOAD  
**OIL TYPE:** SAE 10W30  
**CERTIFICATIONS:** EPA III AND CSA

### FRAME

**TYPE:** POWDER COATED STEEL ROLL CAGE  
**PORTABILITY:** FOLDING HANDLES WITH WHEELS  
**WHEELS:** 10" FLAT FREE

### ALTERNATOR

**MAX WATT:** 6,800 W  
**RUNNING WATT:** 5,500 W  
**MASTER CIRCUIT BREAKER:** 23A  
**VOLTAGES:** 120V/240V  
**GROUNDING:** NEUTRAL BONDED

### OUTLETS

4x AC 120V 20A HOUSEHOLD, NEMA 5-20R  
 1x AC 120V/240V 30A TWISTLOCK, NEMA L14-30R

### BOXED SIZE

**LxWxH:** 28" x 23" x 23"  
**WEIGHT:** 195 LBS

### UNIT SIZE



**UNIT WEIGHT:** 108 LBS

### WARRANTY

**ENGINE:** 2 YEAR  
**ELECTRONICS:** 1 YEAR  
**UPC:** 777987332515



# Generators

## 8,900 Watt Generator

**PURE POWER**<sup>®</sup>

**NEW!**

### FEATURES

- Powerful portable generator ideal for remote worksites and emergency power.
- Rugged and reliable engine with automatic low oil-shutdown that keeps it safe.
- Includes electric start and battery system.
- Easy access outlets are protected by waterproof circuit breakers for safety.
- Durable powder coated steel roll cage protects the generator and allows easy access for maintenance.
- Folding handle and wheels makes it easier to transport.



Part No.	Description	Weight
PURPP8900ER	8,900 Watt Generator	211 lbs.



### ENGINE

MODEL: **PURE POWER**  
 TYPE: **AIR COOLED, 4-STROKE OHV**  
 CC: **420CC**  
 NOISE LEVEL: **76dB**  
 ECONOMY MODE: **YES**  
 START TYPE: **PULL/RECOIL START**  
 FUEL TYPE: **86 OCTANE, UP TO 10% ETHANOL**  
 FUEL TANK SIZE: **25L**  
 APPROX RUN TIME: **10HR @ 1/2 LOAD**  
 OIL TYPE: **SAE 10W30**  
 CERTIFICATIONS: **EPA III AND CSA**

### FRAME

TYPE: **POWDER COATED STEEL ROLL CAGE**  
 PORTABILITY: **FOLDING HANDLES WITH WHEELS**  
 WHEELS: **10" FLAT FREE**

### ALTERNATOR

MAX WATT: **8,900 W**  
 RUNNING WATT: **6,500 W**  
 MASTER CIRCUIT BREAKER: **27A**  
 VOLTAGES: **120V/240V**  
 GROUNDING: **NEUTRAL BONDED**

### OUTLETS

4x AC 120V 20A HOUSEHOLD, NEMA 5-20R  
 1x AC 120V 30A TWISTLOCK, NEMA L5-30R  
 1x AC 120V/240V 30A TWISTLOCK, NEMA L14-30R

### BOXED SIZE

LxWxH: **32" x 23" x 23"**  
 WEIGHT: **211 LBS**

### UNIT SIZE



UNIT WEIGHT: **197 LBS**

### WARRANTY

ENGINE: **1 YEAR**  
 ELECTRONICS: **1 YEAR**  
 UPC: **777987332546**

# Generators

## 10,500 Watt Generator


**NEW!**

**PURE POWER<sup>®</sup>**

### FEATURES

- Powerful portable generator ideal for remote worksites and emergency power.
- Rugged and reliable engine with automatic low oil-shutdown that keeps it safe.
- Includes electric start and battery system.
- Easy access outlets are protected by waterproof circuit breakers for safety.
- Durable powder coated steel roll cage protects the generator and allows easy access for maintenance.
- Folding handle and wheels makes it easier to transport.



Part No.	Description	Weight
PURPP10500ER	10,500 Watt Generator	230 lbs.



### ENGINE

MODEL: **PURE POWER**  
 TYPE: **AIR COOLED, 4-STROKE OHV**  
 CC: **420CC**  
 NOISE LEVEL: **78dB**  
 ECONOMY MODE: **YES**  
 START TYPE: **ELECTRIC/RECOIL START**  
 FUEL TYPE: **86 OCTANE, UP TO 10% ETHANOL**  
 FUEL TANK SIZE: **25L**  
 APPROX RUN TIME: **9HR @ 1/2 LOAD**  
 OIL TYPE: **SAE 10W30**  
 CERTIFICATIONS: **EPA III AND CSA**

### FRAME

TYPE: **POWDER COATED STEEL ROLL CAGE**  
 PORTABILITY: **FOLDING HANDLES WITH WHEELS**  
 WHEELS: **10" FLAT FREE**

### ALTERNATOR

MAX WATT: **10,500 W**  
 RUNNING WATT: **7,500 W**  
 MASTER CIRCUIT BREAKER: **33 A**  
 VOLTAGES: **120V/240V**  
 GROUNDING: **NEUTRAL BONDED**

### OUTLETS

4x AC 120V 20A HOUSEHOLD, NEMA 5-20R  
 1x AC 120V 30A TWISTLOCK, NEMA L5-30R  
 1x AC 120V/240V 30A TWISTLOCK, NEMA L14-30R

### BOXED SIZE

LxWxH: **32" x 25" x 28"**  
 WEIGHT: **230 LBS**

### UNIT SIZE



UNIT WEIGHT: **210 LBS**

### WARRANTY

ENGINE: **2 YEAR**  
 ELECTRONICS: **1 YEAR**  
 UPC: **777987382522**



# Pressure Washers



## 2,700 PSI - 2.3 GPM Gas Powered Pressure Washer

**FEATURES**

- General purpose pressure washer tackles household projects, such as siding, driveways, fencing, vehicles and more.
- Reliable Pure Power engine can be depended on for extended use.
- Pressure pump is maintenance free, equipped with a built-in soap injector, and delivers excellent performance in a compact design.
- Accessories include 25' hose, 36" gun wand assembly, spray nozzles so that it can be used right out of the box.
- Powder coated steel frame with 10" flat free tires easily handles going over rough terrain.
- Built-in soap container allows for quick and easy use of the soap system.
- Extra storage slots are built into the frame to accommodate additional accessories.



Part No.	Description	Weight (lbs)
PURPP277RX	Pressure Washer, 2,700 psi, 212 cc	80 lbs.

**ENGINE**

MODEL: **PURE POWER**  
 TYPE: **AIR COOLED, 4-STROKE OHV**  
 DISPLACEMENT: **212CC**  
 FUEL TYPE: **86 OCTANE, UP TO 10%ETHANOL**  
 OIL TYPE: **SAE 10W30**  
 CERTIFICATIONS: **EPA III AND CALI CARB**

**PUMP**

MODEL: **AR RMV25G24**  
 TYPE: **AXIAL**  
 OIL TYPE: **SEALED**  
 SOAP SYSTEM: **FIXED INJECTOR**  
 UNLOADER: **BUILT-IN**  
 CONNECTIONS: **M22**

**ACCESSORIES INCLUDED**

HOSE: **25' x 1/4" THERMOPLASTIC**  
 NOZZLES: **40° AND SOAPER**  
 SPRAY GUN: **36" SPLIT LANCE**  
 FITTINGS: **M22**

**FRAME**

TYPE: **POWDER COATED STEEL FRAME**  
 WHEELS: **10" FLAT FREE**  
 STORAGE: **UP TO 5 SPRAY NOZZLES**  
**ROTARY NOZZLE**  
**HOSE**  
**SPRAY GUN**  
**SOAP CONTAINER**

**BOXED SIZE**

LxWxH: **21" x 24" x 23"**  
 WEIGHT: **80 LBS**

**UNIT SIZE**



UNIT WEIGHT: **75 LBS**

**WARRANTY**

ENGINE: **2 YEARS**  
 PUMP: **1 YEAR**  
 ACCESSORIES: **90 DAYS**  
 UPC: **777987341852**

# Pressure Washers



## Hot Water Pressure Washer

### FEATURES

- Heating coil is ignited by a 12v Becker that is fueled with diesel.
- The burner can be turned off and controlled with the adjustable thermostat that can be set up to 93°/200°F with output of 330,000 BTU.
- Commercial grade accessories included are a 50 foot high-pressure hose, spray gun wand assembly, and five spray nozzles.
- Powder coated steel frame with four 13" flat free tires
- A lift point is built into the frame to allow the use of a crane to lift it onto a truck or trailer.
- Frame includes mounting brackets for quick installation onto trucks or trailers by removing the wheels.



Pump Style . . . Triplex  
 Unloader . . . External  
 Series . . . . . Commercial  
 Engine . . . . . Honda GX390  
 Pump . . . . . General  
 CC . . . . . 389  
 PSI . . . . . 4,000  
 GPM . . . . . 4.01750 RPM

Part No.	Description
SPPHW4013HG	Hot Water Pressure Washer

## Wall Mounted Pressure Washer

### FEATURES

- 1.5HP Electric Motor 110V
- 1750 RPM
- 1500 PSI Max.
- 1.6 GPM Max.
- 13.2 Amps
- Triplex pump
- 50 ft. steel braided hose
- 36" Spray Gun & Lance
- Low pressure chemical injector
- Wall-mounted Powder Coated Steel Frame
- Automatic Start/Stop System
- Includes GFCI




Unit includes mounting bolts. Slots are spaced 16" apart to line up with studs

Part No.	Description
SPPP1515EPNW	Wall Mounted Pressure Washer

## Electric Pressure Washer

### FEATURES

- 1750 RPM
- 25 ft. steel braided hose
- Spray gun & lance
- Low pressure chemical injector
- Powder coated frame
- Automatic start / stop system

Motor . . . . . 1.5 HP AR Electric  
 Motor 110V  
 Pump . . . . . BE Triplex  
 GPM . . . . . 1.6  
 PSI . . . . . 1500  
 Amps . . . . . 13.2



Part No.	Description
SPPP1515EPN	Electric Pressure Washer

# T&T Cleaner

**MS T&T Cleaner**  
By MS Schippers

## 5 kg. & 22 kg Cleaner *A Quick And Easy Clean!*

Cleaning large equipment like tractors, trailers and trucks can take up a lot of time and use a lot of product. Our product's lower dosage and easy application mean you could be using less detergent in less time for each wash. And T&T Cleaner is completely biodegradable!

MS T&T Cleaner is a powerful and safe foam detergent that can be used to clean any vehicle or equipment (e.g. cars, trucks, trailers, tractors) and lacquered surfaces (e.g. agricultural implements and milking robots). This premium product quickly removes any dirt or debris that may have built up on your equipment, so you can forget about scrubbing and brushing. It is easy to apply and easy to clean.

Because of the lower dosage required, T&T Cleaner is completely biodegradable. You will also use less product on each wash.

**NEW!**



### 5 kg Jug - Clean up to 6 tractors!

If you are looking for a quicker and easier clean, T&T Cleaner's 5 kg jugs are now available. It is the best option for cleaning your farm or construction equipment. Watch as dirt and debris is removed within just 3-5 minutes of soaking.

- Quick clean
- Low concentration
- Exceptional adhesion
- Shining effect
- Safe to use
- Wide range of application
- Biodegradable



Part No.	Description
WSS2505226	T&T Cleaner 2.0 - 5 kg

### 22 kg Jug - Clean up to 100 pickup trucks!

T&T Cleaner is a product that provides a quick clean but will also last longer with its lower concentration. You can clean more equipment with just one jug of this premium cleaning product.

- Quick clean
- Low concentration
- Exceptional adhesion
- Shining effect
- Safe to use
- Wide range of application
- Biodegradable



Part No.	Description
WSS2505235	T&T Cleaner 2.0 - 22 kg

### 230 kg Drum

Part No.	Description
WSS2505236	T&T Cleaner 2.0 - 230 kg Drum



## Foam Kits


  
By MS Schippers

**Foam Kits for T&T Cleaner** *A Quicker And Easier Clean With These Foam Kits!*

### Standard Foam Kit (A)

Do you have a smaller cleaning job? This standard foam kit is ideal for cleaning smaller vehicles and equipment. This includes a powerful LS10 Foam Gun and a plug that attaches to the end of your own pressure washer wash wand.

- 1x Foam gun LS10, 1.8 mm, 2 L
- 1x Plug 1/4" Male threads
- 1x Drain tap 61 mm



Part No.	Description
WSS0803000	Foam Kit A

### Quick Connect Foam Kit (B)

This kit is ideal for cleaning virtually anything from small vehicles to your largest farm or industrial equipment. This kit includes a powerful LS10 Foam Gun, a high quality quick connector and 2 couplers for an easy transition between foaming and rinsing.

- 1x Foam gun LS10, 1.8 mm, 2 L
- 1x Quick connector Kew/Alto Profi 1/4"
- 2x Coupling Kew/alto, 1/4" female thread
- 1x Adapter 2x 1/4" male thread
- 1x Teflon Tape
- 1x Drain tap 61 mm



Part No.	Description
WSS0803001	Foam Kit B

### Deluxe Quick Connect Foam Kit (C)

Whether you need to clean your smaller vehicles or even those large pieces of equipment on your farm or industrial site, these deluxe quick connect foam kits are ideal. This includes the powerful LS10 foam gun, a high quality quick connector, 2 couplers, a high pressure spray gun and a high pressure spray lance.

This is the most convenient system for professional-level results!



- 1x Foam gun LS10, 1.8 mm, 2 L
- 1x Quick connector Kew/Alto Profi 1/4"
- 2x Coupling kew/alto, 1/4" female thread
- 1x Adapter 2x 1/4" male thread
- 1x Teflon Tape
- 1x Drain tap 61 mm
- 1x High pressure gun ST 2600, Servo
- 1x High pressure spray lance 15°, 120 cm
- 1x Quick coupler 1/4" Female threads
- 1x Plug 3/8" Male threads
- 1x Adapter Kärcher, 3/8" male thread

Part No.	Description
WSS0803002	Foam Kit C


**WESTWARD PARTS**

6517 - 67 St.  
Red Deer, AB T4P 1A3  
Fax: 1-800-661-4508

201 Henderson Dr.  
Regina, SK S4N 7E2  
Fax: 1-800-721-2977

1435 St. James St.  
Winnipeg, MB R3H 0W9  
Fax: 1-800-257-8338

Specifications subject to change without notice or obligation.



WESTWARDPARTS.COM



1-888-937-7278



# FENCING EQUIPMENT

- POST HOLE DIGGERS
- AUGERS & OPTIONS
- HYDRAULIC POST DRIVERS



**WESTWARD PARTS**

# Post Hole Diggers



## GMR300 Compact/Utility Tractor Post Hole Digger

GMR300 is designed to fit most 14-24 horsepower tractors equipped with a Category 0, 3 point hitch and a 540 rpm PTO.

It fits the 16 HP Kubota Model B7100. Capable of handling 6", 9" and 12" diameter standard duty 30" length augers, this 3 position boom allows the unit to fit a variety of tractor models.

A lever is provided for the operator to adjust the auger starting angle.

The gearbox has a 3:1 gear ratio and is protected by the shear-pin PTO drive. The gearbox features tapered roller bearings and spring loaded seals and has a 5 year limited warranty. Built for years of trouble-free work with a minimum amount of maintenance.



**NOTE:** Most tractors of this size have lift arms made of  $\frac{1}{8}$  inch diameter, Category I pins, but with the 20 inch Category 0 spacing. Tractors with very short lift arms made for  $\frac{3}{8}$  inch diameter pins may not be suitable for digging post holes. (Special  $\frac{5}{8}$  inch diameter pins are available for those tractors that can handle the post hole digger).



GMR170565



GMR300 Compact/Utility Tractor Post Hole Digger  
(auger not included)

Part No.	Description	Weight (lbs.)
*GMR300	Post Hole Digger	149
GMR170575	6" x 30" Single Flight Post Hole Auger w/teeth	19
GMR170565	9" x 30" Single Flight Post Hole Auger w/teeth	25
GMR170570	12" x 30" Single Flight Post Hole Auger w/teeth	28

\* No auger included


# Post Hole Diggers

**GMR500/720/925** Standard/Heavy Duty/Industrial Post Hole Digger



Part No.	Main Frame	Gear Ratio	Hitch Size	Output Shaft	Driveline Protection	Weight (lbs.)
*GMR500	3" Steel Tube	3.0 to 1.0	Category I/II	2"	Shear Pin	160
*GMR720	3" Steel Tube	3.18 to 1.0	Category I/II	2"	Shear Pin	206
*GMR925	3" Steel Tube	4.1 to 1.0	Category I/II	2"	Shear Pin	210

\* No auger included



**GMR500**

Worksaver's most popular digger, the Model 500 standard duty, offers 3-position boom adjustment allowing

it to adapt to most tractors. Tubular steel stock of 2.875" diameter is used for the boom for increased durability. Horseshoe yoke allows the unit to operate on Cat I/II tractors offering the operator versatility of use. Job matching augers is easy; they are 42" in length in 6", 9" and 12" diameters in single and double flight configuration. Positioning handle is standard equipment. The gearbox has a limited 5 year warranty and features tapered roller bearings and spring loaded seals.

GMR720 Increased performance is offered in the Model 720 heavy-duty digger. Designed for Cat. I/II tractors, this model offers 3-position boom adjustment, rugged gearbox along with 3-1/2" diameter boom for dependable operation. Augers (42" length) are available in 6", 9", 12", 14", 18" and 24" diameters in single and double flight plus standard or heavy-duty configuration offering the outmost in productivity. The gearbox has a limited 5 year warranty and features tapered roller bearings and spring loaded seals.



GMR925 Industrial duty workhorse, provides dependable operation when mated with any auger from 6" to 30" in diameter. It fits any Cat I/II tractor with 540 rpm PTO. When maximum performance is required, the 4.1:1 ratio gearbox provides the torque to make the operator more productive. The gearbox has a limited 5 year warranty and features tapered roller bearings and spring loaded seals.

OPTIONS / ACCESSORIES		
Part No.	Separate Post Hole Digger Accessories	Weight (lbs.)
GMR170810	Down Force Kit for GMR500 - w/Hyd. Cylinder & Hoses	39
GMR706080	Down Force Kit for GMR720 - w/Hyd. Cylinder & Hoses	40
GMR709025	Down Force Kit for GMR925 - w/Hyd. Cylinder & Hoses	42
GMR102160	Parking Stand Kit for Model GMR300 Post Hole Digger	11
GMR102165	Parking Stand Kit for Models GMR500/720 Post Hole Digger	12
GMR102170	Parking Stand Kit for Model GMR925 Post Hole Digger	13

Down Force Kits provide down force pressure to dig through hard soil surfaces.



GMR709025

# Post Hole Diggers



## Hydraulic Post Hole Diggers *Nine Models to Choose From!*

The models GMR614HC and GMR624HC three point post hole diggers are designed for the operator without a front loader but appreciates the benefits that hydraulic operation offers. Both the GMR614HC and GMR624HC mount to tractors with Category I/II hitches.

The GMR714HC and GMR724HC will attach to backhoe booms or excavators to allow an operator to reach hard to get to places. These units also attach to either side of a loader bucket with four ½" bolts for an unobstructed view of the digging operation.

The GMR814HC models clamp on to the bucket for easy on and off. Each unit slips on to the cutting edge of the bucket and has two turnbuckles and chains to secure it to the bucket. Each unit is adjustable for the left or right side of the bucket, allowing the operator to have a better view of the digging operation.

### FEATURES


- Ability to reverse the auger should it become entangled in roots or rocks.
- No need to replace shear-bolts or repair slip clutches as required on PTO operated units.
- No PTO lifting restrictions with tractor, loader, or backhoe boom.
- All hydraulic units (except GMR614HC and GMR624HC) come less hydraulic hoses.



GMR614HC / GMR624HC



GMR714HC / GMR724HC



GMR814HC

Part No.	Description	Weight (lbs.)
*GMR614HC	3 Point Hydraulic - designed for 5–10 gpm @ 1500–3000 PSI hydraulic systems. (includes hoses) (use 6"–14" augers)	180
*GMR624HC	3 point Hydraulic - designed for 10–20 gpm @ 1,500–3,000 PSI hydraulic systems. (includes hoses) (use 6"–24" augers)	182
*GMR714HC	Loader Hydraulic - designed for 5–10 gpm @ 1500–3000 PSI hydraulic systems. Bolt-on Side Plate (less hoses) (use 6"–14" augers)	125
*GMR724HC	Loader Hydraulic - designed for 10–20 gpm @ 1,500–3,000 PSI hydraulic systems. Bolt-on Side Plate (less hoses) (use 6"–24" augers)	127

\* No auger included

# Post Hole Diggers



## Hydraulic Post Hole Diggers *Skid Steer & Euro Global*

Increase your reach over shrubs, fence lines and other obstructions with a skid steer mounted 914HC/924HC hydraulically driven digger. Great time saver with exceptional up-front visibility and control.

**FEATURES**

- “Universal” skid steer mount.
- Hydraulically driven.
- For tractor front loaders with “Universal” skid steer mount.
- Handles augers with 2" inside diameter opening.
- No hoses included.
- Hydraulic operation allows user to reverse the auger to clear obstructions.
- Counter weight provides constant balance for true vertical holes.



GMR914HC



GMR924HC

Part No.	Description	Auger Size	Required GPM/PSI	Weight (lbs.)
*GMR914HC	Universal Skid Steer Mount Hydraulic without auger, less hoses	6"- 14"	5-10 GPM @ 1,500-3,000 PSI	208
*GMR924HC	Universal Skid Steer Mount Hydraulic without auger, less hoses	6"- 24"	10-20 GPM @ 1,500-3,000 PSI	210
*GMR924HC/EURO	For tractor loaders with the Euro/Global bucket quick-attach system	6" - 24"	10-20 GPM @ 1,500-3,000 PSI	220

\* No auger included

# Augers & Options



## Post Hole Digger Augers

Part No.	Description	GMR 500	GMR 720	GMR 925	HC Models	Weight (lbs.)
GMR170585	6" Standard Duty Single Flight Auger w/teeth	●	●	●	●	20
GMR706150	6" Heavy Duty Single Flight Auger w/teeth	●	●	●	●	22
GMR706155	6" Heavy Duty Double Flight Auger w/teeth	●	●	●	●	32
GMR170710	9" Standard Duty Single Flight Auger w/teeth	●	●	●	●	28
GMR706109	9" Heavy Duty Single Flight Auger w/teeth	●	●	●	●	37
GMR706009	9" Heavy Duty Double Flight Auger w/teeth	●	●	●	●	47
GMR170720	12" Standard Duty Single Flight Auger w/teeth	●	●	●	●	32
GMR706112	12" Heavy Duty Single Flight Auger w/teeth	●	●	●	●	46
GMR706012	12" HD Double Flight Auger w/teeth	●	●	●	●	54
GMR706033	14" Heavy Duty Single Flight Auger w/teeth	●	●	●	●	62
GMR706037	14" Heavy Duty Double Flight Auger w/teeth	●	●	●	●	76
GMR706070	18" Heavy Duty Double Flight Auger w/teeth	●	●	●	●	98
GMR706075	24" Heavy Duty Double Flight Auger w/teeth	●	●		●	128



All augers are 2" ID round with 42" useable fighting length.



GMR170705



GMR170430



GMP706021



GMR170802

Part No.	Description	GMR 500	GMR 720	GMR 925	HC Models	Weight (lbs.)
GMR170705	12" Auger Extension w/guard	●	●	●	●	16
GMR170430	Bolted Fish Tail Centre Point	●	●	●	●	4
GMP706021	Red Claw Digger Teeth - Heavy Duty Cutting Edge 9-24"					
GMR170802	Fishtail Auger Point (Threaded)					

# Hydraulic Post Drivers



## Hydraulic Skid Steer Mounted Post Driver *HPD16HSS*

Model HPD-16 HSS is hydraulic, this combination makes transport simple, enables maneuverability into areas not accessible with a tractor while increasing operator productivity and skid steer versatility.

Manual Adjust	GMRHPD16HSS
Max. Post Size	5" x 9'
Impact at Full Stroke	32,000 lbs.
Impact at Half Stroke	16,000 lbs.
Mount Type	Skid Steer
Tilt Adj. Front/Back	17° each way
Tilt Adj. Side/Side	20° each way
Manual Adjust	No
Hydraulic Adjust	Yes
Adj. Cylinders/Size	(2) 3" x 6"
Stabilizer Legs	Standard
Big Foot	Yes
Slide Blocks Material	Nyrim
Spring Post Holder	Standard
Min. Hydraulic Req.	3-4 GPM
QuickChange Rod Seal	Yes
Q-springs	N/A
Valve(s)	Sgl./Dbl. Spool
Hoses less couplers	Standard
Weight (lbs.)	950



## Hydraulic Adjust, 3 Pt. Hydraulic Post Driver *Handles posts 5" x 9'*

Designed and engineered for those who have serious fencing to do. These center mounted units offer all the quality features of the basic HPD16 plus effortless hydraulic driver alignment controlled by two 3" x 6" hydraulic cylinders. Big-foot stabilizer helps control tractor bounce on these larger units.

Part No.	Description	Weight (lbs.)
GMRHPD16SHC	Hydraulic Adjust, 3 Pt. Hydraulic Post Driver	875

Hydraulic Adjust	GMRHPD16SHC
Max. Post Size	5" x 9'
Impact at Full Stroke	32,000 lbs.
Impact at Half Stroke	16,000 lbs.
Mount Type	3-pt. Cat I/II
Tilt Adj. Front/Back	17° each way
Tilt Adj. Side/Side	20° each way
Manual Adjust	No
Hydraulic Adjust	Yes
Adj. Cylinders/Size	(2) 3" x 6"
Stabilizer Legs	Standard
Big Foot	Yes
Slide Blocks Material	Nyrim
Spring Post Holder	Standard
Min. Tractor Size	20-22 hp
Rear Hitch Category	Cat. I or II
Min. Hydraulic Req.	3-4 GPM
QuickChange Rod Seal	Yes
Q-springs	N/A
Valve(s)	Sgl./Dbl. Spool
Hoses less couplers	Standard
Weight (lbs.)	875



# Hydraulic Post Drivers




## Manual Adjust, 3 Pt. Hydraulic Post Driver *Handles posts 5" x 9'*

The HPD-16 model with manual adjust quickly delivers a tight post set for wood or steel posts. Base model offers manual adjustment cranks and bubble level for perfect vertical alignment on flatland or hillsides. Transport lock pin secures unit for travel and storage. Greaseable pivot points provide reliable movement of the driver.

Part No.	Description	Weight (lbs.)
GMRHPD16	Manual Adjust, 3 Pt. Hydraulic Post Driver	600

Manual Adjust	GMRHPD16
Max. Post Size	5" x 9'
Impact at Full Stroke	32,000 lbs.
Impact at Half Stroke	16,000 lbs.
Mount Type	3-pt. Cat I/II
Tilt Adj. Front/Back	10° each way
Tilt Adj. Side/Side	17° each way
Manual Adjust	Yes
Stabilizer Legs	Standard
Slide Blocks Material	Nyrim
Spring Post Holder	Standard
Min. Tractor Size	20-22 hp
Rear Hitch Category	Cat. I or II
Min. Hydraulic Req.	3-4 GPM
QuickChange Rod Seal	Yes
Q-springs	N/A
Valve(s)	Sgl. Spool
Hoses less couplers	Standard



GMR814490



GMR815130

Part No.	Description
GMR815130	Post Holder Assembly. Fits WorkSaver Hydraulic Post Drivers Previously Manufactured Without Post Holders. Spring Loaded, Holds Post In Position Until Post Is Started. Not For "T" Posts.
GMR814490	Holder for Steel T Posts



# HAY & BALE HANDLING EQUIPMENT

- BALE SPEARS
- BALE CLAMPS
- BALE SPINNERS
- BALE UNROLLERS
- HAY RAKES

## Bale Spears




### Bucket Bolt-on or Clamp-on Bale Spears *Tapered forged bolt-in steel spears.*

#### STANDARD FEATURES

- Quickly convert your front loader bucket into a tool for handling large round bales.
- Each spear mounts on the bucket cutting edge with heavy angle iron for additional support and utilizes the bucket underside for leverage.
- The bolt-on or chain system is used to firmly lock the spear on the bucket.
- Units use tapered "forged" bolt-in steel spears.

*Note: Bale spears are to be inserted into bales.  
Do not use spears as forks.*




Part No.	Description	Weight
HAYBBSF-20	Bolt-on Bucket Bale Spear for round bales. Rated at 2,000 lbs. Bolt-in spear has useable length of 42". Requires drilling one 17/32" diameter hole in the bucket. Bolt-together design.	65 lbs.
HAYCBSF-2000	Clamp-on Bucket Bale Spear for round bales. Rated at 2,000 lbs. Uses chain and turnbuckle system. Bolt-in spear has useable length of 42". Bolt-together design.	76 lbs.
HAYCBSF-2028	Clamp-on Bucket Bale Spear for round bales. Rated at 3,000 lbs. Uses chain & turnbuckle system. Bolt-in spears have useable length of 42".	102 lbs.

### Integrated-Frame Design Bale Spears *Features all welded frame!*

#### STANDARD FEATURES

- All welded frame incorporates interfacing quick-attach brackets for John Deere loaders.
- All models utilize durable bolt-in forged spears.
- All models designed for handling round bales.

*Note: Do not exceed weight lifting capacity of your loader.*



Integrated-Frame Design for John Deere loader models: 620, 640, 720, 721, 725, 726, 740 and 741		
Part No.	Description	Weight
HAYJDBS-623	Dual bolt-in forged spears spaced 30" apart, with useable length of 42". Rated at 3,000 lbs.	196 lbs.



# Bale Spears

## 3 Point Bale Spears *Designed to mount to Category I, II & III*

### STANDARD FEATURES

- Designed, depending on model, to handle up to 3,000 lb. bales.
- Features forged spring steel spears designed for hard center bales allowing easier spear penetration of and withdrawal from bale(s).

*Note: Bale spears are to be inserted into bales.  
Do not use spears as forks.*



HAYBSF-1523

Part No.	Description	Weight
HAYBSF-1523	3-pt. spear for handling round bales up to 1,800 lbs. Tapered main spear has useable length of 44" with two welded balance spears. Fits Cat I/II hitches (shipped with 7/8" pins).	57 lbs.
HAYHS-2200	Rated for round bales up to 2,200 lbs. Bolt-in forged spear with 42" useable length. Two welded balance spears. Cat. I/II Quick Hitch compatible (shipped with 7/8" pins).	72 lbs.
HAYHS-3000	Dual bolt-in forged spears with 42" useable length. Spears are spaced 26" apart allowing bale to be picked up & not lose its orientation. Rated at 3,000 lbs. Fits Cat I/II Quick Hitches (shipped with 7/8" pins).	105 lbs.
HAYDBH-6000	Four bolt-in spears (usable length 42"), square frame design allowing transport of two 5-ft or 6-ft diameter round bales at once. Rated at 6,000 lbs. Overall unit width 76". Fits Cat. II/III Quick Hitches. Item #834100	295 lbs.



HAYHS-2200



HAYHS-3000



HAYDBH-6000

# Bale Spears



## Front Loader Bale Spears

### STANDARD FEATURES

- Designed for use on tractor front loaders or most popular quick-attach front loader systems using our optional interfacing brackets.
- Features an all welded frame, cast steel weld-on spear sockets, and bolt-in spears for increased durability.

*Note: Do not exceed weight lifting capacity of your loader.*



HAYFLBS-2200

Part No.	Description	Weight
HAYFLBS-2200	Loader Bale Spear rated at 2,200 lbs. Unit has a tapered spear with a useable length of 42". Designed for use on tractor front loaders. Optional interfacing brackets for most loader quick attach systems are available. (will not accept 831110 brackets). Instead of 831110 brackets, consider SSB-2200.	121 lbs.
HAYFLBS-3000	Loader Bale Spear rated at 3,000 lbs. Unit has Dual tapered spears with a useable length of 42". Designed for use on tractor front loaders. Optional interfacing brackets for most loader quick attach systems are available. (will not accept 831110 brackets). Instead of 831110 brackets, consider SSB-3000.	136 lbs.
HAYFLBS-330	Loader Bale Spear rated at 3,000 lbs. Unit has three tapered spears spaced 26-1/2" apart with a useable length of 26". For mid-size square bales. Designed for use on tractor front loaders. Optional upright kit (831095) for handling two bales. Optional interfacing brackets for most loader quick attach systems are available. Instead of 831110 brackets, consider SSRB-330.	164 lbs.
HAYFLBS-449	Loader bale spear to handle Large-Sized square bales. Features 79-1/2" wide frame with four tapered spears with useable length of 42", spaced 24" apart. Optional upright kit (831095) for handling two square bales. Optional interfacing brackets for most quick attach systems are available. Item #832410,	212 lbs.



HAYFLBS-3000



HAYFLBS-330



HAYFLBS-449




# Bale Spears

## Euro/Global Integrated Frame Design Bale Spears *With Bolt-in Spears*

**STANDARD FEATURES**

- All welded frame design that incorporates the Euro/Global interface.
- Designed to fit tractor loaders with the widely used Euro/Global tool carrier.
- Features bolt-in forged spears for easy penetration of the bale.

*Note: Do not exceed weight lifting capacity of your loader.*



Part No.	Description	Weight
HAYGLB-2200	Single bolt-in forged spear with useable length of 42". Two balance spikes, 1" x 8-1/2" useable. For round bales. Rated at 2,200 lbs.	136 lbs.
HAYGLB-3000	Dual bolt-in forged spears spaced 30" apart, with useable length of 42". For round bales. Rated at 3,000 lbs.	152 lbs.
HAYELB-340	Triple bolt-in forged spears spaced 26" apart, with useable length of 42". For handling single or double large-size square bales. Rated at 4,000 lbs. Optional upright kit (831095) must be used when handling two bales.	200 lbs.
HAYGDBH-6000	Designed for tractor front loaders that use the Euro/Global quick-attach system. Transport two 6' diameter bales at once. Frame sizes 76" x 24" with 4-bolt-in spears with 42" useable length. Rated at 6,000 lbs.	265 lbs.



HAYELB-340



HAYGDBH-6000

# Bale Spears



## Skid Steer Bale Spears

### STANDARD FEATURES

- Designed for front loaders and skid steers using the industry standard “universal quick-attach” system.
- Unique step through design provides easy access to the skid steer.
- Bale spears are offered to handle large round bales as well as mid-size and large rectangular bales.
- Optional uprights allow handling of two rectangular bales at a time.
- All units utilize bolt-in “forged” spring steel tines for easy spear penetration of the bale.



*Note: Do not exceed weight lifting capacity of your loader.*

Part No.	Description	Weight
HAYSSB-2200	Skid steer single bale spear. Forged bolt-in spear with useable length of 42". Rated at 2,200 lbs.	129 lbs.
HAYSSB-3000	Skid steer dual bale spear. Forged bolt-in spear with useable length of 42". Rated at 3,000 lbs.	146 lbs.
HAYSSRB-340	Skid steer triple bale spear. Forged bolt-in spears spaced 26-1/2" apart, with useable length of 42". For handling single or double (with optional uprights HAY831095) large-size square bales. Rated at 4,000 lbs.	190 lbs.




# Replacement Bale Spears

HAYARSP32A  
HAYARSP39A  
HAYARSP49A  
HAYARSP49B



HAYARSP10



HAY832217

HAY831273

HAY830924

HAY830928

Part No.	Description	Weight
HAYARSP49A	3,500 lb. replacement spear & nut - 49" long	28 lbs.
HAYARSP49B	3,500 lb. replacement spear & nut - 49" long	28 lbs.
HAYARSP39A	3,500 lb. replacement spear & nut - 39" long	18 lbs.
HAYARSP32A	3,500 lb. replacement spear & nut - 32" long	16 lbs.
HAYARSP10	4-3/4" sleeve for Westward forged spear (2-3/8" OD x 1-5/8 iD)	-
HAYARSP09	Nut for Westward forged spear	-
HAYARSP09B	Nut for HAYARSP49B only (28 mm)	-
HAYARSP10B	Sleeve for HAYARSP49B only	-
HAY830928	2,200 lb. bolt-in replacement spear only. 47" long (42" useable length)	21 lbs.
HAY832217	2,200 lb. bolt-in replacement spear kit. Includes 47" spear, (42" useable length) sleeve and bolt. Weld in sleeve is 2-1/4" O.D. (Sleeve only part # HAY831069)	26 lbs.
HAY830924	2,200 lb. Bolt-in replacement spear only. 33-1/2" long (26-1/2" useable).	12 lbs.
HAY831273	2,200 lbs. Tapered forged Conus II replacement spear with nut. 49" long (44" useable length)	17 lbs.

# Fine Twine Cutter

*Cut twine, mesh, plastic wrap, feed bags, etc.*

This specially designed knife is the perfect tool to remove bale wrap once you're ready to use it. Because face it, while a pocket knife is great for quick cutting tasks, heavy duty net wrap or silage film can take a toll on your knives. This popular knife features a heavy blade and uses standard blades. Its 30-inch length means you won't have to get on the ground to cut open bales anymore. It also means it won't get lost.

- PROUDLY Made in the U.S.A.
- Has a durable handle and standard blades
- Loosen frozen or embedded twine
- Grip hay knife easily with work gloves on
- Uses replaceable standard utility knife blades
- 30" Length
- Reaches across 6' bales
- Safety close feature
- You'll lose 10 pocket knives before you lose this knife!



**NEW!**



Closed for safety



Twist to open

Part Number	Description
HAY83947	30" Fine Twine Cutter
HAY20302G	10 Pack, 2 Notch, Large Hook Replacement Blades



## Bale Spin Off



### 3 Point & Skid Steer Bale Spin Off

Designed as an efficient hay management tool for moving and feeding round bales, the RW Spin Off hydraulically rotates the bale, unwinding the hay into a windrow. Rotates in both directions for easy feeding and allows the operator to unroll what the cattle will clean up, eliminating wasted hay. Also, by changing the feeding location each day the operator can eliminate manure buildup.

Designed to fit Category II or Category III 3-pt hitches (FSO-906) and skid steers (SSSO908). All models are hydraulically driven for better operator control, provide easy operation from the cab of tractors or skid steers and feature a forged tapered spear for easier bale penetration. All have usable spear length of 53".



	HAYFSO-906	HAYSSSO-908
Frame Size	4" x 4" Sq. Tubing	3" and 4" Sq. Tubing
Spear	Tapered Forged	Tapered Forged
Drive		
Attaching Method	3-pt Cat. II/III**	Skid Steer "Universal"
Chain Type	#50 Roller Chain	#50 Roller Chain
Sprocket Ratio	3.75:1	3.75:1
Hydraulics		
GPM - Requirements	8-10 GPM	8-10 GPM
PSI - Requirements	Min. 1500 psi	Min. 1500 psi
Hoses	Supplied (2) Less Ends	Supplied (2) Less Ends
Cushion Valve		
Factory Settings - Relief	1750 psi	1750 psi
Dimensions		
Height	26-3/4"	23-1/4"
Width	44-3/4"	45-1/4"
Length w/Spear	64-3/4"	64-3/4"
Weight	250 lbs.	325 lbs.

\*\* Optional pin & bushing kit available to allow use on Cat. I 3-pt. hitch.

## Bale Clamps



### Bale Clamp, UBH-Series For wrapped (or dry) round bales

#### STANDARD FEATURES

- The "Bale Hand" will gently handle large round wrapped or unwrapped bales with weight up to 2,200 lbs.
- Provides smooth curved clamping arms to prevent wrapped bale puncture.
- This unit fits most double-cylinder front loaders with load arm distance of 54" or less.
- Optional pin-on brackets or interfacing brackets for most popular quick-attach front loaders are available with loader arm distance of 55" or less.

Part No.	Description	Weight
HAYUBH2072	"Bale Hand" Designed to handle 4' to 6' round bales, wrapped or dry, up to 2,200 lbs. Both arms open to clamp bale. Hydraulic cylinder included.	520 lbs.





# Bale Clamps



## Skid Steer Bale Hand *Designed for wrapped (or dry) round bales*

**STANDARD FEATURES**

- Gently handles large round wrapped or unwrapped bales.
- Features smooth curved arms to prevent wrapped bale puncture when clamping.
- Fits skid steer and front loaders with the “Universal” quick-attach system.



*Note: Do not exceed weight lifting capacity of your loader.*

Part No.	Description	Weight
HAYSSBH-2072	Skid Steer Bale Hand rated at 2,200 lbs., it is designed to handle 4-ft to 6-ft diameter round bales. Both arms open to gently clamp wrapped or unwrapped bales (less hoses).	572 lbs.

# Bale Unroller



## Bale Unroller

Feeding unrolled round bales allows the operator to relocate the feeding area, reducing manure buildup and providing ample space for livestock to “graze” naturally, ensuring that all are fed. Moving, loading, or unloading single stacked round bales from trailers or racks can all be done with this single tool built for multiple bale handling functions.

The HAYBH1 is designed for round bales either 4' or 5' in width and up to 6' in diameter weighing up to 2,000 lbs.


The HAYBH1 mounts on Category I, 3 point hitches. A standard 2" or 2 1/2" x 8" hydraulic cylinder is required (not included) (cylinder with 1" clevis type ends).



**SPECIFICATIONS**

- Length: 68"
- Width: 71"
- Height: 27"
- Weight: 310 lbs.
- Minimum point spread: 25"
- Maximum point spread: 76"
- 3 pt. hitch: Standard Category I
- Heavy steel construction.

Part No.	Description	Weight
HAYBH1	3 Pt. Bale Handler/Unroller	285 lbs.
HYD662293	2" x 8" Cylinder	15 lbs.
HYD662305	2 1/2 x 8" Cylinder	21 lbs.



## Hay Turning Spreader

**FAZA**  
 MACCHINE AGRICOLE

### STANDARD FEATURES

- Mounted hay-turning spreader pulley c/w PTO shaft
- Wheels: 16x650 - 8.6 PR
- Number of tines per arm: 4
- Number of arms per rotor: 11




Part No.	Length	Weight
GMRGF320	210 cm	175 kg.

## Replacement Hay Rake Wheels & Tines

### Rake Wheels

#### SPECIFICATIONS

- Centre Hole = 3 1/8"
- Bolt Hole = 5 1/4"
- Outer Ring (wheel without tines attached) = 32 1/2"
- Complete Rake O.D. = 55"
- QTY of bolt holes = 6



Part No.	Description	Weight
OTMH001	Rake Wheel (RH) Right Rake	38 lbs.
OTMH001L	Rake Wheel (LH) Left Rake	38 lbs.

### Rake Tine

#### SPECIFICATIONS

- Application Notes: Hesston, Jiffy, OTMA, New H&S, Faza
- Mfr Part #: OT-1A 7MM
- Wire Size: .281"
- Application: Hay Rakes
- Style: Straight
- OEM Part #: 203055, 565050, 700001825
- Type: Single
- Diameter: .281"
- Length: 6.5" x 11.5" x 15"



Part No.	Description	Weight
TINOT-1	Rake Tine OT-1A	0.5 lbs.


# Haysaver 3 Point Hay Rakes

**3 Pt. Hay Rakes** 2 Wheel, 3 Wheel or 4 Wheel models to choose from!




**STANDARD FEATURES**

- Faza Haysaver rakes are built of heavy solid steel tubing.
- Forged steel spoke hubs and conical roller bearings.
- Rake wheels feature tines with a larger gauge than the competition for longer life, while retaining maximum flexibility.
- Rakes take up minimal room in transport mode.
- Ultimate in reliability and performance.



	2 Wheel Rake	3 Wheel Rake	4 Wheel Rake
	HAY3P2	HAY3P3	HAY3P4
Number of Wheels	2	3	4
Number of Teeth Per Wheel	40	40	40
Wheel Diameter	55"	55"	55"
Tooth Diameter	9/32"	9/32"	9/32"
Mounting	3 point	3 point	3 point
Working Width	4'	6'3"	8'6"
Transport Width	4'11"	5'	7'3"
Operating Speed	14 mph	14 mph	14 mph
Minimum HP Required	20	20	30
Weight	187 lbs.	286 lbs.	407 lbs.



# Haysaver Pull-Type Wheel Rakes

**MODEL HAYCTH8** 8 Wheel Pull Type Rake **HAYCTH10** 10 Wheel Pull Type Rake

**FAZA**  
MACCHINE AGRICOLE

## STANDARD FEATURES

- 8 or 10–55" diameter raking wheels.
- 17'9" or 21' raking width.
- 9'6" transport width.
- 25 to 35 horsepower required.
- Unique cart design offers excellent flotation and ability to follow the contours of the field.
- Hydraulic cylinders and hoses supplied.
- Easily adjustable for different hay conditions and windrow widths.



*Hydraulic cylinders and hoses supplied.*

**EASILY ADJUSTABLE!**

Model	Diameter	Number Raking Wheels	Working Width	Tractor Req.	Weight	Transport Width	Speed	Tires
HAYCTH8	55"	8	17' 9"	25 hp	1,455 lbs.	9'6"	14 mph (22.5 kmh)	195/75-14
HAYCTH10	55"	10	21'	30 hp	1,631 lbs.	9'6"	14 mph (22.5 kmh)	195/75-14



*Hydraulic cylinders enable the closing device ensuring easy transportation.*

 **WESTWARD PARTS**

6517 - 67 St.  
Red Deer, AB T4P 1A3  
Fax: 1-800-661-4508

201 Henderson Dr.  
Regina, SK S4N 7E2  
Fax: 1-800-721-2977

1435 St. James St.  
Winnipeg, MB R3H 0W9  
Fax: 1-800-257-8338

Specifications subject to change without notice or obligation.

[www.westwardparts.com](http://www.westwardparts.com)

# LAWN & GARDEN EQUIPMENT

- 
- HAND-HELD SHAKERS
  - TOW SPREADERS
  - ATV SPREADERS
  - 3 PT. SPREADERS
  - FLIP-OVER DISCS
  - WOOD CHIPPERS
  - LAWN FERTILIZER



**WESTWARD PARTS**

# Spreaders

**Hand-held Shaker/Spreader** For year round use with ice melt, fertilizer, grass seed and most pelletized products.

**STANDARD FEATURES**

- 64 oz capacity and easy fill design
- Holds up to 4 lbs of product
- 3 shaker settings
- Easy-fill opening & comfortable handle
- Handle designed for use with winter gloves
- Sold individually - boxed in quantity of 6 units

Part No.	Description	Weight (lbs)
SPP8740A	Hand-held Shaker Spreader	0.85



# Spreaders



**GMRDMS-TR-12V-2.2** 145 lbs. ATV Dry Material Spreader - Tow

**STANDARD FEATURES**

- 2.2 Cubic Foot Poly Hopper.
- 12 Volt Motor With Variable Speed Control. (GMRVSC-10) & On/Off Switch.
- Stainless Steel Radial 6-Blade Fan.
- Holds up to 145 lbs of Potash or 99 lbs of Urea.
- Can be used with: Fertilizer, Seed, Bait, Powders, Granular, Insecticides, Fungicides, Herbicides, Pellets, Ice Melting Pellets.
- 5 to 45 Foot Variable Spread Width!



**5' - 45' Variable Spread Width!**



**GMRVSC-10**

GMRVSC-10 can also be purchased separately and works on all 12 volt High-Flo pumps.

Part No.	Mfr Part No.	Description	Weight
GMRDMS-TR-12V-2.2	5302028	ATV Dry Material Spreader - Tow (includes GMRVSC-10)	50 lbs.

# Spreaders



## GMRATV-DMS-12V 145 lbs. ATV/Truck Mount Dry Material Spreader

### STANDARD FEATURES

- 2.2 Cubic Foot Poly Hopper.
- 12 Volt Motor With Variable Speed Control (GMRVSC-10) & On/Off Switch.
- Stainless Steel Radial 6-Blade Fan.
- Holds up to 145 lbs. of Potash or 99 lbs of Urea.
- Can be used with: Fertilizer, Seed, Bait, Powders, Granular, Insecticides, Fungicides, Herbicides, Pellets, Ice Melting Pellets.
- 5 to 45 Foot Variable Spread Width!
- Optional receiver hitch available for truck mount.
- Optional rain cover available.

**APPROVED FOR:**

- FERTILIZER
- SEED
- BAIT
- GRANULAR
- INSECTICIDES
- FUNGICIDES
- HERBICIDES
- PELLETS
- ICE MELTING PELLETS



**Speed Control**  
GMRVSC-10  
5' TO 45'




### 5' - 45' Variable Spread Width!

Part No.	Description	Weight
GMRATV-DMS-12V	ATV Dry Material Spreader (includes GMRVSC-10)	50 lbs.

GMRVSC-10 can also be purchased separately and works on all 12 volt High-Flo pumps.

This ATV spreader is perfect for spreading seed, dry granular materials (fertilizers, insecticides, fungicides, herbicides), and ice melting materials. The spreader's variable speed 12 Volt motor allows you to vary the spread width from 5 to 45 feet. Easily cover sidewalks or parking lots with ice melt material or spread fertilizer over odd-shaped sections of lawn. An adjustable slide gate controls the amount of material thrown – open or close with the turn of a handle. The spreader features a 2.2 cubic foot poly hopper, 12 Volt motor with variable speed control, and stainless steel radial 6-blade fan. The frame and mounting brackets are constructed from steel. Holds up to 145 lbs. of potash or 99 lbs. of urea. Includes spreader, controller, wiring harness, mounting brackets, and hardware.



## OPTIONAL ACCESSORIES



**Speed Control**  
GMRVSC-10  
5' TO 45' Spread width.



**Rain Cover**  
GMR5058193



**2" Hitch**  
GMR5301901

ACCESSORIES	
Part No.	Description
GMRVSC-10	Variable Speed Control
GMR5058193	Rain Cover
GMR5301901	2" Receiver Hitch

# Spreaders



**GMRDMS-3PT-12V-4.5** 220 lbs. Dry Material Spreader 4.5 CU.

**STANDARD FEATURES**

- 4.5 Cubic Foot Poly Hopper.
- Stainless Steel Radial 6-Blade Fan.
- Holds up to 220 lbs of Potash.
- Can be used with: Fertilizer, Seed, Bait, Granular, Insecticides, Fungicides, Herbicides, Pellets, Ice Melting Pellets.
- 5 to 45 Foot Variable Spread Width!



Part No.	Description	Weight
GMRDMS-3PT-12V-4.5	Dry Material Spreader 4.5 CU.	90 lbs.



**LARGE POLY HOPPER**

- 4.5 CU FT Poly Hopper
- Holds Up To 220 Lbs Of Potash



**VARIABLE SPEED CONTROL**

- Control The Spread Width: 5 Feet To 45 Feet
- 20 Feet Of Wire Harness With Alligator Clips



**STAINLESS STEEL RADIAL FAN**

- 6 Blade Fan
- Stainless Steel



**ADJUSTABLE SLIDE GATE**

- Choose The Amount Of Dry Material To Spread
- Easy To Reach Handle



**CATEGORY 1 HITCH**

- Easily Connects To Your Category 1 Tractor Hitch





# Spreaders



**SPF5302957** 220 lbs. Dry Material Spreader 4.5 CU.

**STANDARD FEATURES**

- 2.2 CU FT Poly Hopper
- Holds Up To 145 Lbs Of Material
- 12V Motor w/ Variable Speed Control
- Control The Spread Width: 5 Feet To 45 Feet
- 20 Feet Of Wire Harness With Alligator Clips
- On/Off Switch
- Stainless steel 6 blade fan
- Adjustable slide gate
- Fits 2" Receiver on most ATVs and UTVs
- Rain / Dust cover included



Part No.	Description	Weight
SPF5302957	ATV/UTV Dry Material Spreader - Receiver hitch & dust cover included	60 lbs.



**COMPACT POLY HOPPER**

- 2.2 CU FT Poly Hopper
- Holds Up To 145 Lbs Of Material



**STAINLESS STEEL RADIAL FAN**

- 6 Blade Fan
- Stainless Steel



**12V MOTOR W/ VARIABLE SPEED CONTROL**

- Control The Spread Width: 5 Feet To 45 Feet
- 20 Feet Of Wire Harness With Alligator Clips
- On/Off Switch



**ADJUSTABLE SLIDE GATE**

- Choose The Amount Of Dry Material To Spread
- Easy To Reach Handle



**RAIN / DUST COVER**

- Protects Dry Materials From Adverse Elements
- Easy To Install And Securely Fitted



**2" RECEIVER ATTACHMENT**

- Fits 2" Receiver on most ATVs and UTVs
- Hitch pin included



# Spreaders




## GMRPT100 Broadcast Spreader, Commercial Type

### STANDARD FEATURES

- Spreading disc, moved by the wheels, has an adjustable spreading width from 1m to 6m (3–20 feet).
- Capacity of 100 liters, 0.13 cu. yards.
- Gear box is in oil bath aluminum.
- Weight (empty) 39 kg.



The trailed fertilizer spreader is a professional machine planned for working in parks, greenhouses, nurseries and little gardens. The spreading disc, moved by the wheels, has an adjustable spreading width from 1 m to 6 m.



Part No.	Description
GMRPT100	Broadcast Spreader

### Lever Extension


Part No.
OTMLEVEREXTENSION

# Spreaders - 3 Pt. Hitch

## Fertilizer Spreader *Steel hopper & tubular steel frame designed strong!*

### STANDARD FEATURES

- Three spreading patterns to select from.
- Operating levers used to obtain accurate and uniform spread in the desired direction.
- Spreading disc has four adjustable vanes.
- Maximum efficiency and uniform spread for different types of fertilizers and seeds.
- Weldless metal sheet used on hopper.



Three spreading patterns to select from using levers.



Spreading disc with four adjustable vanes ensures uniform spread.

Part No.	Hopper Capacity	Spreading Width	Spreading Speed	Weight with PTO Shaft	3 Point Hitch Category	Minimum HP Required
GMRFS150	330 lbs.	16'5" to 26'4"	2-10 mph	152 lbs.	1 or 2	8 to 10
GMRFS300	660 lbs.	16'5" to 26'4"	2-10 mph	163 lbs.	1 or 2	8 to 10
GMRFS500	1,100 lbs.	16'5" to 26'4"	2-10 mph	176 lbs.	1 or 2	8 to 10

### Agitator

Part No.
OTMDELUXEAGITATOR

# Discs



## GMRFOD-15 Flip-Over Single Gang Disc for ATV's

### STANDARD FEATURES

- Ideal pull type implement for garden tractors and ATV's.
- Great for tilling gardens, orchards or field game plots.
- Eight 16" notched disc blades.
- Transport wheels 4" x 12" pneumatic.
- Disc gangs are at 20° angle for optimum cutting.
- Rear tab for drag harrow attachment.
- Minimum horsepower 16 HP or 350cc.
- Axle 1" square.
- Cast iron bearings with grease zerks.
- Overall width 53".
- Overall height 35".
- Overall length 70" (w/tongue).



Part No.	Description	Weight
GMRFOD-15	5' Disc Complete	240 lbs.



*Flip-over disc incorporates a square weight frame in its design which allows the operator to strap 3 concrete blocks to the top of the disc, increasing its weight for more aggressive soil penetration.*

# Lawn Fertilizer

## MIS16-10-3-17-3 - with phosphate Ground Keeper Lawn Fertilizer

### INGREDIENTS

- 16% Nitrogen: Your lawn's major requirement for overall growth and development.
- 10% Phosphate: Essential for healthy roots and shoots and critical for photosynthesis.
- 3% Potassium: Like a radiator, creates tolerance to climate conditions, grass hardness.
- 17% Sulphur: Aids in maintaining dark green color and correlates with Nitrogen addition.
- 3% Iron: Necessary for chlorophyll reaction contributes to green coloration of lawn.

Only available by the skid (80 bags) or 1/2 skid (40 bags).

Part No.	Description
MIS16-10-3-17-3	Ground Keeper with Phosphate

BUY THIS,  
WATER THIS,  
BE IMPRESSED!  
(WE AND YOUR LAWN  
THANK YOU!)



 Canadian owned,  
Canadian made.



# Wood Chippers

## 3 Pt. Wood Chipper *BWC Series*

The Tar River Wood Chipper is the perfect tool to help you clear your land of fallen limbs and branches. Use your wood chips to create beautifully covered flowerbeds and natural areas in the yard. Wood chips not only look nice, but they also help regulate soil temperature, retain moisture and even improve plant growth by helping release necessary nutrients into the soil.

### STANDARD FEATURES

- 4 Reversible Blades Made with Hardened Tool Steel
- Shear Pin PTO protection
- 360° Exit Chute
- Gravity-Feeding Hopper
- Quick-Hitch compatible



	GMRBWC-040EC
Diameter Chipping Capacity	4"
Feed	Self-Feed
HP	18-50
Oversized Chipper Wheel	23.5" / 72 lbs.
Discharge Hood Height	59"
Exit Chute Rotation	360°
PTO Protection	Shear-Pin
PTO RPM	540
Weight (lbs)	434 lbs.



## **WESTWARD PARTS**

6517 - 67 St.  
Red Deer, AB T4P 1A3  
Fax: 1-800-661-4508

201 Henderson Dr.  
Regina, SK S4N 7E2  
Fax: 1-800-721-2977

1435 St. James St.  
Winnipeg, MB R3H 0W9  
Fax: 1-800-257-8338

Specifications subject to change without notice or obligation.

# MATERIAL MOVEMENT



- PALLET FORKS
- BUCKET TOOTH BAR
- REAR BLADES
- SNOW BLADES
- LANDSCAPE RAKES
- BOX SCRAPERS
- QUICK HITCHES
- ROTARY BROOMS



**WESTWARD PARTS**

# Grapples



## Electric Sub-Compact Grapple Rake

No auxiliary hydraulics to operate the clamp on a grapple? No problem with WorkSaver's (patent applied for) Electric Sub-Compact Grapple. All you need is a connection to the battery. Engineered for Sub-Compact tractors (up to 32-hp) with a loader to handle debris & so much more. The ESCG-48S is opening up possibilities never before available to large and small property owners.

Now that's the perfect attachment for your tractor!

### STANDARD FEATURES

- 12-volt linear actuator with 8-inch stroke operates the grapple clamp
- Includes wiring harness for direct connection to the tractors' battery
- Pre-wired rocker switch controls the grapples' linear actuator
- Designed for sub-compact tractors up to 32 horsepower



ELECTRIC SUB-COMPACT GRAPPLE RAKE SPECIFICATIONS	
	GMRESCG-48S
Overall Width (in/mm)	49 / 1245
Mount Type	Skid Steer
Overall Height Closed (in/mm)	41.5 / 1054
Grapple Opening (in/mm)	31 / 787
Upper Grapple Width (in/mm)	28.25 / 718
Lower Grapple Width (in/mm)	49 / 1245
Tine Spacing (in/mm)	9.25 / 235
Number of Tine/Grapple (lower/upper)	6 / 3
Type of Linear Actuator	12-volt, IP65 Rated
Actuator Stroke (in/mm)	8 / 203
Weight (lbs/kg)	247 / 112



**No Auxiliary  
Hydraulic Required**



12-volt industrial actuator with 8-inch stroke, slip clutch protected for dependable operation.



Rocker switch allows the operator to control grapple movement with the touch of a finger.



Heavy Duty power connectors with soft shell boot protector are standard.



# Grapples

## ETG Series Tine Grapple

### STANDARD FEATURES

- Unique upper grapple design on single clamp units provides clamping force to hold material securely.
- Recommended power unit size 30-55 HP.
- Greaseable pivot points on upper grapple(s) for long service life.
- Low profile design offers great forward visibility.
- Shield plate on upper grapple provides protection for hydraulic cylinder(s).
- Hoses are routed through the tube to provide hose protection on the ETG-26 models.
- ETG-26 with dual upper grapples for additional clamping is offered with Skid Steer mount, Euro/Global mount and John Deere 400/500 mount.



FORKS SPECIFICATIONS	
	GMRETG-26JD
Overall Width (in/mm)	71.75 / 1822
Overall Depth (in/mm)	35.5 / 901
Inside Depth (in/mm)	28.5 / 724
Overall Height (in/mm)	25.5 / 648
Grapple Opening (in/mm)	34 / 864
Upper Grapple Width (in/mm)	20 / 508
Number of Upper Grapples	2
Number of Tines	8
Tine Spacing (in/mm)	10 / 254
Cylinder Pressure Rating (psi/bar)	3000 / 207
Mounting Type	"Universal" Skid Steer
Horsepower Range	30 – 55 HP
Weight (lbs/kg)	525 / 238

# Sweep Action Rock Grapple

### STANDARD FEATURES

- The front hydraulically controlled grapples with their spring and hinge design operates with a sweeping action to pull rocks and debris into the unit.
- The springs hold the front sweep rakes open until the rear part of the grapple is down. Then the front rakes pull the material into the bucket.
- Grapple design retains the rocks or debris, allowing the operator to pivot the attachment to sift loose dirt out. Through the tube hose routing provides protection for the hoses, and flat-face couplers make hook up a breeze. Rocks, brush, logs, stumps, debris or scrap, the SARG handles them all.
- Bolt-on side plates hold smaller rocks in the bucket. They can be removed from the bucket to allow the SARG to handle logs and stumps.



	GMRSARG-72	GMRSARG-84
Overall Width (in/mm)	72 / 1829	84 / 2134
Bucket Depth (in/mm)	34 / 864	34 / 864
Upper Grapple Width (in/mm)	34 / 864	40 / 1016
Length of Sweep Clamp (in/mm)	21 / 533	21 / 533
Degrees of Sweep	66	66
Grapple Opening (in/mm)	45 / 1143	45 / 1143
Cylinder Size (in/mm)	2 x 14 / 51 x 356	2 x 14 / 51 x 356
Tine Diameter (in/mm)	1.25 / 31.75	1.25 / 31.75
Removeable End Plates	Standard	Standard
Bolt On Cutting Edge	N/A	N/A
Mount Type	Universal Skid Steer	Universal Skid Steer
Weight (lbs/kg)	1194 / 542	1375 / 610

*WARNING: Read and understand the operator's manual before operation. Be sure tractor/skid steer is properly counterbalanced. Damage to equipment or personal injury could occur.*

## Bucket Tooth Bar

**Bucket Tooth Bar** *Bucket not included*



### STANDARD FEATURES

- Designed to fit 60" bucket.
- Installs easily in minutes
- Requires no drilling of holes in bucket
- Fits most common loader buckets
- Increases effectiveness of front loader buckets
- Teeth made of A572 Grade 50 steel
- No. of teeth: 7



Part No.	Description	Weight (lbs)
GMRTB60	Tooth Bar for 60" bucket	53

## Pallet Forks

**Sub Compact Pallet Forks**

### STANDARD FEATURES

- Fits Loaders w/Skid Steer Mount <35 hp
- Features Class I solid alloy steel forks, 42-inches in length
- SS models are "universal" skid steer mount
- Rated at 1,250 lbs.
- Spring loaded latches for easy adjustment spacing



FORKS SPECIFICATIONS	
	GMRSSPF-1242
Equipment Used On	Loaders w/Skid Steer Mount <35 hp
Weight Capacity	1,250 lbs / 567 kg
Frame Construction	Welded Steel
Overall Width	44.125"
Overall Height	21.5"
Fork Carrier	Notched Rail
Forks	1.18" x 3" x 42"
Weight	245 lbs / 111 kg




# Pallet Forks

## 3-Point Pallet Forks *Quick Hitch Compatible*



### STANDARD FEATURES


These 3 Point Forks are ideal for picking up and moving pallets and bins. Models 1200, 1500 and 2000 are equipped with Category 1, 3-point hitches and 41" length non-adjustable tines and available in 1,200-pound, 1,500-pound, and 2,000-pound capacities. Model 1500-A forks are equipped with 41" length adjustable tines and available in 1,500-pound capacities. Model 3500 forks are equipped with ITA Class II forks and a Quick Hitch compatible Category 1 and 2, 3-point hitches. Fork tines are adjustable from 10" to 36" center to center. The 3,750-pound capacity fork tines are available in 42" and 48" lengths.



GMR1200

### 3 POINT PALLET FORK SPECIFICATIONS

Models	Lift Capacity	Fork Length	Tine Size	Fork Centers	Weight
GMR1200	1,200 lbs.	41"	2" x 4" x 3/16" Tubing	25"	115 lbs.
GMR1500	1,500 lbs.	41"	1" x 4" Solid	25"	160 lbs.
GMR2000	2,000 lbs.	41"	1-1/4" x 4" Solid	25"	180 lbs.
GMR1500A	1,500 lbs.	41"	1-1/4" x 4" Solid	Adjustable 4" to 26"	300 lbs.
GMR3542	3,700 lbs.	42"	1-3/8" x 4" Solid	Adjustable 10" to 36"	300 lbs.
GMR3548	3,700 lbs.	48"	1-3/8" x 4" Solid	Adjustable 10" to 36"	300 lbs.



GMR1500



GMR1500-A



GMR3500

## Mini Skid Steer Pallet Forks

### STANDARD FEATURES

Pallet forks designed for Mini Skid Steers/Compact Tool Carriers. These tools elevate the professional's productivity while offering the large property owner increased flexibility. Model MPF-900 features forks that are 1"x3"x31.5" mounted on a frame that is 30.5" wide with a rated unit capacity of 900 lbs. Model MPF-2000 (rail style) utilizes Class I tines (1.18"x3"x42") mounted on a frame that is 33.25" wide with a rated capacity of 2,000 lbs.



Part No.	Description	Weight
GMRMPF-1200	Pallet forks rated at 1,250 lbs. for Mini Skid Steer	178 lbs.

# Pallet Forks



## Universal Pallet Forks

### STANDARD FEATURES

- Fits many popular loaders.
- Equipped with a high visibility load guard and adjustable forks.
- Fork tines are constructed of Boron Steel and heat treated.
- All models are equipped with adjustable forks.
- Fork tines available in 42" and 48" usable lengths (model dependent).

UNIVERSAL PALLET FORKS SPECIFICATIONS	
GMRPF-448	
Lift Capacity	4,000 lbs.
Fork Length	48"
Tine Size	1-1/4" x 4" solid
Adj. Fork Features	Standard
Loader Mounts	Fits many loader frames with arms up to 50" C to C
Fork Style	Rail
Weight	438 lbs.
*Requires loader brackets to attach to loader. Call Inside Sales with loader model for pricing and availability.	



Universal

## Pallet Forks To Fit Euro/Global

### STANDARD FEATURES

- Integrated frame pallet forks with Euro/Global quick attach.
- Equipped with a high visibility load guard and adjustable forks.
- Fork tines are constructed of Boron Steel and heat treated.
- All models are equipped with adjustable forks.

GLOBAL PALLET FORKS SPECIFICATIONS		
	GMRGLPF-448	GMRGLPF-5548
Lift Capacity	4,000 lbs.	5,500 lbs.
Fork Length	48"	48"
Tine Size	1 1/4" x 4"	1 1/2" x 4"
Adj. Fork Features	Standard	Standard
Loader Mounts	Euro/Global quick coupler tractor loaders	Euro/Global quick coupler tractor loaders
Fork Style	Rail	Rail
Weight	350 lbs.	393 lbs.



# Pallet Forks



## Pallet Forks To Fit John Deere Front Loaders

### STANDARD FEATURES

- Skid steer pallet forks (4,000 lbs. or 5,500 lbs.) are offered with a one piece backstop or a step through design for easy cab access and excellent visibility.
- Premium forks include spring loaded latches for easy adjustment spacing.
- Machined rails allow ease of fork spacing adjustment.



JOHN DEERE PALLET FORK SPECIFICATIONS			
	GMRJDPF-2000	GMRJDPF-5442	GMRJDPF-5448
Lift Capacity	4,000	4,000	5,500
Mounting	400 / 500 Series	400 / 500 Series	400 / 500 Series
Fork Spacing	6-40"	6-40"	6-40"
Fork Carrier	Beveled Notched Rail	Beveled Notched Rail	Beveled Notched Rail
Forks	1.375" x 4" w/Latch	1.375" x 4" w/Latch	1.57" x 4" w/Latch
Fork Length	42"	42"	48"
Weight	345 lbs.	359 lbs.	435 lbs.

## Skid Steer Pallet Forks

### STANDARD FEATURES

- Equipped with a high visibility load guard and adjustable forks.
- Fork tines are constructed of Boron Steel and heat treated.
- All models are equipped with adjustable forks.
- Fork tines available in 42" and 48" usable length.



SKID STEER PALLET FORKS SPECIFICATIONS			
	GMRSSPF-242	GMRSSPF-442	GMRSSPF-448
Lift Capacity	2,000 lbs.	4,000 lbs.	4,000 lbs.
Fork Length	42"	42"	48"
Tine Size	1" x 3" solid	1-1/4" x 4" solid	1-1/4" x 4" solid
Adj. Fork Features	Standard	Standard	Standard
Loader Mounts	Fits skid steer style quick couplers	Universal skid steer mount	Universal skid steer mount
Fork Style	Rail	Rail	Rail
Weight	280 lbs.	375 lbs.	395 lbs.



# Pallet Forks



## Sub-Compact Pallet Forks

### STANDARD FEATURES

- Class I solid alloy steel forks, 42-inches in length
- JD models are John Deere hook & pin style quick attach
- Rated at 1,250 lbs.
- Spring loaded latches for easy adjustment spacing
- Class I forks are 1.18" x 3" x 42" with the forks mounted to a 3/8" upper rail with 6-positioning notches, allowing the operator to find the fork spacing needed for the application.
- For sub-compact tractors up to 35 HP, these pallet forks are rated at 1,250 lbs. for large property owners and provide more productivity in a small package and offer strength without added weight for maximum lifting capacity.



Part Number	GMRJDPF-1242
Equipment Used On	JD Loaders with Hook & Pin Quick Attach
Weight Capacity (lbs/kg)	1,250 / 567
Frame Construction	Welded Steel
Overall Width	44.125 / 1121
Overall Height	21.5 / 546
Fork Carrier	Notched Rail
Forks	1.18" x 3" x 42"
Weight (lbs/kg)	237 / 108

# Manure Forks

## Manure Fork

### STANDARD FEATURES

- Designed for picking up manure, matted straw or other loose materials
- Use on Skid Steers and Tractor Front Loaders.
- Produces cleaner stalls with less physical effort.
- 66" & 72" models feature forged cranked tines.
- 50" & 60" models use straight tines of 1-1/8" alloy steel.
- Mount types: "universal" skid steer and John Deere hook & pin.



Part Number	GMRMF/S-50S
Overall Width (in/mm)	50 / 1270
Overall Depth (in/mm)	23.75 / 603
Overall Height (in/mm)	21.5 / 546
Upper Grapple Width (in/mm)	N/A
Upper Grapple	No
Useable Tine Length (in/mm)	20.8 / 528.3
Number of Tines	7
Tine Type	1-1/8" Alloy Steel
Mounting Type	Skid Steer
Weight (lbs/kg)	146 / 66
Tine Spacing (in/mm)	7.75 / 196.85

# Bucket Forks



## Clamp-On Bucket Forks *Clamp-On Bucket Forks*

### STANDARD FEATURES

Built to meet the demands of today's acreage owner. Sturdy construction provides outstanding performance over years of service. Easy on/off design offers the utmost in convenience when moving palletized materials.

- Mounts to most loader buckets without the use of tools – easy on/off design.
- Rated from to 1,000 to 4,000 lbs. Lift is limited by fork capacity or loader capacity, whichever is less.
- Usable fork length of 35 to 42 inches.
- Designed for handling palletized material only.
- “T” handle design saves time when clamping and unclamping forks.
- Each fork has a built-in stake pocket for a 2x4 to be installed as an upright backstop (recommended).
- Sturdy all steel welded construction.
- Completely independent – allows fork adjustment to any pallet width.
- Forks extend 14.5 inches under bucket, 8 inches inside bucket.
- Sold as a pair



	GMRBF-1000	GMRBF-2000	GMRBF-4000
Weight Capacity (lb/kg)	1,000/453.5	2,000/907	4,000/1814
Overall Length (in/cm)	49.5/126	56.5/143.5	56.5/143.5
Usable Tine Length (in/cm)	35/89	42/107	42/107
Tine Size (in/cm)	2x3/5x7.6	2x3/5x7.6	2x4/5x10
Weight (lb/kg)	78/35	102/46	191/87

# Skid Steer Attachments

## Skid Steer Plate *Universal Weld-on Attachment Plate*

### STANDARD FEATURES

Use these universal weld-on attachment plate to convert whatever you want to skid steer quick-attach. These units are manufactured to interface with most universal skid steer quick attach mounting.



Part No.	Description	Weight (lbs.)
GMRWSP	Standard duty weld-on plate - 1/4". Maximum Capacity 3,500 lbs.*	46
GMRWSP-HD	Heavy duty weld-on plate - 3/8". Maximum Capacity 5,000 lbs.	96
GMR832625	Euro/Global heavy duty weld-on plate - 5/16". Unit measurements are 44.50" x 19.84" Maximum Capacity 5,000 lbs.	95
GMR832630	Euro/Global Weld-on Kit. Individual left and right hand brackets.	36

\*Note: Maximum capacity is that of the adapter bracket. Do not exceed it or loader/tractor operating lift capacity. These are attachment carriers only. Do not use for back dragging.



GMR832625

GMR832630

# Skid Steer Attachments

## Skid Steer Adapters



These all welded designs feature plated handles, springs and lock pins. These adapters provide greater versatility to your choice of attachments. In addition, you can easily switch attachments between a skid steer loader and a tractor loader.

Part No.	Description	Weight (lbs.)
GMR832810	Kubota LA350/401/402/450/452/480/481/482/680/681/LB681/402/552/702 to skid steer adapter. Interfaces with Kubota loader models LA350, LA401, LA402, LA450, LA452, LA480, LA481, LA482, LA680, LA681, LA682 LB402, LB552, LB702, with pin-on buckets retained by 1" pins. Allowing the use of skid steer type attachments (shipped less pins). Max Capacity: 3,500 lbs.	110
GMR835150	Interfaces with Kubota models LA504, LA434 & LA534 allowing the use skid steer type attachments (shipped less pins).Max Capacity 1,500 lbs*	97
GMR832915	Kubota LA852 to skid steer adapter. Interfaces with Kubota loader model LA852 with pin-on bucket retained by 1-3/16" pins. Allowing the use of skid steer type attachments (shipped less pins). Max Capacity: 3,500 lbs.	105
GMR835130	Kubota LA240, LA243 to Skid Steer. Maximum Capacity 1,200 lbs.*	68
GMR835160	Kubota LA524 & LA525 Loader to Skid Steer Adapter. Interfaces with Kubota models LA524, LA525 allowing the use skid steer type attachments (shipped less pins). Mac Capacity: 1,500 lbs.	103
GMR832815	Fits John Deere 48/58 loaders with 1-1/4" pins (shipped less pins). Max Capacity 3,000 lbs.*	148
GMR831875	John Deere 145/146/148/158 to skid steer adapter. Max Capacity: 3,000 lbs.	125
GMR831980	John Deere 240/245 260/265 to skid steer adapter	165
GMR832650	John Deere 600/700 to skid steer adapter. Mac Capacity: 5,000 lbs*	140
GMR832620	John Deere 300/400/500 Series to Skid Steer. Maximum Capacity 4,000 lbs.*	132
GMR832631	Euro/Global to John Deere 600/700. Maximum Capacity 5,000 lbs.*	140
GMR835120	Kioti SL2410 to Skid Steer. Maximum Capacity 1,200 lbs.*	67
GMR835145	Mahindra Max 24L to Skid Steer. Maximum Capacity 1,500 lbs.	85



GMR832810



GMR835150



GMR832915



GMR835130

\*Note: Maximum capacity is that of the adapter bracket. Do not exceed it or loader/tractor operating lift capacity. These are attachment carriers only. Do not use for back dragging.



GMR835160



GMR832815



GMR831875



GMR831980



GMR832650



GMR832620



GMR832631



GMR835120



GMR835145

The Interfacing Quick-Attach Brackets Reference can be found online under the Resources Tab for all Skid Steer Adapters listed above.



# Skid Steer Attachments

## Skid Steer Adapters (Continued)

Part No.	Description	Weight (lbs.)
GMR831895	Massey Ferguson 232/236/832/838/1032 to skid steer adapter	148
GMR835250	New Holland 82LB, 84LB, 7614 Loader on NH Bidirectional Tractor to Skid Steer. Maximum Capacity 4,000 lbs.*	250
GMR835255	New Holland 82LB, 84LB, 7614 Loader on NH Bidirectional Tractor to Euro/Global. Maximum Capacity 5,000 lbs.	280
GMR835190	Loaders used on Versatile 160, 256, 276 & Ford 9030 Bidirectional Tractors to Skid Steer. Maximum Capacity 4,000 lbs.*	255
GMR832660	Univ. skid steer adapter for standard pin-on loaders, requires pin-on brt. set	144
GMR832655	Univ. skid steer adapter for compact pin-on loaders, requires pin-on brt. set	140
GMR832820	Fits IH 2250 & 2255 loaders with 1-1/8" pins (shipped less pins)	120
GMR835045	Euro adapter for standard pin-on loader bracket	146
GMR832550	Euro/Global to Skid Steer. Maximum Capacity 4,000 lbs.*	110
GMR835020	Skid Steer to Euro/Global. Maximum Capacity 4,000 lbs.*	145
GMR835080	3-pt. Hitch to Skid Steer Adapter	140
GMR835095	Skid Steer to Cat. I Quick Hitch. Interfaces with "Universal" Skid Steer attach, allows the use of non-PTO powered implements. Supplied with one set of adapter bushings. Additional bushings,	148



GMR831895



GMR835250



GMR835255



GMR835190



GMR832660



GMR832655



GMR832820



GMR835045



GMR832550



GMR835020



GMR835080



GMR835095

*\*Note: Maximum capacity is that of the adapter bracket. Do not exceed it or loader/tractor operating lift capacity. These are attachment carriers only. Do not use for back dragging.*

The Interfacing Quick-Attach Brackets Reference can be found online under the Resources Tab for all Skid Steer Adapters listed above.

# Trailer Mover - Skid Hitch

## Skid Steer Trailer Mover

This handy attachment allows you to quickly add a standard 2" trailer hitch receiver (not included) to your skid loader so you can move trailers around your farm yard with your skid steer.

Can also be used on any tractor loader with a universal skid steer plate.

Lightweight and easy to install and remove. It will fit right in your truck toolbox!

NOTE: 2" standard draw bar and ball hitch not included.

**NEW!**



Part No.	Description	Weight
GMR83884	Skid Steer Loader Skid Hitch	15 lbs.





# Trailer Mover



## Skid Steer Trailer Mover

To assist with moving and spotting standard ball type equipment. A 2" receiver tube with 5/8" hitch pin hole accepts a standard 2" mount which must be purchased separately. Models are available for Mini Skid Steer and Standard Skid Steer



Part No.	Description
GMR812440	Trailer Mover for Standard Skid Steers, universal skid steer mount. Features 2" receiver tube with 5/8" hitch pin hole. Maximum tongue weight / vertical lift capacity 2,500 lbs. Hitch Ball Mount not included.

## Cat 1 Light Duty Trailer Mover

Effortlessly transport gooseneck trailers, standard trailers, or agricultural wagons using this Light Duty Trailer Mover. This rear-mounted, 3-point hitch trailer mover allows you to relocate trailers without the need to elevate the landing gear.

Note: For moving unloaded/empty trailers ONLY. Do not exceed lift capacity of tractor.

### STANDARD FEATURES

- CAT 1 Tractor
- CAT 1 Quick Hitch
- 2" Hitch Receiver
- 2 5/16" Gooseneck Ball
- Load Rating: 3500 lbs




Part No.	Weight
GMR26-223	47 lbs. (no bushings)

## Standard Rear Blades

### RB-Series Blades *Designed for Cat. I or Cat. I Quick Hitch*

#### STANDARD FEATURES

- Designed for Category I or Category I Quick Hitch, these standard duty blades are ideal for the small acreage owner.
- The main frame consists of an all-welded mast and 3" x 3" square tubing.
- The RB-Series features mechanical offset and angle adjustment.
- Angle adjustment is done by simply removing a pin, angling the blade and reinstalling the pin.
- All models have a reversible cutting edge and are supplied with a parking stand for convenient storage.
- Available as an option are skid shoes to assist in cutting height adjustment to reduce the chance of surface damage during snow removal.



Part No.	Description	Weight
GMRRB-1272	6' standard rear blade	190 lbs.
GMRRB-1284	7' standard rear blade	206 lbs.


#### RB-SERIES SPECIFICATIONS

	RB-1272	RB-1284
Maximum hp	40 hp	40 hp
Frame Size	3" x 3"	3" x 3"
A-Frame	Welded Mast	Welded Mast
3-pt. Hitch	Cat. I	Cat. I
Moldboard Width	6'	7'
Moldboard Height	12"	12"
Moldboard Thickness	1/4"	1/4"
Cutting Edge – Reversible	1/2" x 6"	1/2" x 6"
Angle/Pivot	360°	360°
Angle Forward (degrees)	0, 15, 30	0, 15, 30
Angle Reverse (degrees)	0, 15	0, 15
Offset	12" R/L	12" R/L
Tilt	N/A	N/A
Parking Stand	Standard	Standard
Weight	190 lbs.	206 lbs.
Optional Item		
SK-5 Skid Shoes	Yes	Yes

## ATV Grader Blade

Durable, tow-behind grader blade lets you keep surfaces levels and well-kept using your ATV or UTV.

Part No.	Description
GMRBE-GBA5G	ATV Grader Blade





# Rear Blades

## MCRB-72 Economical 6' blade for tractors

### STANDARD FEATURES

- An economical 6' blade for tractors up to 35 hp, with Category I 3-pt. hitch.
- The MCRB-72 only offers mechanical angle adjustment.
- The main frame is formed with 3" x 2.5" channel; replaceable straps are used for the A-frame.
- The formed moldboard includes a 1/2" x 6" reversible cutting edge.




MCRB-72 SPECIFICATIONS	
Maximum hp	35 hp
Frame Size	3" x 2.5" Formed Channel
A-Frame	Bolted Straps
3-pt. Hitch	Cat. I
Moldboard Width	6'
Moldboard Height	12"
Moldboard Thickness	1/4"
Cutting Edge – Reversible	1/2" x 6"
Angle/Pivot	360°
Angle Forward (degrees)	0, 15, 30
Angle Reverse (degrees)	0, 15
Offset	N/A
Tilt	N/A
Parking Stand	N/A
Weight	186 lbs.
Optional Item	
GMRSK-5 Skid Shoes	Yes

Part No.	Description	Weight (lbs.)
GMRMCRB-72	6' Rear Blade	186

# Rear Blade Options

- Remove snow
- Level gravel
- Clean feedlots and barns
- Reduce blade damage
- Increase blade life
- Prevent gouging



SKID SHOES FOR REAR BLADES		
Model	SK-5	SK-8
Part No.	GMRSK-5	GMRSK-8
Used On	MCRB/RB Series	RBHD Series
Weight	9 lbs.	24 lbs.

# Heavy Duty Rear Blades



## RBHD-Series Blades *Designed for Cat. I or Cat. I Quick Hitch*

### STANDARD FEATURES

- Designed for Category I or Category I Quick Hitch, these standard heavy duty blades have the strength required to handle the tough jobs.
- The main frame consists of an all welded mast and 4" x 4" square tubing.
- The RBHD-Series features mechanical offset and angle adjustment.
- Angle adjustment is done by simply removing a pin, angling the blade and reinstalling the pin.
- The RBHD-6-T and RBHD-7-T utilize a 3-position tiltassembly that is easy to use.
- All models have a reversible cutting edge and are supplied with a parking stand for convenient storage.
- Available options are skid shoes to assist in cutting height adjustment to reduce the chance of surface damage during snow removal.
- Optional end plates provide a boxed area for grading.



3-position tilt assembly

### RBHD-SERIES SPECIFICATIONS

	RBHD-6	RBHD-7	RBHD-6-T	RBHD-7-T
Maximum hp	50 hp	50 hp	50 hp	50 hp
Frame Size	4" x 4"	4" x 4"	4" x 4"	4" x 4"
A-Frame	Welded Mast	Welded Mast	Welded Mast	Welded Mast
3-pt. Hitch	Cat. I	Cat. I	Cat. I	Cat. I
Moldboard Width	6'	7'	6'	7'
Moldboard Height	14"	14"	14"	14"
Moldboard Thickness	1/4"	1/4"	1/4"	1/4"
Cutting Edge – Reversible	1/2" x 6"	1/2" x 6"	1/2" x 6"	1/2" x 6"
Angle/Pivot	360°	360°	360°	360°
Angle Forward (degrees)	0, 15, 30	0, 15, 30	0, 15, 30	0, 15, 30
Angle Reverse (degrees)	0, 15	0, 15	0, 15	0, 15
Offset	12" R/L	12" R/L	12" R/L	12" R/L
Tilt	N/A	N/A	3 position	3 position
Parking Stand	Standard	Standard	Standard	Standard
Weight	275 lbs.	299 lbs.	306 lbs.	331 lbs.
Optional Items				
GMRSK-8 Skid Shoes	Yes	Yes	Yes	Yes
EP-40 End Plates	Yes	Yes	Yes	Yes

# Heavy Duty Rear Blades

**RB400 Series** Quick Hitch Compatible

**WAP WESTWARD PARTS**

Rear Blades are an ideal choice for landscaping, road maintenance, snow removal, feedlot cleaning, irrigation ditching and a wide range of additional uses to suit your needs. They feature rolled moldboards to keep material flowing and reversible heat-treated cutting edges that add to the life of the blade.



**STANDARD FEATURES**

- Cat 1 hitch.
- Quick hitch compatible.
- Available in 72", 84" & 96" widths.
- Clevis type Cat 1/Cat 2 hitch.
- Rolled-formed moldboard for excellent loading and unloading of soil.
- 5 forward and 5 reverse angle settings.
- 1/2" x 6" high carbon reversible cutting edge.
- Tough powder coat paint.

Part Number	GMRRB400-72	GMRRB400-96
Working Width	72"	96"
Hitch	Cat 1/Cat 2 Clevis	Cat 1/Cat 2 Clevis
Moldboard Height	16"	16"
Moldboard Thickness	1/4"	1/4"
Moldboard Cutting Edge	1/2" x 6" Reversible	1/2" x 6" Reversible
Moldboard Offset	24" left or right	24" left or right
Moldboard Tilt	16 degrees - 3 holes	16 degrees - 3 holes
Weight	503 lbs.	578 lbs.
Max Tractor HP	75	75
Parking Stand	Standard	Standard

# Snow Blades



## STANDARD FEATURES

- Ideal for residential or commercial snow removal. Use on driveways, parking lots, or other large areas.
- 7.5-ft. & 9-ft. models feature 5° lateral oscillation to allow blade to follow ground contours.
- Two trip springs for controlled break over in snow.
- Reinforced 21" or 27" high 10-gauge moldboards provide long service life.
- 3/8" x 6" cutting edge of 1044 steel.
- Blade locks for light grading of loose dirt or gravel.
- Step-through design allows for easy access to skid steer seat.
- Quick hook up on skid steers or front loaders equipped with "Universal" mounting plate.
- Blade angles right or left.
- Adjustable skid shoes of AR steel are 1/2" thick and rotate for long life.
- Select models integrate either the Euro/Global or John Deere 400/500 series mounting for easier hook up.
- Two bucket clamp-on models for compact tractors.
- SBFL models can be paired with optional brackets for most tractor loaders.
- Clamp-on Models for Tractors up to 35 HP, Max.
- 27-Series Snow Blade 7-1/2' and 9' for Skid Steer and Tractors w/ Loader 40 – 95 HP, Max.



Skid Steer Snow Blade



Clamp-on Snow Blade

## SNOW BLADE SPECIFICATIONS

	GMR SBS-27108A	GMR SBFL-2790A	GMR SBS-2790A	GMR SBS-2172	GMR SBC-2160
Overall width (in/cm)	108/274	90/229	90/229	72/183	60 / 152
Overall height (in/cm)	27/69	27/69	27/69	21/53	21 / 53
Moldboard Thickness	10-gauge	10-gauge	10-gauge	10-gauge	10-gauge
Cutting edge (in/mm) 3/8" x 6"/9.525 x 152.4	Standard	Standard	Standard	Standard	Standard
5° Lateral Oscillation	Standard	Standard	NA	NA	NA
Extension trip springs	2	2	2	2	2
Manual angle positions	NA	5	5	5	5
Width @ full angle	96/244	80/203	80/203	62/157	52 / 132
Mounting for Tractor Loader (SBFL)	NA	Brackets required*	NA	NA	Clamp-On
Mounting for Skid Steer (SBS)	"Universal" Skid Steer	NA	"Universal" Skid Steer	"Universal" Skid Steer	NA
Adjustable Skid Shoes	Standard	Standard	Standard	Standard	Standard
Horse power range	50-95 HP	40-80 HP	40-80 HP	<45 HP	<35 HP
Weight (lb/kg)	735/333	660/299	646/293	353/160	305/138
Front Loader Angle Hydraulic Kit	NA	Optional GMR360168	NA	NA	Optional
Skid Steer Angle Hydraulic Kit	Standard	NA	Optional GMR360165	Optional GMR360170	NA
Crossover Rel. Valve	Standard	Optional	Optional	Optional	Optional
Optional Top Deflector	360230	360227	360227	NA	360220
Opt. Sight Indicator	360235	360235	360235	360235	360235
Snow Blade Item No.	360070	360040	360800	360130	360280

\*Optional Interfacing Quick Attach brackets available for most popular loaders. Be sure tractor/skid steer is properly counter-balanced.

# Snow Pusher



## 20 Series Universal Skid Steer Attach

**STANDARD FEATURES**

- Models designed for Sub-Compact tractors up to 32 HP.
- Adjustable skid shoes of AR-400 material.
- End plates with gentle slope design.
- Models are available to fit “Universal” skid steer attaching system and John Deere hook & pin quick attach.
- Optional Pull-Back kit available for all models.
- Available in widths of 4' or 5' with either a ultra rubber edge or alloy steel cutting edge.
- CNC formed 11-gauge moldboard with formed 10-gauge back brace for strength and durability.



GMRSPS-2472R SPECIFICATIONS	
Overall Width (in/mm)	64 / 1626
Overall Height (in/mm)	21.5 / 546
Overall Depth (in/cm)	21 / 533
Moldboard Thickness	11-gauge
End Plate Thickness	7-gauge
Inside Angle Bracing	Yes
Rubber Cutting Edge	No
Alloy Steel Cutting Edge	Yes (3/8" x 4")
Skid Shoes of AR-400	Yes
Horsepower Rating	Up to 32 HP
Operating Weight of Power Unit	1,800 lbs. Max.

Part No.	Description	Weight (lbs.)
GMRSPS-2060M	5' Snow Pusher w/Metal Edge	180

## 24 Series Universal Skid Steer Attach



**STANDARD FEATURES**

- Engineered to fit compact tractors equipped with a front loader.
- Replaceable 1" x 6" reversible ultra rubber cutting edge is standard on “R” models.
- All models feature adjustable & reversible skid shoes of high abrasive resistance steel.
- Optional Pull-Back kit available for all models features 1' x 6" ultra rubber cutting edge.
- Models to fit loaders with “Universal” skid steer attaching system.
- HP rating: 25-40 HP

GMRSPS-2472R SPECIFICATIONS	
Overall Width (in/cm)	78.5 / 199.4
Overall Height (in/cm)	25.6 / 65
Overall Depth (in/cm)	26 / 66
Moldboard Thickness	10-gauge
End Plate Thickness (in/cm)	¼ / 0.635
Reinforced Endplates	Yes
Rubber Cutting Edge	Yes
Steel Cutting Edge	No
Adjustable/Reversible Skid Shoes	Standard
Horsepower Rating	25-40 HP
Operating Weight of Power Unit	3,500 lbs. Max.



Part No.	Description	Weight (lbs.)
GMRSPS-2472R	6' Snow Pusher w/Rubber Edge	430

# Box Scrapers



## Box Scrapers *Reversible Cutting Edge!*

### STANDARD FEATURES

- Radius formed 17" moldboard.
- Bucket depth of 21 $\frac{3}{4}$ ".
- 1/2" x 2 $\frac{1}{2}$ " straps.
- Reversible 1/2" x 6" cutting edge.
- Height adjustable scarifiers.
- 1/2" x 2 $\frac{1}{2}$ " heat-treated spring steel shanks.
- Replaceable heat-treated dimpled-on tips.
- Back fill blade.
- Ruggedly built, applicable for sit preparation, restoration projects or farm practices.
- Scarifier height can be adjusted to loosen the soil at a desired depth or raised out of the way.
- Reversible cutting edge to scrape material into the box area.
- Heavy duty back fill blade smoothly levels material.
- 3-position heat treated steel scarifier shanks are height ideal for leveling, finish grading, feedlots, outdoor arenas, back filling at building sites and so much more.



Part No.	Description	Scarifiers	HP Required	Weight (lbs)	Working Width (in/cm)	Hitch Category	Overall Depth (in/cm)
GMRSBX-4	4 ft. box scraper Cat 0/1 (3 shanks)	3	18-25	320	48/122	3	21.5/55
GMRSBX-5	5 ft. box scraper Cat I (4 shanks)	4	20-25	378	60/152	4	21.5/55
GMRSBX-6	6 ft. box scraper Cat I (5 shanks)	5	25-40	428	72/183	5	21.5/55
GMRSBX-7	7 ft. box scraper Cat I (6 shanks)	6	25-40	469	84/213	6	21.5/55
GMP341675	Replacement Tine						





# Cement Mixer

## Hydraulic Concrete Mixer *Universal Skid Steer Mount*

### STANDARD FEATURES

- All welded drum construction with internal paddles for uniform mixing and clean dumping.
- Compact, trouble free, long life design with few moving parts.
- Hydraulic motor drive for easy operation and low maintenance requirements.
- Five (5) cu./ft. capacity (1 bag mix).
- Perfect for fence posts, footings, sidewalls and hard to reach areas.
- Direct gearbox drive of drum.
- Welded main frame with “universal” skid steer mount allows easy access to the operators seat.
- Flow control valve allows easy control of speed of the mixer.
- All welded frame with store onboard parking stands for easy storage of the mixer when not in use.



GMRSS-590 SPECIFICATIONS	
Capacity:	Five (5) cu./ft. (1 bag mix)
Drum opening (in/cm):	20 / 51
Overall drum length (in/cm):	32 / 81
Drum construction:	Welded Steel
Drive system:	Hydraulic Direct thru Gearbox
Hydraulic Requirements:	Minimum 8 GPM
Hitch Requirements:	N/A
Drive ratio:	3.18:1
Shield PTO drive:	N/A
Flow Control Valve:	Standard
Connect Under Pressure Couplers:	Standard
Parking stands:	Standard
Shipping weight (lb./kg)	395 / 180

# Quick Hitches



## Category I, II & III Quick Hitches *Adjustable Quick Hitch*

### STANDARD FEATURES

WorkSaver Quick Hitches are built for fast, reliable and easy connection (or disconnection) of 3-pt. implements. These Quick Hitches are built to work with implements built to ASAE 3-pt. hitch standards (Cat. I, II, or III). All Quick Hitches feature high strength tubing for torsional strength. Over-center spring-loaded mechanism provides a positive lock yet easy release. A tapered top hitch point bracket allows for easier connection.

Part No.	Description	Weight (lbs.)
GMRQH-101	Category I - with adapter (up to 50 HP)	76
GMRQH-102	Category II - with adapter (up to 100 HP)	134
GMRQH-107HD	Category II HD - with adapter (up to 150HP)	160
GMRQH-103	Category III (up to 225 HP)	182
GMRQH-106N	Category III Narrow (up to 225 HP)	176
GMRQH-1023	Allows the use of the Cat. III implements on tractors with Cat. II hitches	185
GMR862500	Category I Adapter Bushing Kit	3
GMR862530	Category II Adapter Bushing Kit	2.2




GMRQH-101



GMRQH-1023



GMRQH-107HD



### Quick Hitch Specifications (inches unless noted)

Model	A	B	C	D	E	F	G
GMRQH-101	27.25	29.50	14.50 - 17.50	1.25	7/8	3/4	7/8" to 1-7/16"
GMRQH-102	32.75	36.25	14.88	1.25	1-1/8	1	1-1/8" to 1-7/16"
GMRQH-107HD	32.5	37.75	14.88	1.25	1-1/8	1-1/4	1-1/8" to 1-7/16"
GMRQH-103	38.5	42.75	19	1.25	1-7/16	1-1/4	Not Required
GMRQH-106N	33.25	37.5	19	1.25	1-7/16	1-1/4	Not Required
GMRQH-1023	38.5	42.75	19	1.25	1-7/16	1-1/4	Not Required



# Rotary Broom

## 3-Pt. Rotary Brooms

### STANDARD FEATURES

- Designed for use by contractors, municipalities, institutions, and farmers.
- 32 inch diameter convoluted brushes available in Poly (P) or both Poly and Wire (PW).
- All models available in 5-ft., 6-ft. and 7-ft. widths.
- Remove dirt, sand, gravel and trash from construction entrances, parking lots, bridges, driveways and sidewalks.
- Remove thatch and prepare turf for the growing season.
- Clean snow or leaves from streets, driveways, and building entrances.
- Excellent for general clean up before sealing or repairing pavement.
- Broom angles up to 30° right or left.
- Manual or hydraulic angle adjustment kits available (one is required).
- Height adjustment chains maintain an even operating position.
- Parking stands included as standard equipment.
- PTO driven 3-pt. tractor mount in 5-ft., 6-ft., & 7-ft. widths with 32" diameter brushes.
- Designed for Category I tractors with 1,000 lbs. or greater 3-pt. lift capacity. With bushings these models can be used on most Cat. II tractors.
- Double gearbox drive with patented top "T-shaft" for smooth power transmission and easy reversal of brush rotation.



3-PT. SPECIFICATIONS		
Part No.	GMRRMB-325P	GMRRMB-326PW
Overall Width (in/cm)	69 / 175	81 / 206
Brush Diameter (in/cm)	32 / 81	32 / 81
Sweeping Width (in/cm)	60 / 152	72 / 183
Width @ 30° Angle (in/cm)	53 / 135	64 / 163
Mounting System	3-pt. (Cat. I)	3-pt. (Cat. I)
Brush Material	Poly	Poly/ Wire
PTO RPM Range	540	5
Dirt Deflector	Optional	Optional
Weight (lbs/kg)	640 / 290	736 / 346

### ADJUSTMENT KITS (one is required)

Part Number	Description
GMR610702	Manual Angle Adjustment Kit for either skid steers or tractor 3-pt.
GMR610703	3-pt. Hydraulic Angle Adjustment Kit - includes cylinder & hoses less tips

# Rotary Broom



## Skid Steer Rotary Broom - Hydraulically Driven

### STANDARD FEATURES

- Designed for use by contractors, municipalities, institutions, and farmers.
- Hydraulically driven skid steer models in 5-ft., 6-ft., and 7-ft. widths with 32" diameter brushes.
- Variable flow control valve for optimum broom speed.
- Step-through mount design for easy in/out of skid steer cab.
- Optional electric solenoid hydraulic angle kit also offered
- Optional electrical wiring kits to connect (optional) electric solenoid control to most OEM skid steer auxiliary controls.
- 4.36/1 chain drive ratio provides job matched torque to get through tough conditions.
- 32 inch diameter convoluted brushes available in Poly (P) or both Poly and Wire (PW).
- Remove dirt, sand, gravel and trash from construction entrances, parking lots, bridges, driveways and sidewalks.
- Remove thatch and prepare turf for the growing season.
- Clean snow or leaves from streets, driveways, and building entrances.
- Excellent for general clean up before sealing or repairing pavement.
- Broom angles up to 30° right or left. Optional manual or hydraulic angle adjustment kits available.
- Height adjustment chains maintain an even operating position.
- Parking stands included as standard equipment.



### SKID STEER ROTARY BROOM SPECIFICATIONS

Part No.	GMRSSMB-325P
Overall Width (in/cm)	69 / 175
Brush Diameter (in/cm)	32 / 81
Sweeping Width (in/cm)	60 / 152
Width @ 30° Angle (in/cm)	53 / 135
Mounting System	Skid Steer
Brush Material	Poly
Hydraulic Motor Rating	16 GPM
Oil Flow Requirement (gpm/lpm)	12-30 / 45-114
Dirt Deflector	Optional
Weight (lbs/kg)	720/327

## **WESTWARD PARTS**

6517 - 67 St.  
Red Deer, AB T4P 1A3  
Fax: 1-800-661-4508

201 Henderson Dr.  
Regina, SK S4N 7E2  
Fax: 1-800-721-2977

1435 St. James St.  
Winnipeg, MB R3H 0W9  
Fax: 1-800-257-8338

Specifications subject to change without notice or obligation.

# TILLAGE EQUIPMENT

- ARENA GROOMERS
- CULTIVATORS
- HARROWS
- AERATORS
- RAKES
- PLOWS
- ROTOTILLERS



**WESTWARD PARTS**

# Harrows



**S3 Delta Harrows** *Typical applications, unlimited flexibility*

This product is good for customers who are looking for inexpensive terrain management options. In sizes most suitable for towing with ATV's or lawn tractors, this multi-tool can be easily customized by the user to agitate surfaces with three different levels of aggression.

The secret is in the design of the tine, which tackles contours and debris without bridging or plugging. Meanwhile, the tines accomplish a variety of improvements:

- Resurface roads and arenas
- Aerate and dethatch turf (lawns, pastures)
- Distribute and smooth animal droppings or mounds
- Incorporate chemical or moisture
- Prepare smooth seedbeds

**ALL-SEASON USE:**

**Spring:** stand matted foliage up to stimulate growth, loosen thatch and bunched debris, aerate lawns before feed & seed and then harrow afterwards to incorporate and increase germination speed, prep seed beds.


**Summer:** break up dry soil crusts or incorporate moisture, rake pastures or corrals regularly to scatter mounds and stimulate grass, lift longer grass before mowing, rake and smooth dirt or gravel paths and athletic fields.

**Fall:** shred dry leaves, aerate and dethatch lawns.

**Winter:** break up ice crusts and fluff or smooth snow on trails.



Flexible Two-Way design for optimum debris clearance.




Part No.	Description (W x L)	Tyne Size	Weight
GMR202130	4' x 4' Flexible Harrow	1/2"	95 lbs.
GMR202127	4' x 8' Flexible Harrow	1/2"	152 lbs.
GMR202160	6' x 4' Flexible Harrow	1/2"	129 lbs.
GMR202128	6' x 8' Flexible Harrow	1/2"	245 lbs.
GMR202161	8' x 4' Flexible Harrow	1/2"	150 lbs.
GMR202129	8' x 8' Flexible Harrow	1/2"	318 lbs.


\*Drawbar & Chain included.



**Heavy Action**  
Tynes stand at an aggressive 75° angle.



**Medium Action**  
Reversed, tynes have a lighter angle of action.



**Light Action**  
Turned over, resulting in a finer leveling effect.





**Dual Action**  
Front section heavy action, rear section levels.

# Harrows



## S3 Delta Harrows *Heavy Duty applications*

Standard Drawbar Style is the traditional industry choice. It features a flat bar onto which the sections are easily hooked with an "S" shaped connector. Quickly switch the section to aggressive or smoothing mode with this drawbar combination.



Part No.	Description (W x L)	Tyne Size
GMR24202163	4' x 8' Flexible Harrow	5/8"
GMR24202164	6' x 8' Flexible Harrow	5/8"

\*Drawbar not included.


# Harrows - Diamond

## GMRDH40 & GMRDH60 *Harrows - Diamond*

### STANDARD FEATURES

- 5/8" teeth.
- Great for pulling behind a quad or ATV.
- Perfect for conditioning horse paddocks.
- Use for weed control and final seedbed preparation.

Part No.	Description	Weight
GMRDH40	Diamond Harrow - 40" x 52" has 20 (5/8") teeth	62 lbs.
GMRDH60	Diamond Harrow - 60" x 52" has 30 (5/8") teeth	98 lbs.



### Replacement Teeth

Part No.	Description	Carton Quantity	Length	Thread	Thread Length
TIN58S	Short Shank Harrow Teeth	50 w/nuts	7-1/2"	9/16"	1-1/2"
TINX58S	Short Shank Large Harrow Teeth	50 w/nuts	8-1/2"	9/16"	1-1/2"
TIN58L	Long Shank Harrow Teeth	50 w/nuts	7-1/2"	9/16"	2"
TINX58L	Long Shank Large Harrow Teeth	50 w/nuts	8-1/2"	9/16"	2"

# Heavy Duty Disc Harrows

## DH 300 Series *Quick Hitch Compatible*

- Cat 1 hitch
- Quick hitch compatible
- Clevis hitch provides easy hook-up
- 3" square frame tube
- 3" square gang tube
- 3/8" thick bearing hangers with reinforcement
- 1" square, high carbon steel gang axles
- Self aligning sealed bearings
- 7 1/2" disc blade spacing
- Tough powder coat paint
- 18" notched or smooth disc blades




Part No.	GMRDH300-72	GMRDH300-84
Working Width	72"	84"
Hitch	Cat 1 Clevis Hitch	Cat 1 Clevis Hitch
Number of Blades	20	24
Disc Blade Size	18"	18"
Disc Blade Spacing	7 1/2"	7 1/2"
Disc Blade Type	Notched or Combination	
Weight	815 lbs.	900 lbs.
Frame Tube	3" Square	3" Square
Bearing Hanger	1/2" Plate Reinforced	
Bearing Type	Self-aligning, sealed bearings	
Gang Tube	3" Square	3" Square
Gang Axle	1" Square	1" Square
Angling	Front gang: 0, 7, 14, 21 degrees w/adjustment handle Rear gang: 0, 7, 14, 21 degrees w/adjustment handle	
HP Required	35	40

The Disc Harrow is an ideal choice for landscaping, food plotting, gardening, small acreage or general farm tilling. Front and rear gangs are easy to adjust with our built-in adjustment handle. The 7 1/2" disc blade spacing allows the blade to cut evenly over the ground. The 3" square tubing is heavy enough to pull an attachment behind the disc harrow to better level the soil.

# 3 in 1 Soil Conditioner

## SC Series

- 3 soil conditioning tools in 1 machine
- Heavy-duty 20" high clearance S-tines to penetrate and till up to 7" deep
- 7" sweeps standard - optional 1-3/8" reversible points - specify when ordering
- Spring loaded, 12" diameter rolling crumblers w/serrated bars angled to finish mulching the soil
- Tapered frame & crumbler permits traveling through vegetation without damage
- Ideal for nurseries, berry growers, orchards, vineyards & general cultivation work



*Quick Hitch Compatible*

Part No.	Working Width	No. of Shanks	Shank Size	Shank Clearance	Hitch	HP	Weight
GMRSC6	6'	11	1/2" x 1-3/4"	20"	Cat 1	22-39	800 lbs.



# Arena Vator III



**QUICK HITCH COMPATIBLE**

## AV3 SERIES

**FEATURES:**

- Adjustable 12" rear pipe roller
- 4" diameter adjustable leveling bar
- Two rows heavy duty S-tines with reversible points
- Frame designed to accept scarifier shank kits

MODELS	WORKING WIDTH	NO. OF SHANKS	SHANK SIZE	SHANK CLEARANCE	HITCH	HP REQUIRED	WEIGHT
GMRAV3-4	4'	11	1-1/4" x 3/8" x 22"	16"	Cat.1	18 to 32	400
GMRAV3-5	5'	13	1-1/4" x 3/8" x 22"	16"	Cat.1	20 to 32	480
GMRAV3-6	6'	15	1-1/4" x 3/8" x 22"	16"	Cat.1	25 to 39	550
GMRAV3-7	7'	17	1-1/4" x 3/8" x 22"	16"	Cat.1	30 to 47	660
GMRAV3-8	8'	19	1-1/4" x 3/8" x 22"	16"	Cat.1 & 2	35 to 53	745
GMRAV3-10	10'	23	1-1/4" x 3/8" x 22"	16"	Cat.1 & 2	40 to 60	930
GMRAV3-12	12'	27	1-1/4" x 3/8" x 22"	16"	Cat.1 & 2	50 to 70	1120

Optional Equipment: Scarifier Shank Kit, Gauge Wheels, Pull-Hitch, 60 Gal. Water Tank w/ Mounting Bkt, Finger Rake in lieu of Pipe Roller & Pipe Leveler

## AV3-M SERIES

**FEATURES:**

- Adjustable 12" rear mesh roller
- 4" diameter adjustable leveling bar
- Two rows heavy duty S-tines
- Frame designed to accept scarifier shank kits



**QUICK HITCH COMPATIBLE**

MODELS	WORKING WIDTH	NO. OF SHANKS	SHANK SIZE	SHANK CLEARANCE	HITCH	HP REQUIRED	WEIGHT
GMRAV3-4M	4'	11	1-1/4" x 3/8" x 22"	16"	Cat. 1	18 to 32	370
GMRAV3-5M	5'	13	1-1/4" x 3/8" x 22"	16"	Cat. 1	20 to 32	460
GMRAV3-6M	6'	15	1-1/4" x 3/8" x 22"	16"	Cat. 1	25 to 39	530
-	7'	17	1-1/4" x 3/8" x 22"	16"	Cat. 1	30 to 47	640
GMRAV3-8M	8'	19	1-1/4" x 3/8" x 22"	16"	Cat. 1 & 2	35 to 53	725

Optional Equipment: Scarifier Shank Kit, Gauge Wheels, Pull-Hitch, 60 Gallon Water Tank with Mounting Bracket




AV3 with optional Finger Rake & Gauge Wheels



AV3 with optional Pull-Type Hitch, AV3-4 & AV3-5



AV3 with optional Scarifier Shanks



AV3 with optional 60 Gallon Water Tank

# Arena Groomer


## AC Series Arena Comb *Ideal for horse arenas!*

### STANDARD FEATURES

- Developed for the highest quality arenas that usually have decomposed granite or ground rubber base under approximately 4" of quality sand.
- Two large 8" wide adjustable flotation gauge wheels for depth control are mounted in front.
- Two rows of heavy-duty vibrating S-tine shanks loosen and aerate the soil.
- Special 3/4" thick steel comb levels, gauges the depth on the rear of the machine and finish combs the sand.
- Quick hitch compatible.

### RHE SERIES ARENA-HARROWS SPECIFICATIONS

MODEL	GMRAC7
Working Width	7'
Number of Shanks	17
Shank Size	1 1/4" x 3/8" x 22"
Shank Clearance	16"
Quick Hitch	Category 1
HP Rating	25 to 50
Weight	530 lbs.
Leveling Comb	
Gauge Wheels	



*The AC Series Arena Comb is designed as a light to medium duty tillage tool for working up, leveling and conditioning arenas and tracks.*

*The Arena-Comb consists of a cultivator frame, two gauge wheels and a leveling comb. It will work the soil, level and condition the surface in one pass.*



Equipped with 8" wide flotation wheels. Quick hitch compatible.



Two rows of heavy duty S-tine shanks.

## Replacement Parts

Part Number	Description	Weight
GMRV3-GW	Gauge Wheels for AV3-4-8	
GMRV3-PH	Pull-Type Hitch with Ratchet Jack	100 lbs.
GMRV3-SH4	Scarifier Shank Kit AV3-5, 6, & 7	35 lbs.
GMRV3-SH6	Scarifier Shank Kit AV3-8	54 lbs.
GMRV3-SH8	Scarifier Shank Kit AV3-10, 12	



GMRV3-GW



GMRV3-SH4  
GMRV3-SH6

# Heavy Duty Core Aerators

**AE 200 Series** Quick Hitch Compatible

**WESTWARD PARTS**

**STANDARD FEATURES**

- Cat 1 hitch.
- Quick hitch compatible.
- Powder coat paint.
- Available in 48", 60" & 72" widths.
- 3/4" hardened spoons with closed design.
- Rotor flanges are welded with 2 bronze bushings per rotor.
- 3 Support stands.
- Paired hubs turn independently.
- Six spoons per hub - penetration of 4 1/2".



200 Series Core Aerators help to relieve soil compaction and allow air circulation in grassy surfaces. When your grassy surface begins to suffer the effects of compaction and wear, such as shallow root zones, thatch build-up, worn pathways or water stands, our 20 Series Core Aerator will provide immediate relief.

Part No.	GMRAE200-48	GMRAE200-60	GMRAE200-72
Overall Width	48"	60"	72"
Coring Width	42"	54"	66"
Height	36"	36"	36"
Hitch	Cat 1	Cat 1	Cat 1
# of Spoons	48	60	72
# of Spoons Wheels	8	10	12
# of Hubs	4	5	6
Spoon Penetration	4 1/2"	4 1/2"	4 1/2"
Weight (lbs.)	320	350	400

### Replacement Spoons

Part Number	Description
GMP800101	Aerator Tine

# Single Shank

**GMR200** Single Shank

**STANDARD FEATURES**

- 4" x 4" x 3/8" tube frame.
- Shear bolt protection.

Part No.	GMR200
# of Shanks	1
Frame Tube Size	4" x 4"
Shank Length	23"
Shank Size	1" x 6"
Hitch	Cat. 1
Max. HP	50
Weight	130



# Rakes



## Three Point Hitch Landscape Rake *Sturdy Frame and Construction!*

### STANDARD FEATURES

- For commercial or home use.
- Use for soil preparation for seeding, distributing or spreading of crushed stone and top soil, clean up of debris such as roots, rocks, etc.
- Rakes are maneuverable, permitting close work around fences, walls and other objects.
- Five forward – three rear angle positions on the DCR series and seven forward, seven rear on the LRHD series provides for precision leveling and grading.
- Sturdy frame construction with heavy duty  $\frac{5}{16}$ " x 1" x 15" standard on both series.
- Single gauge wheel kit fits DCR and MCR models.
- Dual gauge wheel kit fits MCR-7 and LRHD models.
- A "waffle plate" for added strength, supports each tine.



Part Number	Description	Weight (lbs.)
GMRMCR-6	6' Standard Duty Landscape Rake - Category I (40 HP)	187
GMRMCR-7	7' Standard Duty Landscape Rake - Category I (40 HP)	199
GMRLRHD-6	6' Heavy Duty Landscape Rake - Category I (60 HP)	279
GMRLRHD-7	7' Heavy Duty Landscape Rake - Category I (60 HP)	305
GMRLRHD-8	8' Heavy Duty Landscape Rake - Category I (60 HP)	331
GMRSGW-10	*Single gauge wheel kit DCR, MCR	26
GMRDGW-20	*Dual gauge wheel kit MCR-7, LRHD	57

\*Optional

Part Number	Description
GMR341889	Tinebar Weldment of 5' Landscape Rake (GMRMCR-6)
GMR341891	Tinebar Weldment of 6' Landscape Rake (GMRMCR-7)



### Replacement Tine

Part Number	Description
GMP341704	Landscape Rake Tine



## Pull Chassis

### STANDARD FEATURES

- Ideal for grading; leveling; spreading topsoil, stone, gravel, or cinders; removing stones, roots, and trash; breaking up sod clumps, smoothing ball diamonds, parking lots, etc.
- Rakes permit close work around fences, walls and other objects.
- Rakes are designed for ATV's and garden tractors from 10 to 22 horsepower.
- 5 angle position, heavy-duty w  $5/16$ " x 1" heat-treated tines, pneumatic tires on transport gauge wheels, a turnbuckle adjustment for operating depth and a rope pull lever to raise unit on turns or to dump.
- Pull lever is locked up for transport.
- Pull-type Chassis only (Clevis Hitch)

Part Number	Description	Weight (lbs.)
GMR341970	Pull Chassis (Bridge Only)	84




# 3 Pt. Hitch Rototillers

**TXG Series Rototiller** *Compact Rotary Tiller*

**WESTWARD PARTS**

**STANDARD FEATURES**

- Single speed Gearbox with 540 rpm PTO.
- Rotor revolutions (rpm): 268.
- PTO shaft with clutch (1" 3/8 Z6 tractor side yoke).
- Side Gear drive.
- Universal three point hitch, cat. 1.
- 6 blades per flange.
- Safety guards.



Part No.	Working Width	Working Depth	Blade (PCS)	Power (HP)	Input Power (RPM)	Weight	Measurement	Replacement Blades
GMRTXG40	37"	7"	24	20-35	540	323 lbs.	47" x 26" x 23"	GMPTX-71R (Right) GMPTX-71L (Left)
GMRTXG48	47"	7"	30	20-35	540	363 lbs.	56" x 25" x 23"	
GMRTXG56	56"	7"	36	20-35	540	394 lbs.	65" x 25" x 23"	

## 3 Pt. Hitch Rototillers

### TSG Series Rototiller *Medium Rotary Tiller*


**WESTWARD PARTS**

#### STANDARD FEATURES

- Single speed Gearbox with 540 rpm PTO.
- Rotor revolutions (rpm): 242.
- PTO shaft with clutch (1" 3/8 Z6 tractor side yoke).
- Side Gear drive.
- Universal three point hitch, cat. 1.
- 6 blades per flange.
- Safety guards.



Part No.	Working Width	Working Depth	Blade (PCS)	Power (HP)	Input Power (RPM)	Weight	Measurement	Replacement Blades
GMRTSG50	47.2"	7"	36	35-50	540	-	-	GMPTS-64R (Right) GMPTS-64L (Left)
GMRTSG58	55"	7"	42	35-50	540	541 lbs.	65" x 24" x 28"	
GMRTSG66	63"	7"	48	35-50	540	594 lbs.	73" x 24" x 28"	
GMRTSG74	71"	7"	54	35-50	540	638 lbs.	81" x 24" x 28"	
GMRTSG81	79"	7"	60	35-50	540	706 lbs.	89" x 24" x 28"	

### RXGU Series Rototiller *Heavy Duty Rotary Tiller*


**WESTWARD PARTS**

#### STANDARD FEATURES

- Single speed Gearbox with 540 rpm PTO.
- Rotor revolutions (rpm): 249.
- PTO shaft with clutch (1" 3/8 Z6 tractor side yoke).
- Side Gear drive.
- Universal three point hitch, cat. 1 & cat.2.
- 6 blades per flange.
- Safety guards.

Drive style



Part No.	Working Width	Working Depth	Blade (PCS)	Power (HP)	Input Power (RPM)	Weight	Measurement	Replacement Blades
GMRXGU200	75"	8"	60	60-90	540	981 lbs.	87" x 30" x 31"	GMPRX-100R (Right) GMPRX-100L (Left)
GMRXGU220	83"	8"	66	60-90	540	1030 lbs.	94" x 30" x 31"	
GMRXGU240	90"	8"	72	60-90	540	1080 lbs.	102" x 30" x 31"	


**WESTWARD PARTS**

6517 - 67 St.  
Red Deer, AB T4P 1A3  
Fax: 1-800-661-4508

201 Henderson Dr.  
Regina, SK S4N 7E2  
Fax: 1-800-721-2977

1435 St. James St.  
Winnipeg, MB R3H 0W9  
Fax: 1-800-257-8338

Specifications subject to change without notice or obligation.

# SPRAYERS AND ACCESSORIES

- BATTERY POWERED BACKPACK SPRAYERS
- MANUAL BACKPACK SPRAYERS
- HAND-HELD SPRAYERS
- FOAM SPRAYERS
- CONCRETE SPRAYERS
- 3 PT. HITCH SPRAYER PUMP
- FIMCO SPRAYERS



**WESTWARD PARTS**

## Hand Held Sprayer

### SPWIN1000 Industry ERGO Acid 1000

Part No.	Description
SPWIN1000	Industry ERGO Acid 1000

An acid-resistant sprayer that is also light and handy.



### SPWP3000 Foam Sprayer Axel 3000

Part No.	Description
SPWP3000	Foam Sprayer Axel 3000



## Compression Sprayers

### SPW1232231 1.3 Gallon Handheld Sprayer

#### STANDARD FEATURES

- Working pressure (maximum) 35 PSI (2.4 bar)
- Net weight 3.3 lbs.
- Hose length 64.9 inches
- Spray lance length 13.7 in

For all your quick spot spraying needs!

Part No.	Description
SPW1232231	1.3 Gallon Handheld Sprayer



### SPWP5/PP 1.3 Gallon Sprayer Professional Plus

#### STANDARD FEATURES

- Total Capacity: 1.3 Gallon or 5.70 L.
- 58 PSI
- Net weight 2.20 kg or 4.85 lbs.

Multifunctional, richly equipped, thanks to it, you can do more. In one package, you get from us everything you expect from the sprayer.

Spraying with natural plant preparations;  
 Spraying with plant protection products;  
 Foliar fertilization of vegetables and herbs.

Part No.	Description
SPWP5/PP	1.3 Gallon Sprayer Professional Plus







# Compression Sprayers

- SPWP5H** 1.3 Gallon Hobby Sprayer
- SPWS023.111** 2.3 Gallon Hobby Sprayer

If you are just starting your adventure with the garden, then the hobby™ sprayer will be perfect for you. It draws from all the most advanced solutions, and the ability to mount each of our lances to it makes it the best choice for start.

- Spraying with natural plant preparations;
- Spraying with plant protection products;
- Foliar fertilization of vegetables and herbs.

	SPWP5H	SPWS023.111
Total Capacity	1.3 Gallon or 5.70 L	2.3 Gallon or 9.50 L
Pressure	58 PSI	58 PSI
Net Weight	3.3 lbs. or 1.50 kg	3.96 lbs. or 1.90 kg



SPWP5H

SPWS023.111



Part No.	Description
SPTW500	Complete Telescoping Spray Wand
SPPZ12/15	A nozzle with adjustable jet angle fits all sprayers (excluding mini sprayers) and lances manufactured by Marolex



- SPWS105.232** 1.3 Gallon Industry Acid Sprayer
- SPWP7MVTs** 1.8 Gallon Industry Acid Sprayer
- SPWP12MVTs** 3.1 Gallon Industry Acid Sprayer

Heavy industry™ and aggressive chemistry require durability at the highest level. Regardless of pH, the industry sprayers are unbeatable. Resilience and safety are priority when working with hazardous chemicals.

- Neutralization of oils and harmful substances;
- Disinfection of halls and production devices;
- Cleaning and maintenance of stainless steel surfaces;
- Removal of limescale from metal surfaces;
- Removal of rust from metal tanks.



SPWS105.232

SPWP7MVTs

SPWP12MVTs

	SPWS105.232	SPWP7MVTs	SPWP12MVTs
Total Capacity	1.3 Gallon 5.70 L	1.8 Gallon or 7.8 L	3.1 Gallon or 11.60 L
Pressure	0.4MPa	0.4MPa	0.4MPa
Net Weight	1.90 kg	4.4 lbs. or 2 kg	5.0 lbs. or 2.30 kg

# Manual Backpack Sprayers



## XP SERIES 3 & 4 Gallon Manual Backpack Sprayers

Ultra-comfortable, lightweight professional grade Backpack sprayers. Jacto's new XP range was born from tradition of serving the needs of farmers in some of the most forbidding environments in the world. Jacto's robust XP models require less pumping to achieve maximum operating pressure than just about any other sprayer you can find.

The Jacto XP is an easy-pumping, high (88 PSI) pressure marvel of engineering!



Part No.	Description
SPW1210806	XP Series - White 3 Gallon Manual Backpack Sprayer
SPW1210807	XP Series - White 4 Gallon Manual Backpack Sprayer
SPW1210811	XP Series - Blue 3 Gallon Manual Backpack Sprayer
SPW1210812	XP Series - Blue 4 Gallon Manual Backpack Sprayer

## HD 400U Series 4 Gallon Urban Manual Backpack Sprayers

The Jacto HD-400U offers a spray trigger made of stainless steel with a blue adjustable cone nozzle, providing versatility in the regulation of the spray patterns and an extended reach of up to 6 meters (20 ft.) in height.

The sprayer reversible, and thus can be set up for either right- or left-handed operators. The operator's comfort is further enhanced with adjustable padded shoulder straps.

The Jacto HD-400U is one of the lightest sprayers in its category, with a 16-liter (4 gal.) tank and a carrying handle that helps in transporting the equipment.

Part No.	Description
SPW1245277	HD400U - White 4 Gallon Manual Backpack Sprayer



## PJ-16U 4 Gallon Urban Manual Backpack Sprayers

The Jacto HD-400U offers a spray lance made of stainless steel with a blue adjustable cone nozzle, providing versatility in the regulation of the spray jet and a continuous reach of up to 6 meters in height.

It is a symmetrical sprayer, which can pump on both sides (left and right), and for the operator's comfort, it has adjustable padded straps. The operator's ergonomics and long working hours in mind, a 16-liter tank and strap for handling and carrying the equipment.

The white see-through tank makes it easy to prepare the liquid and to check the amount of product available to be sprayed.

Part No.	Description
SPW1277547	HD400U - White 4 Gallon Manual Backpack Sprayer



# Manual Backpack Sprayers



## HD 400 SERIES 4 Gallon Manual Backpack Sprayers

Very popular with landscape professionals and organic farmers, the 4-gallon (16-liter) HD400 has an internal mechanical agitator that does an excellent job of keeping powdered chemicals such as kaolin clay organic insecticides in suspension.

The HD400 was independently tested for more than 1,500 continuous hours of operation with no breakdowns and the Jacto HD400 is easily converted for either right-hand or left-hand operation.



Part No.	Description
SPW1210802	HD 400 Series - Blue 4 Gallon Manual Backpack Sprayer
SPW1210803	HD 400 Series - White 4 Gallon Manual Backpack Sprayer

- SPW1210799** PJ16 Blue 4 Gallon Manual Backpack Sprayer
- SPW1210801** CD400 White 4 Gallon Manual Backpack Sprayer

Jacto's 4-gallon (16-liter) CD400 has long been a popular choice among farmers, landscapers, construction crews and others who need extreme toughness and maximum resistance to abusive chemicals.



Part No.	Description
SPW1210799	PJ16 Blue 4 Gallon Manual Backpack Sprayer
SPW1210801	CD400 White 4 Gallon Manual Backpack Sprayer

## SPW1210800 PJH - Blue 5 Gallon Manual Backpack Sprayer

The world's top selling backpack sprayer – and the most imitated backpack sprayer ever. The PJH has a heavy duty internal brass piston pump, fitted with dual Viton piston cups, accurate tank measurements, locking handle and wand storage, convenient molded in top carry handle and extra large padded adjustable shoulder straps. No matter what your application, herbicide, fungicide, pesticide or crop nutrient, the PJH is a workhorse sprayer.



Part No.	Description
SPW1210800	PJH - Blue 5 Gallon Manual Backpack Sprayer

# Manual Backpack Sprayers

## **SPP26021XP** 2 Gallon Pro Series Sprayer

### STANDARD FEATURES

- 2-Gallon translucent tank with 4-inch wide mouth opening for easy filling and cleaning.
- Compatible with common fertilizers, weed killers and pesticides.
- Cushion grip shut-off, poly wand and adjustable brass, poly-fan and poly-cone nozzles.
- Shutoff matches most backpack shutoff assemblies.
- Material: Poly
- GPM: 0.4 to 0.5
- PSI: 40 to 60
- Weight: 5.1 lbs

Part No.	Description
SPP26021XP	2 Gallon Pro Series Sprayer



## **SPP61800** Chapin 4 Gallon Pro Series Backpack Sprayer

### STANDARD FEATURES

- 4 gallon translucent tank, weight 10.5 lbs.
- 4" wide mouth opening for easy filling and cleaning.
- Compatible with common fertilizers, weed killers and pesticides.
- 3-Stage filtration system with in-tank removable/cleanable filter.
- Cushion grip poly shut-off and brass nozzle.
- 3 piece nozzle kit for a variety of applications.
- Padded shoulder straps to accommodate a full backpack for hours.
- Applications: General Purpose Cleaning, Fertilizers, Weed & Feed, Fungicides, Herbicides, and Pesticides.

Part No.	Description
SPP61800	4 Gallon Pro Series Backpack Sprayer



## **SPP64800** Chapin Pro Series Diaphragm Pump Backpack Sprayer

### STANDARD FEATURES

- 4 gallon translucent tank, weight 10.5 lbs.
- 4" wide mouth opening for easy filling and cleaning.
- Diaphragm pump provides compatibility with common fertilizers, weed killers and pesticides in both liquid and wettable powder form.
- 3-Stage filtration system with in-tank removable/cleanable filter.
- Cushion grip poly shut-off and brass nozzle.
- Padded shoulder straps and lumbar support for comfort.
- Applications: Wettable Powders, Powders, and General Purpose Cleaning.

Part No.	Description
SPP64800	4 Gallon Pro Series Diaphragm Pump Backpack Sprayer



# Backpack & Handheld Sprayers



SPWHH1



SPWHH6



SPWHH8



SPWBP16

Part No.	Description
SPWHH1	1.2 litre handheld sprayer. Easy to use handheld sprayer ensures precise application.
SPWHH6	6.5 litre handheld sprayer Lightweight handheld sprayers ensure reliable application of products like liquid fertilizer, and pest control.
SPWHH8	8.0 litre handheld sprayer Lightweight handheld sprayers ensure reliable application of products like liquid fertilizer, and pest control.
SPWBP16	16.0 litre backpack sprayer The Backpack Sprayer is ideal for use as a lawn sprayer, garden sprayer, weed sprayer, chemical sprayer, spot sprayer, and fertilizer sprayer.

# Industrial Concrete Sprayer

## SPP1949 Chapin 3.5 Gallon Industrial Concrete Open Head Sprayer

Chapin's 1949 open head form oil sprayer is the best selling unit and is unmatched for quality. It's compatible for most professional concrete applications and extreme chemicals.

### STANDARD FEATURES

- 3.5-gallon Tri-Poxy tank - triple protection against rust, corrosion, and damage from dents.
- Chemical-resistant seals.
- 4-inch wide mouth opening for easy filling and cleaning.
- 48-inch reinforced hose with threaded fittings.
- Brass pump, wand, nozzle and shut-off with lock-on feature.
- Unique Tri-Lock seal feature that locks the pump cap tight.
- Applications: form oil, concrete additives.

Part No.	Description
SPP1949	3.5 Gallon Industrial Concrete Open Head Sprayer



# Battery Powered Backpack Sprayers



## **SPW1230663** PJB-8C Series - 2 Gallon Battery Powered Shoulder Carry Sprayer

The PJB-8c combines technology and ease of use in a very compact size. This 2 gallon shoulder carry sprayer is perfect for use in small plot growing and tight spaces such as greenhouses, border control in landscapes or plantscape environments in office buildings. Homeowners will like it's lightweight and ease of use for around their home gardens, fruit trees or just general weed control. Whether you need to apply fungicides, pesticides or herbicides, this lightweight easy to use sprayer will do the job efficiently and with less effort as compared to pump-up compression sprayers.



Part No.	Description
SPW1230663	2 Gallon Battery Powered Shoulder Carry Sprayer

## **SPW1272393** PJB-16 - Blue 4 Gallon Battery Powered Backpack Sprayer

## **SPW1272385** PJB-20 - Blue 5 Gallon Battery Powered Backpack Sprayer

### STANDARD FEATURES

- Full battery charge in 4 hours.
- Average run time - 8 hours.
- Horizontal Spray 30 Ft.
- Vertical Spray 25 Ft.

Part No.	Description
SPW1272393	PJB-16 Blue 4 Gallon Battery Powered Backpack Sprayer
SPW1272385	PJB-20 Blue 5 Gallon Battery Powered Backpack Sprayer



## **SPW1277571** DJB-16 Blue 4 Gallon Battery Powered Backpack Sprayer

## **SPW1236352** DJB-20 Blue 5 Gallon Battery Powered Backpack Sprayer

### STANDARD FEATURES

- Full battery charge in 4 hours.
- Approximately 50 Gallons per charge.

Part No.	Description
SPW1277571	DJB-16 Blue 4 Gallon Battery Powered Backpack Sprayer
SPW1236352	DJB-20 Blue 5 Gallon Battery Powered Backpack Sprayer



# Battery Powered Backpack Sprayers



**SPW1301141** SB-8U Urban Li-ion Battery Shoulder Carry Sprayer

**STANDARD FEATURES**

- Full battery charge in 4 hours.
- Approximately 50 Gallons per charge.

Part No.	Description
SPW1301141	SB-8U Urban Li-ion Battery Shoulder Carry Sprayer



# ATV Sprayer

**SPWATV25BL**

The Workhorse ATV Sprayer is the perfect choice for weed control for gardens, fence rows food plots, pastures and more.

**Specific features include:**

- 15 to 25 Gallon Set-Ups
- Durable Polyethylene Tank
- 12 Volt Pump – 2.2 GPM or 5.0 GPM pumps
- 18” Spray Wand
- Adjustable Spray Nozzle
- 3/8” PVC Reinforced Spray Hose
- Heavy Duty Manifold design
- 8’ Universal Wiring Harness
- Quick attach boom system
- Pressure Gauge
- Chemical Resistant
- RoundUp Ready



Part No.	Description	Size	Pressure	Style	Nozzles	Coverage	Handgun
SPWATV25BL	25 Gallon ATV Sprayer	5.0 GPM	0-60PSi	Boomless	2	288"	Heavy Duty

# H2O Fire Pro



**SPW1230663** PJB-8C Series - 2 Gallon Battery Powered Shoulder Carry Sprayer

The H2O Fire Pro, intended for fighting fires and hot spots, delivers a strong uniform stream of water to the intended area. A 40 US gallon tank and a 5 GPM pump allows the user 8 minutes of use before refill.

Can be mounted to grain carts, service trucks, ATVs, Side by Sides, etc. Can be secured with straps or you can bolt using the 1/2" threaded inserts in the bottom.

**STANDARD EQUIPMENT:**

- 6" Vented Screw Cap
- Suction Strainer
- 1/2" Hose Assembly – 25'
- Adjustable Spray Nozzle
- 12V DC, 5 GPM pump with on/off switch
- 1/2" Drain plug
- Built in hose reel
- 1/2" threaded inserts in bottom of tank

**OPTIONAL EQUIPMENT:**

- 12 Gauge Fused Power Cord with clamps – 20'



**NEW!**

Part Number	Description	Capacity	Weight
FFM26006178	H2O Fire Pro	33 gallons (125 L)	35 lbs.





# Super Sponge Weed Wipers

## SPWWWTKT120-SP - Kit for Sprayers

The 120 ft. sprayer boom kit that can easily be mounted to your existing spray boom! Each 30" sponge section has a separate feed tube that adapts directly to the closest TeeJet or Hypro nozzle body. Nozzle body caps are also included to shut down any tip that is not feeding a sponge section. The special brackets, U-bolts, and risers allow you to easily attach the sponges to your boom quickly. The brackets also allow you to remove the sponges quickly without taking off the U-bolts. Bottom line...you can quickly convert your sprayer into a weed wiper and eliminate taller growing weeds with very little chemical.



Weed Wiper Mounting Bracket With Hardware

X 64



Tubing, Black, 1/4" Solid

95FT



WW Mounting Bracket

X 69



Cap & Gasket, Shut Off

X 18



T Riser, Assembly, Top Crop

X 69



Teejet Nozzle Con. w/ 1/4 PTC & Washer

X 55

Part No.	Description
SPWWWTKT120-SP	Weed Wiper 120' Kit Spray Boom

## SPWWWTKT40 - Kit For Custom Built Booms

Build your own custom weed wiper, or convert your old gravity fed weed wiper to a modern pump fed system. Mount this kit to a boom of your choosing. This unit requires a spray tank with a 3 GPM minute pump or larger. Wipe out taller growing weeds with no drift.

### INCLUDES

- Smucker Catalog VS 9 + Manual
- 38 x Clamp, Hose #24
- 18 x Tie, Nylon, 11 T40 1-Black
- 200 ft Tubing, Black, 1/4" Solid
- 19 x T Riser, Assembly, Top Crop
- 16 x 30" Sponge Assembly
- 2 x 8-Port Manifold for 20' Top Crop



Part No.	Description
SPWWWTKT40	40ft. Pump Fed Top Crop Kit

## Digital Pressure Tester

### SPW28040 Digital Pressure Tester

Accurately Check Nozzle Pressure Where It Counts!

- Verify Accuracy Of Sprayer's Pressure Sensor Or Gauge
- Find Blockages In Hoses And Booms
- Installs Between Nozzle And Nozzle Body
- Digital Display Reads In Psi, Bars, Or Kpa
- Uses Industry Standard Quick Connects
- Simple One Button Operation
- Shock Proof Rubber Covering Protects Against Drops And Mishandling



Part No.	Description
SPW28040	Digital Pressure Tester

## Nozzle Cleaner & Tip Tool

### SPW27860 Nozzle Cleaner & Tip Tool

Clears plugged spray tips with a 50 psi air blast!

Get both the innovative air blast Nozzle Cleaner and 4-in-1 Tip Tool multi-tool. These tools are designed specifically for spray tip and nozzle body cleaning and maintenance. The SpotOn Nozzle Cleaner provides a 50 PSI air blast for clearing debris from spray tips. The 4-in-1 Tip Tool features a brush, foldout plastic pick, spanner wrench, and utility hook that make tip maintenance quick and easy.

- 4-in-1 Spray Tip Maintenance Tool - Utility hook, Spanner Wrench, Plastic Pick, Brush

Part No.	Description
SPW27860	Nozzle Cleaner & Tip Tool



# Sprayer Calibrator

## SPWSC-2

Provides quick and accurate flow rate checking of individual spayer nozzles. This model is the best for flow rates below 2.25 GPM typical of herbicide and insecticide application.

**STANDARD FEATURES**

- Automatically calculates and displays tip flow rate in GPM, LPM, oz/min, tip wear in %, and application rate in GPA/LPH
- Fast and simple operation: readings in about 10 seconds per tip
- Quickly find worn spray nozzle tips
- Accurately measure true tip flow rate

Part No.	Description	Range & Units
SPWSC-2	SC-2 Sprayer Calibrator	0.02 - 2.25GPM, 0.08 - 8.52 LPM, 3-288 oz/min



# Universal Flow Meter

## SPWSC-5 SC-5 Universal Flow Meter

Quickly and accurately check water flow from nozzles, faucets, sprayers, and showers up to 5GPM

**STANDARD FEATURES**

- Provides high-resolution digital flow rate display within seconds
- Collapsible 4.25in (10.8cm) dia. rubber collection funnel for shower heads
- Fits under faucets with as little as 7.5in (19cm) clearance height
- Internal difuser pad controls strong nozzle spray
- Simple rugged design has no moving parts
- Self-contained for one-handed operation

Part No.	Description	Range & Units
SPWSC-5	SC-5 Universal Flow Meter	0.08 - 5.00 GPM, 0.30 - 19.00 LPM, 2-1140L/hr



# 3 Pt. Hitch Sprayer Pump

## SPWWP6RC 6 Roller PTO Pump

Delavan 6900C Roller Pump with quick disconnect coupler, anti-rotate bar and chain. Delivers up to 19.6 GPM and 300 PSI.

### STANDARD FEATURES

#### PUMP:

- Type: 6-roller design
- Max Pressure: 300 PSI
- Max Recommended Temperature: 140°F
- Port Size: 3/4" FNPT
- 6900: side ports
- Mounting: Base Mounted: 5/16" – 18UNC-2B (2 holes)
- PTO: Use Torque Bar and Chain Weight: 9 lbs

#### MATERIALS OF CONSTRUCTION:

- Pump Housing: Cast Iron
- Rollers: 1/2" Ultra Rollers
- Shaft Seals: Viton cartridge type lip seals
- Shaft & Rotor: C Extra-fine finish 404 SST
- Bearings: Permanently-lubricated, heavy-duty sealed bearings



### 6900 SERIES PERFORMANCE

PSI	540 RPM	1000 RPM	1200 RPM
0	10.5	19.6	22.8
20	9.7	19.0	22.0
40	8.6	18.4	21.3
60	6.9	16.3	19.7
80	4.8	13.9	17.9
100	3.0	11.5	15.8

Part No.	Description
SPWWP6RC	6 Roller Pump Kit - 6 spline, 540 PTO

# Westward Parts FIMCO Catalogue



*We are proud to partner with FIMCO Industries to provide our Dealers with a wide variety of top quality products.*

*Refer to the current FIMCO Sprayer Catalogue to see a complete listing of all products available.*

## WESTWARD PARTS

6517 - 67 St.  
Red Deer, AB T4P 1A3  
Fax: 1-800-661-4508

201 Henderson Dr.  
Regina, SK S4N 7E2  
Fax: 1-800-721-2977

1435 St. James St.  
Winnipeg, MB R3H 0W9  
Fax: 1-800-257-8338

Specifications subject to change without notice or obligation.

# STORAGE TANKS & CHEMICAL HANDLERS

- VERTICAL TANKS
- HORIZONTAL TANKS
- ELLIPTICAL TANKS
- SPECIALTY TANKS
- CHEMICAL HANDLERS
- CHEMBINE CHEMICAL MIXER



**WESTWARD PARTS**

# Storage Tanks



## Vertical Storage Tanks

Vertical storage tanks are most frequently used for bulk storage and mobile nursing applications. Norwesco vertical tanks feature tie-down slots, built-in graduated gallon indicators, an offset fill-opening and a self-vented, slosh-proof lid.



Part No.	Imperial Gallons	Litres	Fitting Size	Diameter	Overall Height	Manway	Weight
SPP41135	160	725	No Ftg	29.5"	71"	8"	60 lbs.
SPP43201	200	909	No Ftg	29.5"	91"	8"	70 lbs.
SPP41057	315	1,430	No Ftg	35"	99"	16"	120 lbs.
SPP41061	500	2,270	No Ftg	48"	84"	16"	150 lbs.
SPP41065	750	3,405	No Ftg	48"	116"	16"	190 lbs.
SPP41067	800	3,632	No Ftg	61"	83"	16"	180 lbs.
SPP41069	900	4,155	No Ftg	48"	148"	16"	250 lbs.
SPP44162	1000	4,540	2"	72"	78"	16"	250 lbs.
SPP41219	1250 Water	5,675	2"	87"	66"	16"	190 lbs.
SPP41221	1250 Premium	5,675	2"	87"	66"	16"	215 lbs.
SPP41931	1750 PW	7,955	2"	87"	89"	16"	300 lbs.

## Pickup Truck Tanks

Designed to fit in the bed of full-size pickups as well as under a truck canopy, the 270 and 350 sizes have low profiles for better rear vision. They feature fill openings to set to the side of the tank for safety and easy access.

A tough circular design adds strength. The 185 gallon tank fits both the "mini" pickups and full-sized models.

Depending upon which way the tank is turned, the bottom width can be either 39" or 48". Our pickup truck tanks feature built-in, graduated gallon indicators and slosh-proof lids.



Part No.	Imperial Gallons	Litres	Fitting Size	Length	Width	Overall Height	Manway	Weight
SPP41213	185	823	2"	60"	48"	28"	8"	55 lbs.
SPP40693	270	1,201	2"	62"	49"	32"	8"	80 lbs.
SPP41227	350	1,557	2"	65"	49"	37"	8"	95 lbs.

## Flat Bottom Tanks

Flat Bottom Tanks are designed to be the most rugged and durable utility transport tanks on the market. Unlike other tanks, Flat Bottom Tanks provide all the strength you need for transporting liquids without the use of bands. Tanks should be mounted on flat surfaces with full length and width support.



Part No.	Imperial Gallons	Litres	Fitting Size	Length	Width	Overall Height	Manway	Weight
SPP43157	1350	6008	2"	126"	80"	53"	16"	515 lbs.

*Note: All tanks 500 gallons and above are special order only. Tanks 1,000 gallons and above are available as direct ship at dealer expense or pickup from factory only.*



# Storage Tanks

## Flat Bottom Utility Tanks

The Flat Bottom Utility tanks are all purpose tanks used for a variety of applications. They are the perfect choice when looking for a tank to put in the bed of a pickup truck. They are often used in agricultural, industrial, manufacturing, auto detailing and liquid transportation industries for storage of water, wastewater, fertilizer and chemicals.



Part No.	Imperial Gallons	Litres	Fitting Size	Length	Width	Overall Height	Manway	Weight
SPP45312	37	165	No Ftg	37.5"	18"	19"	5"	22 lbs.
SPP45315	91	405	1"	48"	35"	18"	5"	60 lbs.

## Low Profile Holding Tanks

Low profile tanks are ideal for storage in areas where height in an important consideration. The low profiles are designed to fit under a cottage or cabin and the strong deep ribs create extra structural strength.



Part No.	Imperial Gallons	Litres	Fitting Size	Length	Width	Overall Height	Manway	Weight
SPP41188	160 Water	712	N/A	80"	46"	15"	8"	75 lbs.
SPP45316	165 Water	735	N/A	60"	48"	20"	8"	80 lbs.
SPP41189	230 Water	1,023	N/A	80"	46"	20"	8"	100 lbs.
SPP43123	500 Water	2,225	2"	98"	72"	28.5"	16"	190 lbs.
SPP42890	1075 Water	4,783	2"	131"	84"	36"	16"	350 lbs.
SPP42891	1325 Water	5,896	2"	131"	84"	42"	16"	460 lbs.
SPP44335	2100 Water	9,350	2"	159"	90"	51"	16"	750 lbs.

## Low Profile Holding Tanks - for Water Storage, Black

Part No.	Imperial Gallons	Litres	Fitting Size	Length	Width	Overall Height	Manway	Weight
SPW41899	500 Water	2,225	2"	98"	72"	28.5"	16"	190 lbs.

## Indoor Freestanding Potable Water Tanks

These tanks have been specially designed with residential and commercial applications in mind.

The dimensions of the water tanks allow them to fit through a conventional doorway. The 230 and 350 come standard with a steel support frame. The design of the 330 and 500 imperial gallon tanks allows them to be freestanding/self-supporting and eliminates the need for a steel support frame.



Part No.	Imperial Gallons	Litres	Fitting Size	Length	Width	Overall Height	Manway	Weight
SPP45408	83	370	1-1/4"	36"	18"	43"	5"	40 lbs.
SPP41199	230	1045	-	48"	24"	60"	16"	-

*Note: All tanks 500 gallons and above are special order only. Tanks 1,000 gallons and above are available as direct ship at dealer expense or pickup from factory only.*

# Storage Tanks



## Horizontal Leg Tanks

With the broadest leg tank line available, Norwesco manufactures a size that will fit your needs. Used primarily for transport and nursing applications, Norwesco leg tanks feature molded-in legs that act as “baffles” to reduce sloshing.



Part No.	Imperial Gallons	Litres	Fitting Size	Length	Width	Overall Height	Manway	Weight
SPP41092	40	178	No Ftg	42"	20"	23"	5"	20 lbs.
SPP41939	55	245	3/4"	43"	23"	25"	5"	26 lbs.
SPP41183	80	356	No Ftg	59"	23"	26"	5"	45 lbs.
SPP41941	100	445	2"	41"	32"	34"	8"	50 lbs.
SPP41094	125	556	2"	59"	30"	32"	8"	60 lbs.
SPP41943	200	890	2"	55"	38"	40"	8"	75 lbs.

## Specialty Water Transport Tanks

These tanks have been specially designed with residential and commercial applications in mind.

The dimensions of the water tanks allow them to fit through a conventional doorway. The 230 and 350 come standard with a steel support frame. The design of the 330 and 500 imperial gallon tanks allows them to be freestanding/self-supporting and eliminates the need for a steel support frame.

\* Loaf Tank



Part No.	Imperial Gallons	Litres	Fitting Size	Length	Width	Overall Height	Manway	Weight
SPP41123	90*	400	No Ftg	47"	23"	28"	5"	50 lbs.
SPP41124	180*	800	No Ftg	58"	29"	35"	5"	90 lbs.
SPP44332	250*	1,114	No Ftg	62.5"	41.5"	28.5"	8"	98 lbs.

## Black Vertical Water Tanks

Water tanks are manufactured using resins that meet FDA specifications to ensure safe storage of potable water. The black color limits light penetration which reduces the growth of water-borne algae. These tanks are rated at 10 pounds per gallon, which means that they are for WATER STORAGE ONLY! They should not be used for chemicals, fertilizers or any other product.

Part No.	Imperial Gallons	Litres	Height	Dia	Fill Opening	Top Fitting	Bottom Fitting
SPW44533	1250	5,682	66"	87"	16"	1.5"	2"
SPP44524	5000	22,730	140"	120"	16"	1.5"	3"



*Note: All tanks 500 gallons and above are special order only. Tanks 1,000 gallons and above are available as direct ship at dealer expense or pickup from factory only.*



# Storage Tanks



## Polyethylene Horizontal Tanks

All tanks come with vented lids and drain fittings.

Part No.	Imperial Gallons	Litres	Length	Dia	Lid Style
SPP7697	10	45	19"	16"	5"
SPW79011	25	114	18"	23"	5"
SPW79008	50	227	37"	23"	5"



# Chemical Handlers



## Handler III *The H33 is the super-sized version of the popular H23*

With its larger tank it is perfect for handling everything from dry flowables, to 10L and 20L containers, to bulk containers. Water is simply pumped to the inlet of the H33 which provides the flow to agitate and fill the tank, empty and rinse containers, power the dual inlet venturi, rinse the tank, and of course transfer water to your sprayer tank. The Handler exclusive dual inlet venturi comes plumbed to draw from your choice of the Handler tank or your bulk containers, directly into your sprayer fill line.

The full 3" bypass line on the H33 is designed to handle the rigors of any pump with capacities of up to 280 GPM (1060 LPM) without concern for pressure. Banjo's sweep elbows are used to eliminate as much line turbulence as possible. To ensure this larger tank size can be thoroughly cleaned, all H3 models incorporate the Rotacraft tank cleaning nozzle.



### FEATURES & BENEFITS

- Full 10L/20L container emptying and rinsing capabilities
- Dual-inlet venturi and bulk draw capabilities
- Durable 3" bypass for flows up to 280 GPM (1060 LPM)
- Comes with the original Handler Knife

### SPECIFICATIONS

- 70 US gallons/275L
- 3" Camlock connections
- 16" Hinged & lockable lid
- 2" Dual-inlet venturi
- Rotacraft tank rinsing nozzle



Part No.	Description	Inches			Meters			Weight	
		L	W	H	L	W	H	LBS	KG
SPW30842	Handler III - 3"	42	44	44	1.1	1.1	1.1	180	82


# Chemical Handlers



**Handler IV** *The king of batch induction systems with its larger liquid volume and incredible agitation capability.*

The H43P65V comes complete with a total drainage tank, Banjo 3” pump, a dual inlet venturi for bulk chemical induction, twin agitation lines, two 16” hinged lids (one with the Handler Knife and one without), container and tank rinsing nozzles, a 4-way forkliftable steel frame, and a pump containment tray. Using closed loop recirculation through the exclusive dual inlet venturi, this model is able to induct bulk chemical into the Handler tank without your sprayer needing to be there! Whether it is high volumes of liquid pesticides or large amounts of dry flowables needing to be agitated, a Handler IV can do it all before your sprayer is back to be filled.

Dry AMS (ammonium sulfate) users may be interested in even more agitation. The similar model H43P65 replaces the venturi with a second 2” full port agitation line and provides agitation strong enough to dissolve even AMS that is not spray-grade.



### FEATURES & BENEFITS

- Twin agitation lines
- Comes with The Handler Knife
- Closed loop recirculation and agitation
- Full 10L/20L container emptying and rinsing capabilities

### SPECIFICATIONS

- 230 US gal/870L
- 3” camlock connections
- Two x 16” hinged and lockable lid
- 2” dual port venturi
- Rotacraft tank rinsing nozzle
- 3” Banjo/GX200 Honda

Part No.	Description	Inches			Meters			Weight	
		L	W	H	L	W	H	LBS	KG
SPW30848	Handler IV - 3" with 3" Pump	72	47	50	1.8	1.2	1.3	525	238

## Hypro Cleanload

The Hypro Cleanload is an onboard education system for quick and safe loading of chemicals into spray tanks.

- The Cleanload system is self-contained and allows the operator to mix the liquid and dry chemicals safely and quickly
- All crop protection chemistry is mixed at ground level, ensuring the safety of both the operator and the environment.
- Comes equipped with CycloRinse tank rinse, designed to wash the Cleanload hopper completely
- The ProClean™ II Push Valve is designed to self-flush to help prevent sticking open or closed, even with heavy particulates. Compatible with all ProClean series nozzles



Part No.	Tank Size	Inlet-Outlet Connection Size
SPW3376-1171	7 Gallon (26 Litre)	220 Universal Flange

# Chembine Chemical Mixer



## Chembine Chemical Mixer



This new product by Free Form Plastics, with several Patent Pending designs, is a cutting-edge way of mixing and blending chemicals for your agricultural needs. The CHEMBINE incorporates all the features of a typical chemical mixer plus adds some user-friendly features while dramatically improving in the following areas:

- New and innovative knife block design provides a more efficiently shaped cut requiring less effort, faster & more complete drainage/rinsing as well as easier removal of the jugs
- Increased agitation with the use of 4 vertically molded ribs in the tank combined with our unique vortex cycling water jet eductor system
- Easy rinse and drain process with the bottom drain valve, all interior surfaces sloped to the drain and a rotary rinse system with 1" lines
- Improved ergonomics with the commonly used valves raised and a molded stop for the hinged lid to rest on Improved stability with the stand incorporated into the poly tank and the addition of large feet with mounting holes Improved visibility with all hoses having clear sidewalls



Part Number	Size	Description
FFM26003-83	2"	CHEMBINE - Complete mixing unit w/o engine, pump, recirculation kit
FFM26003-85	2"	CHEMBINE - Complete, 5.5 HP Honda/Banjo WET SEAL pump/mounting/recirculation kit
FFM26002-42	3"	CHEMBINE - Complete mixing unit w/o engine, pump, recirculation kit
FFM26002-58	3"	CHEMBINE - Complete, 6.5 HP Honda/Banjo WET SEAL pump/mounting/recirculation kit
FFM26004-61	3"	CHEMBINE - Complete, 13 HP ES Honda/Banjo WET SEAL pump/mounting/recirculation kit

Part Number	Description
FFM26003 27	Tank Batching System - 4 Eductor Nozzles, Antivortex, Vented, Rotary Rinse, Valves
FFM26003 69	Chembine To Hot-Tank System Plumbing (c/w 40' Of 3" Hose, Valves, Camlocks)

The CHEMBINE custom molded poly mixer tank has a capacity of 75 US gallons (62.5 Imperial) and offers a faster jug drain time, superior knife cutting block for more complete drainage, quicker rinse times and the latest agitation engineering to offer superior mixing for both wet and dry chemicals. This Free Form Plastics poly mixer tank is custom designed with a 10 degree cone bottom angle for complete drainage plus vastly improves performance when using dry chemicals (this feature also offers a lower, more stable profile, allowing a lower fill height). A micro-valve, complete with nipple, is installed at the lowest point in the tank to allow for easy and complete drainage of the unit.

When designing the tank cradle, where the tank sits onto the powder-coated metal frame, a gentle slope was incorporated so material does not get caught on a ledge, which can be an inconvenience with some competitors' models. The light green colour is well suited to give customers a good view of the tank liquid level. An optional quick attach metal "pump frame" is available for models purchased without the pump. The CHEMBINE utilizes the Banjo threadless plumbing system. Designed and manufactured in St. Brieux, SK, Canada (Free Form Plastics is a Division of Bourgault Industries Ltd).

See following page for more information..

# Chembine Chemical Mixer


**Chembine Chemical Mixer** (Continued)



## STANDARD EQUIPMENT



**ROTARY RINSE**  
Easy rinse and drain process with the bottom drain valve, all interior surfaces sloped to the drain and a rotary rinse system with 1 inch lines.



**MIXING**  
Two agitator jets stir the fluid while the four vertical ribs disrupt the flow increasing the rate of mixing and virtually eliminating the chances of undissolved particles.




**SECURED HINGED TANK LID**  
Has a raised stop to rest on when open. This raised stop feature molded into the tank reduces reach and effort required to open and close the lid.



**MOUNTING**  
The frame legs have large feet with pre-drilled holes to allow easy and secure fastening. The tank is vertically ribbed so that the legs cradle into the tank to give superior agitation plus stability when opening and closing the lid.

## OPTIONS



**KNIFE BLOCK**  
Design provides a more efficiently shaped cut requiring less effort, faster & more complete drainage / rinsing as well as easier removal of the jugs.



**PLUMBING**  
Available in two sizes: 2 inch and 3 inch.



**REMOTE THROTTLE KIT**  
This kit can be added to any of the Honda engines (5.5, 6.5, 13 hp) and allows operation of the throttle from the front of the unit. Allows you to easily vary your throttle as needed to get the best possible performance.

## SPECIFICATIONS

CHEMBINE	
Capacity	75 US Gallon / 62.5 Imperial Gallon / 284 Litres
Features	2 x Agitator Jets / 4 x Vertical Ribs / 1 x Rotary Rinse Nozzles / 1 x 2 inch Tote Connection / Knife Block / Secure Hinged Lid / Frame legs drilled for mounting
Measurements	58-5/16" long x 44-11/16" wide x 41-13/16" high. *based on the base unit
HOT TANK	
Capacity	1,680 US Gallon / 1,400 Imperial Gallon / 6,359 Litres
Features	4 x Agitator Jets / 2 x Rotary Rinse Nozzles / Heavy Duty Stand. Easy Clean Out (10 degree cone bottom to a 3 inch complete drain bulkhead) Two 3- Way Valves

EXPANSION KITS	
3 Tote System w/o Flow Meter	Powder coated bracket included
3 Tote System c/w Flow Meter	Banjo or Dura Meter included depending on application with powder coated bracket
HONDA PUMPS	
5.5 HP Honda GX160 with Banjo Wet Seal Pump	Powder coated frame included
6.5 HP Honda GX200 with Banjo Wet Seal Pump	256 US gpm Powder coated frame included
13 HP Honda GX390 with Banjo Wet Seal Pump	368 US gpm Powder coated frame included

# WATER, TRANSFER, TRASH, & MINI BULK PUMPS



- TRANSFER PUMPS
- MINI BULK PUMPS
- HYDRAULIC PUMPS
- PEDESTAL PUMPS
- CHEMICAL PUMPS
- WATER TRANSFER PUMPS
- FIREFIGHTING PUMPS
- TRASH PUMPS

# Transfer Pump System



## SHURflo® Ag Runner™ Transfer Pump System

The SHURflo AG Runner™ Transfer Pump System is designed to safely and accurately transfer bulk chemicals to the point of use.

### STANDARD FEATURES

Chemical Transfer Pump with 12 VDC motor, 20 ft. cable, alligator clips and in-line fuse (Part# SF-1100-EPDM valves or SF-1105 - Viton valves), electronic flow meter, 1 in. NPT x 12 ft EPDM discharge hose with ball valve/spout, and 1 in. NPT x 12 ft. EPDM inlet hose with 1 in. elbow/ball valve/fitting assembly with locking cam arms.

- Simple and accurate flow indicator
- Industry leading pump
- Portable
- Can be used with a variety of bulk containers
- Built for rugged service with a variety of bulk containers
- Built for rugged service with a heavy-duty welded frame



Part No.	Flow Meter Type
SPWSF-1100-PTS	Pump-mounted (FM-1100)
SPWSF-1100-PTS <i>i</i>	Inline (FM-1100 <i>i</i> )
SPWSF-1105-PTS	Pump-mounted (FM-1100)
SPWSF-1105-PTS <i>i</i>	Inline (FM-1100 <i>i</i> )



# Mini-Bulk Pumps

**SHURFLO® Mini-Bulk Pumps** *Designed for efficiency and power*



The SF-1100 Series Bulk Chemical Pumps are the industry leader. They are designed for efficiency and power to handle highly viscous fluids. Servicing the SF-1100 series pump is a rare event, but if needed, it can be serviced quickly and easily with only a few hand tools.

**STANDARD FEATURES**

- Specialized EPDM elastics or Viton option.
- 12 volt DC or 110 volt AC motor option.
- 20 foot cord with alligator clips and in-line fuse (DC only).
- Weather protected on/off switch.
- Internal bypass to protect the pump at shut-off.
- 2" MNPT inlet, 1" FNPT outlet.
- Capable of priming up to 12 feet.



Part No.	Valves	Motor
SPWSF-1100	EPDM	12 VDC
SPWSF-1100-110V	EPDM	110 VAC
SPWSF-1105	Viton	12 VDC

Model	PSI	BAR	GPM	L/min	Amps
SPWSF-1100 & SPWSF-1105	0	0.0	10.7	40	9.3
	5	0.3	10.1	38	10.3
	10	0.7	8.7	33	12.3
	15	1.0	7.6	29	13.9

# Mini-Bulk Flow Meters

**SHURFLO® Mini-Bulk Flow Meters**



The Shurflo FM-1100 Mini Bulk Electronic Flow Meter are highly accurate, positive displacement, nutating disk, fluidmetering devices. The FM-1100 meter is designed for mounting to a pump or other device that can provide support to the meter. The FM-1100i meter may be mounted at the dispense end of the hose. The inlet connection on the meter should be connected to the hose and a shut-off valve should be connected to the outlet connection.

**STANDARD FEATURES**

- Max. flow of 20 gpm (76 lpm) (.5% accuracy after calibration)
- Max pressure of 120 psi (8.3 bar)
- Accurate nutating disk design
- Large LCD display makes meter reading easy



Model	Max. GPM	Max. LPM	Max. PSI	Max. Bar	Description
SPWFM-1100	20	76	120	8.3	Pump-mounted meter kit- 1" MNPT inlet & outlet
SPWFM-1100i	20	76	120	8.3	Inline meter kit -1" FNPT inlet & outlet

# Hydraulic Pumps




## SPP200PIHY 2" Cast Iron Pump w/Hydraulic Motor

Cast iron construction for rugged dependable service. Hydraulic Fluid Capacity (Min: 6 gallons/ Max 10 gallons). Open or closed system with a 12 HP motor. Replaceable inlet and outlet flanges, and dynamically balanced impellar .Recommendation is to use the motor spool control valve or a suitable equivalent. The lack of such a valve in this circuit may cause failure to the hydraulic motor.

**CAUTION-WARNING:** Please do not run pumps dry, restrict or reduce port sizes or dead head pumps. This could cause component failure to pump.  
**DO NOT USE WITH FLAMMABLE LIQUIDS.**

### STANDARD FEATURES

- Material: Cast Iron
- 12 HP Motor
- Inlet/Outlet: 2" FNPT



Part No.	Description	Weight
SPP200PIHY	2" Cast Iron Pump w/Hydraulic Motor	48 lbs.

## SPP300PHYV 3" Poly Hydraulic Pump-FKM

**CAUTION-WARNING:** Please do not run pump dry, restrict or reduce port sizes, or dead head pump. This could cause component failure to pump.  
**DO NOT USE WITH FLAMMABLE LIQUIDS.**

### STANDARD FEATURES

- Material: Polypropylene
- Style: Hydraulic Pump
- 12 HP Motor
- Hydraulic fluid capacity - Maximum 10 Gallons.
- Open or closed system.
- 3600 R.P.M.

Part No.	Description	Weight
SPP300PHYV	3" Poly Hydraulic Pump-FKM	N/A





# Pedestal Pumps



**SPW200PB** 2" Poly Bearing Pedestal With 3/4" Shaft & 3 Vane Impeller

**STANDARD FEATURES**

- With the addition of the Banjo bearing pedestal, the pump is easily adaptable to electric power. — flexible shaft coupling is used between motor and pump shaft. Pump and motor assembly is mounted on — metal base.
- Material: Polypropylene
- Style: Bearing Pedestal
- Size: 2"

Part No.	Description	Weight
SPW200PB	2" Poly Bearing Pedestal With 3/4" Shaft & 3 Vane Impeller	15.786 lbs.
SPW205PB	2" Poly Bearing Pedestal With 3/4" Shaft & 5 Vane	16 lbs.
SPW200PO	Pump only	7.286 lbs.



**SPW300PB** 3" Poly Bearing Pedestal With 3/4" Shaft & 4 Vane Impeller

**STANDARD FEATURES**

- Material: Polypropylene
- Style: Bearing Pedestal
- Size: 3"
- Corrosion resistant
- High performance impellers
- High strength polypropylene
- Lightweight — portable

Part No.	Description	Weight
SPW300PB	3" Poly Bearing Pedestal With 3/4" Shaft & 4 Vane Impeller	20 lbs.
SPW300PO	Pump only	12 lbs.



# Poly Centrifugal Pumps



## M350 Centrifugal Pumps 3" Wet Seal Poly Pump w/ Vanguard or Honda Engine

The M350 pump saves money in spraying operations.

M350 FastFlow™ technology utilizing a customized diffuser design greatly increases flow rates. With performance over 500 gallons per minute (see chart), you'll spend less time filling, which means less downtime in the field and most importantly, less cost per acre.



Part Number	Description	Weight
SPPM350PH13W	3" Wet Seal Poly Pump with 13 HP Honda Gas Engine	88 lbs.
SPPM350PVAN14W	3" Wet Seal Poly Pump with 14 HP Vanguard Gas Engine	102 lbs.
SPPM350POW	3" Wet Seal Poly Pump Only	17 lbs.



### FILL FASTER - SPRAY MORE!

The FastFlow diffuser design incorporates multiple channels that maximize fluid flow through the pump outperforming traditional one channel volute designs.

### NO LEAKS - NO WEAR - NO WORRIES!

Patent pending tandem wet seal design:

- Produces less wear
- Prevents seal breakage from high pressure clean out
- Eliminates eight leak points
- Works with natural system pressure to keep seal intact.
- Withstands over one hour of dry run.



With tandem wet seals, pressure within the pump body acts in the same direction as the inner seal spring, holding the seal closed preventing leaks. Traditional opposed wet seals can be forced open by high internal pump pressure - causing leaks.

### ATTACHES EASILY!

The M350 Pump Only is manufactured fully assembled and ready for immediate use. The unique design of the M350 Pump Only allows for easy replacement and retrofitting, saving time and effort (up to 30 minutes).

M350's Tandem Wet Seals



Traditional Opposed Wet Seals



## 4" PLUMBING FITTINGS

Part Number	Description
SPPM300400A	3" Manifold x 4" Male Coupler
SPPM300400BRB	3" Manifold x 4" Hose Barb




# Poly Centrifugal Pumps



## M350 Centrifugal Pumps (cont'd)

### Specifications:

- Patent pending tandem wet seal design
- Run dry capability of greater than one hour
- Industry-leading burst pressure
- Wetted components are glass-filled polypropylene or stainless steel
- All 300 series stainless steel hardware
- EPDM seals for broad chemical resistance
- Standard manifold inlet and outlet for easy plumbing
- With safety guard installed, no exposure to moving parts
- Typical operating speed: 3600 RPM
- Capable of handling occasional solid particles up to 1/2" in diameter
- Maximum self-priming height 25 ft (7.6 m)
- Hydraulic model optimized for suction lift
- Other models optimized for flooded suction
- 4 year commercial warranty when registering Vanguard Gas Engine - 3 year warranty on Honda engine.



\*Using flooded suction piping.



**MAX FLOW**  
3" SUCTION

**MAX FLOW**  
4" SUCTION

BANJO PUMPS	GAS ENGINE	450 GPM	515 GPM
	ELECTRIC MOTOR	450 GPM	515 GPM
	HYDRAULIC MOTOR	450 GPM	500 GPM
	LEADING COMPETITOR	424 GPM	449 GPM
	BANJO ADVANTAGE	6.1%	14.5%

\*Using flooded suction piping

## SPW300PH-6 3" Banjo Poly Pump with 6.5 Honda Engine



- Corrosion resistant
- High performance impellers
- High strength polypropylene
- Lightweight — portable

Part No.	Description	Weight
SPPSPW300PH-6	3" Polypropylene Pump - Gas Engine & Pump	50.0 lbs.



# Transfer Pumps

## Series 1543P 3" Polypropylene Transfer Pumps

# HYPRO®

Hypro self-priming centrifugal transfer pumps handle big, high capacity, liquid transfer jobs with ease. The line of pumps offer flow rates from 150 gpm up to 440 gpm to make short work of jobs such as filling nurse tanks, watering seedbeds and transferring liquids.

The durable and powerful line includes polypropylene, aluminum and cast iron models. Use them for transferring water, liquid fertilizers and other chemicals compatible with pump materials. Polypropylene is a lightweight option that provides excellent resistance to corrosive chemicals. Aluminum is an economical choice for water transfer. Cast Iron is most suitable for rugged applications.

Hypro transfer pumps share these features:

- Low oil sensor prevents engine seizing when oil level is too low (gas engine models)
- Easily handles high capacity liquid transfer jobs up to 440 gpm
- Self-priming capabilities
- Cast iron impellers (in cast iron models) and Nylon impellers, constructed for improved strength, can handle solid particles in suspension up to 3/8" diameter.
- Gas engine-driven versions powered by field proven 13 HP Hypro PowerPro™ engine or Honda GX390.
- Housing: 3" x 3" Polypropylene.
- Pump Seals: EPDM Mechanical.
- Suction lift: 25 ft./7.62 m.
- Poly impeller with stainless steel insert.



SPP1543P-130SP

Part No.	Max GPM	Max PSI	Port Size	Engine Mfg. & HP
SPP1543P-130SP	440	54	3" x 3"	PowerPro 13 HP
SPP1543P-130ESP	440	54	3" x 3"	PowerPro 13 HP w/ elec. start
SPP1543P-390EHSP	440	54	3" x 3"	Honda GX390 w/ elec. start

Achieve the highest performance available in a 3" poly transfer pump (up to 484 GPM) with the highest efficiency and horsepower on the market. Ideal for nurse tank and transfer and other closed system applications. The polypropylene housing and EPDM elastomers protect the pump from most chemicals and corrosive environments.

### U.S. Units

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 58 PSI
440	400	338	269	184	68	0

### Metric Units

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.0 BAR
1666	1514	1279	1018	697	257	0



# Chemical Transfer Pumps

**BEPNP-2065HR** 2" Chemical Transfer Pump

**BEPNP-3065HR** 3" Chemical Transfer Pump



Versatile pump system that can move water as well as a variety of chemicals such as liquid fertilizer. Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday. Fiberglass-reinforced polyester pump body construction withstands agriculture and industrial chemicals that would corrode aluminum pumps. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

	BEPNP-2065HR	BEPNP-3065HR
Fuel Capacity	0.82 GAL (3.1L)	0.82 GAL (3.1L)
Impeller	Fiberglass Reinforced Poly	Fiberglass Reinforced Poly
Suction Lift	26'	26'
Total Lift	115'	92'
Series	Commercial	Commercial
Pump	Fiberglass Reinforced Poly	Fiberglass Reinforced Poly
CC	196	196
Weight	60 lbs.	64 lbs.
Engine	Honda GX200	Honda GX200
GPM	154	265



## **BEPNP2065K** 2" Chemical Transfer Pump with Kohler SH270 Engine

Versatile pump system that can move water as well as a variety of chemicals such as liquid fertilizer. Rugged Kohler engine drives the pump with plenty of power. Fiberglass-reinforced polyester pump body construction withstands agriculture and industrial chemicals that would corrode aluminum pumps. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

- Discharge Lift: 89'
- Inlet/Outlet Size: 2"
- Suction Lift: 26'
- Total Lift: 115'
- Series: Commercial
- Engine: Kohler SH270
- CC: 196
- PSI: 40
- GPM: 154
- Weight: 54 lbs.



Part No.	Description
BEPNP2065K	2" Chemical Transfer Pump with Kohler SH270 Engine

# Chemical Transfer Pumps

**BEPNP-2070R** 2" Chemical Transfer Pump

**BEPNP-3070R** 3" Chemical Transfer Pump



Heavy-duty, reinforced trash pump that will handle water with dirt, grit and rocks. Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday. Heavy-duty reinforced aluminum pump body and cast iron impellers can handle solids up to 1" making this pump ideal for moving dirty water. Quick access flanges allow for rapid cleaning of the pump body. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

	BEPNP-2070R	BEPNP-3070R
Fuel Capacity	0.95 GAL (3.6L)	0.82 GAL (3.1L)
Impeller	Fiberglass Reinforced Poly	Fiberglass Reinforced Poly
Suction Lift	26'	26'
Total Lift	115'	96'
Series	Workshop	Workshop
Engine	Powerease	Powerease
Pump	Fiberglass Reinforced Poly	Fiberglass Reinforced Poly
CC	223	223
Weight	60 lbs.	64 lbs.
GPM	154	265



# Water Transfer Pumps

**BEPWP-2070S** 2" - 7 HP Power Ease Water Pump

**BEPWP-3070S** 3" - 7 HP Water Transfer Pump



Extremely popular, general purpose pump that quickly moves large volumes of water. Rugged and reliable Powerease engine drives the pump with plenty of power. The pump body is made with aluminum to lower weight, and has a cast iron impeller for strength. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.



	BEPWP-2070S	BEPWP-3070S
Fuel Capacity	0.95 GAL (3.6L)	0.95 GAL (3.6L)
Impeller	Cast Iron	Cast Iron
Suction Lift	26'	26'
Total Lift	82'	85'
Series	Workshop	Workshop
Engine	Powerease	Powerease
Pump	Centrifugal Aluminum	Centrifugal Aluminum
CC	223	223
Weight	NA	63 lbs.
GPM	158	264

**BEPWP-2065HL** 2" 200CC Honda GX Water Pump

**BEPWP-3065HL** 3" 6.5 HP Honda GX Water Pump

	BEPWP-2065HL	BEPWP-3065HL
Fuel Capacity	0.82 GAL (3.1L)	0.82 GAL (3.1L)
Impeller	Cast Iron	Cast Iron
Suction Lift	26'	26'
Total Lift	82'	85'
Series	Commercial	Commercial
Engine	Honda GX200	Honda GX200
Pump	Centrifugal Aluminum	Centrifugal Aluminum
CC	196	196
Weight	62 lbs.	67 lbs.
GPM	158	264



# Water Transfer Pumps



## **BEPWP-1020R** 1" Water Transfer Pump With Powerease 79 Engine

A lightweight, general purpose pump for those who need to move water. Rugged and reliable Powerease engine drives the pump with plenty of power. The pump body and impeller are both made with aluminum to minimize weight. Mounted on a steel plate with carry handle for ease of storage and transportation while maintaining the stability it needs during operation.

### STANDARD FEATURES

- Fuel Capacity: 0.5 GAL (2L)
- Impeller: Aluminum
- Suction Lift: 23'
- Total Lift: 85'
- Series: Workshop
- Engine: Powerease
- Pump: Centrifugal Aluminum
- CC: 79
- GPM: 42



Part No.	Description
BEPWP-1020R	1" Water Transfer Pump w/ Powerease 79 Engine

## **BEPHP-2065HR** High Pressure Water Pump

Powerful pump system that increases pressure to deliver water over a longer distance. Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate. Higher pressure pump that displaces water like normal pumps, but also has the ability to spray water with the correct attachments.

SPRAY ATTACHMENTS (SOLD SEPARATELY): Fire Hose Kit 50.400.001 Hose Adapter 50.015.007

### STANDARD FEATURES

- Fuel Capacity: 0.82 GAL (3.1L)
- Impeller: Aluminum
- Suction Lift: 26'
- Total Lift: 197'
- Series: Commercial
- Engine: Honda GX200
- Pump: Centrifugal Aluminum
- CC: 196
- GPM: 126
- Weight: 73 lbs.



Part No.	Description
BEPHP-2065HR	High Pressure Water Pump, 2" Ports 6.5 HP Honda



# Water Transfer Pumps



**BEPHP-2070R** 2" High-Pressure Water Transfer Pump with Powerease 225 Engine

Powerful pump system that increases pressure to deliver water over a longer distance. Rugged and reliable Powerease engine drives the pump with plenty of power. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate. Higher pressure pump that displaces water like normal pumps, but also has the ability to spray water with the correct attachments.

**STANDARD FEATURES**

- Discharge Lift: 171'
- Inlet/Outlet Size: 2"
- Suction Lift: 26'
- Total Lift: 197'
- Series: Workshop
- Engine: PowerEase
- CC: 223
- PSI: 85
- GPM: 126



Part No.	Description
BEPHP-2070R	2" High Pressure Water Pump with Powerease 225 Engine

**BEPWP2065K** 2" Water Transfer Pump with Kohler SH270 Engine

Extremely popular, general purpose pump that quickly moves large volumes of water. Rugged Kohler engine drives the pump with plenty of power. The pump body is made with aluminum to lower weight, and has a cast iron impeller for strength. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

**STANDARD FEATURES**

- Discharge Lift: 59'
- Inlet/Outlet Size: 2"
- Suction Lift: 26'
- Total Lift: 85'
- Series: Workshop
- Engine: Kohler SH270
- CC: 196
- PSI: 33
- GPM: 158
- Weight: 62 lbs.



Part No.	Description
BEPWP2065K	2" Water Transfer Pump with Kohler SH270 Engine

# Water Transfer Pumps



## **BEPHP-2013HR** 2" High-Pressure Water Transfer Pump With Honda GX390 Engine

Powerful pump system that increases pressure to deliver water over a longer distance. Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate. Higher pressure pump that displaces water like normal pumps, but also has the ability to spray water with the correct attachments.

### STANDARD FEATURES

- Fuel Capacity: 1.8 GAL (6.1L)
- Impeller: Heavy Duty Aluminum
- Suction Lift: 26'
- Total Lift: 330'
- Series: Commercial
- Engine: Honda GX390
- Pump: Centrifugal Cast Iron
- CC: 389
- Weight: 140 lbs.
- GPM: 140



Part No.	Description
BEPHP-2013HR	2" High-Pressure Water Transfer Pump w/ Honda GX390 Engine

## **BEPWP4013H** 4" Water Transfer Pump With Honda GX390 Engine 389CC

Powerful general purpose pump that quickly moves large volumes of water. Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday. The pump body is made with aluminum to lower weight, and has a cast iron impeller for strength. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

### STANDARD FEATURES

- Fuel Capacity: 6.1L (1.6 US G)
- Engine: Honda GX390
- PSI: 38
- Weight: 112 lbs.
- GPM: 422



Part No.	Description
BEPWP4013H	4" Water Transfer Pump w/ Honda GX390 Engine 389CC

# Firefighting Water Pumps

## **BEPHPFK-2070R** 2" Firefighting Water Pump with Powerease 225 Engine

- Firefighting kit that includes the hoses and accessories needed to setup and operate the high pressure pump to spray water up to 80 feet.
- Rugged and reliable Powerease engine drives the pump with plenty of power.
- Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it.
- Built-in data plate includes all the key information the user would need to operate.
- Higher pressure pump that displaces water like normal pumps, but also has the ability to spray water with the included attachments.
- Kit Includes 12' suction hose, 50' fire hose and fire hose nozzles.
- **WARNING:** Do not use to attack fire line.



Part No.	Description
BEPHPFK-2070R	2" Firefighting Water Pump with Powerease 225 Engine

## **BEPWS1565H** 1.5" High-Pressure Water Pump with Honda GX200 Engine

- Firefighting high pressure pump that includes outlets to attach hoses to spray water.
- Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday.
- Higher pressure pump that displaces water like normal pumps, but also has the ability to spray water with the correct attachments.
- Steel frame protects the machine and provides ergonomic hand holds to easily maneuver it.
- Built-in data plate includes all the key information the user would need to operate.
- Specifically designed to spray water up to 80 feet with the fire hose and nozzle attachment.
- **WARNING:** Do not use to attack fire line
- **SPRAY ATTACHMENT (Sold Separately):** Fire Hose Kit 50.400.001



Part No.	Description
BEPWS1565H	1.5" High-Pressure Water Pump with Honda GX200 Engine

## **BEPHPFC-2065HR** 2" Firefighting Water Pump with Honda GX200 Engine

- Firefighting kit that includes the hoses and accessories needed to setup and operate the high pressure pump to spray water up to 80 feet.
- Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday.
- High pressure pump that displaces water like normal pumps, but also has the ability to spray water with the correct attachments.
- Steel roll cage cart has everything needed to move and set up the system.
- Kit Includes 12' suction hose, 50' fire hose and fire hose nozzles.
- **WARNING:** Do not use to attack fire line.



Part No.	Description
BEPHPFC-2065HR	2" Firefighting Water Pump with Honda GX200 Engine

# Trash Pumps



## **BEPTP-2065HT** 2" Semi-Trash Transfer Pump With Honda GX200 Engine

Reinforced semi-trash water pump that will handle water with dirt, grit and small rocks. Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday. Reinforced aluminum body and cast iron impellers can handle solids up to 5/8" making this pump ideal for moving dirty water. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

### STANDARD FEATURES

- Suction Lift: 26'
- Total Lift: 85'
- Series: Commercial
- Engine: Honda GX200
- CC: 196
- GPM: 158
- Weight: 80 lbs.



Part No.	Description
BEPTP-2065HT	2" Semi-Trash Transfer Pump w/ Honda GX200 Engine

## **BEPTP-3070R** 3" Semi-Trash Transfer Pump With Powerease 225 Engine

Reinforced semi-trash water transfer pump that will handle water with dirt, grit and small rocks. Rugged and reliable Powerease engine drives the pump with plenty of power. Reinforced aluminum body and cast iron impellers can handle solids up to 5/8" making this pump ideal for moving dirty water. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

### STANDARD FEATURES

- Fuel Capacity: 0.95 GAL (3.6L)
- Impeller: Heavy Duty Cast Iron
- Solid Handling: Up to 1"
- Suction Lift: 26'
- Total Lift: 85'
- Series: Workshop
- Engine: Powerease
- Pump: Centrifugal Aluminum
- CC: 223
- Weight: 90 lbs.
- GPM: 264
- Weight: 90 lbs.



Part No.	Description
BEPTP-3070R	3" Semi-Trash Transfer Pump w/ Powerease 225 Engine

# Trash Pumps

**BEPTP-2065HR** 2" Trash Transfer Pump with Honda GX200 Engine

**BEPTP-3065HR** 3" Semi-Trash Transfer Pump with Honda GX200 Engine



Heavy-duty, reinforced trash pump that will handle water with dirt, grit and rocks. Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday. Heavy-duty reinforced aluminum pump body and cast iron impellers can handle solids up to 3/4" making this pump ideal for moving dirty water. Quick access flanges allow for rapid cleaning of the pump body. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

	BEPTP-2065HR	BEPTP-3065HR
Discharge Lift	59"	59"
Inlet/Outlet Size	2"	3"
Max Solid	3/4"	5/8"
Suction Lift	26"	26"
Total Lift	85'	85'
Series	Commercial	Commercial
Engine	Honda GX200	Honda GX200
CC	196	196
PSI	33	36
GPM	180	264
Weight	80	90



**BEPTP-3013HM** 3" Trash Transfer Pump with Honda GX390 Engine

Heavy-duty, reinforced trash pump that will handle water with dirt, grit and rocks. Commercial Honda engine with excellent weight to power ratio. Designed to be used all day, everyday. Heavy-duty reinforced aluminum pump body and cast iron impellers can handle solids up to 1" making this pump ideal for moving dirty water. Quick access flanges allow for rapid cleaning of the pump body. Steel roll cage protects the machine and provides ergonomic hand holds to easily maneuver it. Built-in data plate includes all the key information the user would need to operate.

**STANDARD FEATURES**

- Discharge Lift: 72'
- Inlet/Outlet Size: 3"
- Max Solid: 1"
- Suction Lift: 26'
- Total Lift: 98'
- Series: Industrial
- Engine: Honda GX390
- CC: 389
- PSI: 37
- GPM: 370
- Weight: 144 lbs.



Part No.	Description
BEPTP-3013HM	3" Trash Transfer Pump with Honda GX390 Engine

## Fuel Transfer Pumps (AC)

**WSEFR610HA** 115 Volt AC Pump With Auto Nozzle 15 GPM

**FILL-RITE.**

### 115V AC 15 GPM Heavy-Duty Fuel Transfer Pump with Automatic Nozzle

The Fill-Rite FR610HA is a 115V AC heavy-duty, cast-iron, rotary vane fuel transfer pump that is capable of generating up to 15 GPM. It is designed to handle flammable liquids such as gasoline, diesel, biodiesel blends up to B20, ethanol blends up to E15, kerosene, and mineral spirits. The pump motor utilizes a low amp draw and is thermally protected to prevent overheating. The FR610HA model is available with a 3/4" automatic (red boot) nozzle, 12' UL fuel hose, as well as other accessories. With UL/cUL listed pump and motor, this product is ideal for agriculture, construction, or any industry requiring mobile fuel transfer.



#### STANDARD FEATURES

- Adjustable electric junction box rotates 180°
- Reliable, heavy-duty power switch withstands heavy abuse in rugged environments
- Focused weight reduction while preserving expected heavy-duty performance
- Thermally protected motor prevents overheating to maximize motor life
- Premium paint shield for exemplary corrosion resistance

Part Number	Description
WSEFR610HA	115 Volt AC Pump w/ Auto Nozzle 15 GPM



### Shaft Seal Kit For FR300 and FR700 Series Pumps

Kit includes retaining ring, spring, O-ring (small), stainless steel mating ring, O-ring (large), and carbon sealing ring (large).

Part Number	Description
WSEKIT700SL	Shaft Seal Kit for FR300 and FR700 Series Pump



# Fuel Transfer Pumps (AC)



**WSEFR710VB** 115 Volt AC Pump w/ Auto Nozzle 20 GPM

## 115V AC 20 GPM Heavy-Duty Fuel Transfer Pump With Auto Nozzle

The Fill-Rite 710V Series AC heavy-duty fuel transfer pumps lead the industry in performance and longevity. Designed with all cast-iron construction, thermal overload protection, and provided in a variety of supplied configurations, it's no surprise why the FR710V Series is considered the most dependable AC pump in the industry. You name the application and the durability and dependability of Fill-Rite's 20 GPM FR710V Series will meet the challenge. These rugged pumps are also backed by the industry's most stringent safety standards like UL/cUL, ATEX, CE.



### STANDARD FEATURES

- High volume fuel transfer at a rapid 20 GPM
- All cast-iron construction provides rugged durability
- Superior flexibility working with gasoline, diesel, biodiesel, B20, E15, kerosene, and mineral spirits Explosion-proof motor and UL listing assure the highest level of safety engineering

Part Number	Description
WSEFR710VB	115 Volt AC Pump w/ Auto Nozzle 20 GPM

**WSENX25-120NB-AA** 120 Volt Continuous Duty Pump W/ Ultra HF Nozzle

## 120V AC 25 GPM Continuous Duty Fuel Transfer Pump with Ultra Hi-Flow Auto Nozzle

The NX25-120 continuous duty fuel transfer series allows users to fuel all day with less downtime. The NX25's robust variable speed motor actively adjusts its speed for optimal performance and produces a true 25 GPM flow rate at the nozzle. It reduces long-term damage on wetted components while also improving suction lift. Its low profile, lightweight construction reduces installation time. Intelligent audible tones simplify the troubleshooting process by informing users when and where attention is needed. Its rugged powder-coated paint stands the test of time against even the toughest environmental factors. The NX25 series defines elite efficiency in fuel transfer.



### STANDARD FEATURES

- Continuous duty cycle, transfer fuel all day with no downtime
- Pumps 25% faster, eliminating hours of costly driver downtime while filling up equipment
- Consumes up to 45% less electricity, slashing operating costs and boosting efficiency
- 60% lighter weight, making installation faster and strain free
- 75% reduction in common field repair costs through quality design and construction
- Built-in remote on/off, ideal for tall, above ground tanks

Part Number	Description
WSENX25-120NB-AA	120 Volt Continuous Duty Pump w/ Ultra HF Nozzle

## Fuel Transfer Pumps (DC)

### WSEFR1210HARC 12 Volt DC Pump Arctic Series

**FILL-RITE**

#### 12V DC 15 GPM Heavy-Duty Fuel Transfer Pump with Auto Arctic Nozzle

The Fill-Rite FR1210HARC model with NPT fittings is a 12V DC heavy-duty, cast-iron, rotary vane fuel transfer pump that is capable of generating up to 15 GPM. It is designed to handle flammable liquids such as gasoline, diesel, biodiesel blends up to B20, ethanol blends up to E15, kerosene, and mineral spirits. The pump motor utilizes a low amp draw and is thermally protected to prevent overheating. The FR1210HARC model is available with a 3/4" automatic (blue boot) nozzle, 15' arctic fuel hose, 20" - 34" steel telescoping suction pipe, swivel, as well as other accessories. Rated to -40°F/-40°C, this pump has a UL/cUL listed motor. This product is ideal for agriculture, construction, or any industry requiring mobile fuel transfer in cold climates.



*"ARCTIC KITS" include a complete complement of -40C/F rated components: fuel hose, auto nozzle, and multi plane swivel.*

#### STANDARD FEATURES

- Adjustable electric junction box rotates 180°
- Reliable, heavy-duty power switch withstands heavy abuse in rugged environments
- Focused weight reduction while preserving expected heavy-duty performance
- Thermally protected motor prevents overheating to maximize motor life
- Premium paint shield for exemplary corrosion resistance
- UL/cUL listed motor

Part Number	Description
WSEFR1210HARC	12 Volt DC Pump Arctic Series

### WSEFR1210HA 12v DC 15 gpm Heavy-Duty Fuel Transfer Pump w/ Auto Red Nozzle

#### 12V DC 15 GPM Heavy-Duty Fuel Transfer Pump With Auto Red Nozzle

The Fill-Rite FR1210HA model with NPT fittings is a 12V DC heavy-duty, cast-iron, rotary vane fuel transfer pump that is capable of generating up to 15GPM. It is designed to handle flammable liquids such as gasoline, diesel, biodiesel blends up to B20, ethanol blends up to E15, kerosene, and mineral spirits. The pump motor utilizes a low amp draw and is thermally protected to prevent overheating. The FR1210HA model is available with a 3/4" automatic (red boot) nozzle, 12' fuel hose, 20" - 34" steel telescoping suction pipe, as well as other accessories. This product is ideal for agriculture, construction, or any industry requiring mobile fuel transfer.



#### STANDARD FEATURES

- Adjustable electric junction box rotates 180°
- Reliable, heavy-duty power switch withstands heavy abuse in rugged environments
- Focused weight reduction while preserving expected heavy-duty performance
- Thermally protected motor prevents overheating to maximize motor life
- Premium paint shield for exemplary corrosion resistance
- UL/cUL listed motor

Part Number	Description
WSEFR1210HA	12V DC 15gpm Heavy-Duty Fuel Transfer Pump w/ Auto Red Nozzle



# Fuel Transfer Pumps (DC)



**WSEFR4210HD** 12 Volt High Flow w/ Auto Nozzle

## 12V DC 20 GPM Heavy Duty Fuel Transfer Pump with Ultra Hi-Flow Auto Nozzle

The Fill-Rite FR4210HB model with NPT fittings is a 12V DC heavy-duty, cast-iron, rotary vane fuel transfer pump that is capable of generating up to 20 GPM. It is designed to handle flammable liquids such as gasoline, diesel, biodiesel blends up to B20, ethanol blends up to E15, kerosene, and mineral spirits. The pump motor utilizes a low amp draw and is thermally protected to prevent overheating. The FR4210HB model is available with a 1" Ultra Hi-Flow automatic (red) nozzle, 12' fuel hose, 20" - 34" steel telescoping suction pipe, as well as other accessories. This product is ideal for agriculture, construction, or any industry requiring mobile fuel transfer in cold climates.



### STANDARD FEATURES

- Adjustable electric junction box rotates 180°
- Reliable, heavy-duty power switch withstands heavy abuse in rugged environments
- Focused weight reduction while preserving expected heavy-duty performance
- Thermally protected motor prevents overheating to maximize motor life
- Premium paint shield for exemplary corrosion resistance
- UL/cUL listed motor

Part Number	Description
WSEFR4210HD	12 Volt High Flow w/ Auto Nozzle

**WSENX25-DDCNB-AA** 12-24 Volt Pump Only Continuous Duty For Fuel Transfer W/ Ultra HF Nozzle

## 12/24V DC 25 GPM Continuous Duty Fuel Transfer Pump with Ultra Hi-Flow Auto Nozzle

The NX25-DDC Continuous Duty fuel transfer series allows users to fuel all day with less downtime. The NX25's robust variable speed motor actively adjusts its speed for optimal performance and produces a true 25 GPM flow rate at the nozzle. It reduces long-term damage on wetted components while also improving suction lift. Its low-profile, lightweight construction reduces installation time. Intelligent audible tones simplify the troubleshooting process by informing users when and where attention is needed. Its rugged powder-coated paint stands the test of time against even the toughest environmental factors. The NX25 Series defines elite efficiency in fuel transfer.

### STANDARD FEATURES

- Continuous duty cycle, transfer fuel all day with no downtime
- True 25 GPM, high-flow fuel transfer rates at the nozzle
- 12 to 24V DC dual voltage, accepting a range of DC power
- Lightweight at less than 25 pounds, easing installation and reducing setup costs
- Auto power down after 20 minutes of inactivity, reducing energy costs
- Lower amp draw, saving battery power and extending pump life

Part Number	Description
WSENX25-DDCNB-AA	12-24 Volt Pump Only Continuous Duty For Fuel Transfer w/ Ultra Hf Nozzle



## Fuel Transfer Pumps (DC)

**WSENX25-DDCNF-AA** 12/24V DC 25 GPM Fuel Transfer Pump with Nozzle

**FILL-RITE.**

### 12/24V DC 25 GPM Fuel Transfer Pump with Nozzle

The NX25-DDCNF-AA model is a 12/24V DC, 25 GPM premiere fuel transfer pump. This pump and accessory bundle comes complete with a hose, nozzle, and installation components.

- Unmatched Performance - Pumps 25% faster, eliminating hours of costly driver downtime while filling up equipment
- Continuous Operation – brushless variable speed motor transfers fuel all day without overheating, extending pump life and eliminating driver downtime
- Flexible Power Input – dual voltage design allows you to power from 12-24V DC batteries without worrying of burning up the motor
- Energy Efficient - Consumes up to 45% less electricity, slashing operating costs and boosting efficiency
- Ultra-Lightweight – pump weighs 60% less at only 25 pounds, making installation faster and strain free
- Reduced Maintenance Costs — 75% reduction in common field repair costs through patented design and robust construction



Part Number	Description
WSENX25-DDCNF-AA	12/24V DC 25 GPM Fuel Transfer Pump with Nozzle

**WSEFR4210HARC** 12 Volt DC High Flow Pump Arctic Series

### 12V DC 20 GPM Heavy Duty Fuel Transfer Pump with Auto Arctic Nozzle

The Fill-Rite FR4210HARC model with NPT fittings is a 12V DC heavy duty, cast-iron, rotary vane fuel transfer pump that is capable of generating up to 20 GPM. It is designed to handle flammable liquids such as gasoline, diesel, biodiesel blends up to B20, ethanol blends up to E15, kerosene, and mineral spirits. The pump motor utilizes a low amp draw and is thermally protected to prevent overheating. The FR4210HARC model is available with a 1" automatic (blue boot) nozzle, 18' arctic fuel hose, 20" - 34" steel telescoping suction pipe, swivel, as well as other accessories. Rated to -40F/-40C, this pump has a UL/cUL listed motor and is ideal for agriculture, construction, as well as any industry requiring mobile fuel transfer in harsh cold climates.

- Adjustable electric junction box rotates 180°
- Reliable, heavy-duty power switch withstands heavy abuse in rugged environments
- Focused weight reduction while preserving expected heavy-duty performance
- Thermally protected motor prevents overheating to maximize motor life
- Premium paint shield for exemplary corrosion resistance
- UL/cUL listed motor



*"ARCTIC KITS" include a complete complement of -40C/F rated components: fuel hose, auto nozzle, and multi plane swivel.*

Part Number	Description
WSEFR4210HARC	12 Volt DC High Flow Pump Arctic Series

# Fuel Transfer Pumps (DC)

**WSEFR1612** 12V DC 10 GPM Fuel Transfer Pump



## 12V DC 10 GPM Fuel Transfer Pump

Fill Rite's 1600 Series provides extreme portability for low-volume diesel transfer, ideal for transferring out of drums and totes into smaller equipment. Fill Rite's 1600 Series provides extreme portability for low-volume diesel transfer, ideal for transferring out of drums and totes into smaller equipment.



### STANDARD FEATURES

- **Cast-Iron Construction** - durable cast-iron construction provides heavy-duty performance and withstands daily use in diesel applications
- **Compact Size** – weighing under 8 pounds, can be easily transported or held during operation
- **Ready Out of Box** – battery cable and clips are pre-installed at the factory, saving you time and eliminating frustration
- **Reliable Technology** – proven for over 60 years, rotary vane technology produces consistent flow performance over the entire life of your pump
- **Easy to Use** — toggle switch allows pump to be turned on and off with the simple touch of a button

Part Number	Description
WSEFR1612	12V DC 10 GPM Fuel Transfer Pump

## Bypass Valve Kit *For DC Pumps*

Bypass Valve Kit for FR1200, FR2400, FR4200, FR4400, FR600, SD1200, and SD600 series pumps. Kit includes bypass valve, bypass cap, bypass O-ring, and bypass valve spring.



Part Number	Description
WSEKIT120BV	Bypass Valve Kit for DC Pumps

## Ag Chemical Pumps

### **WSESS415B** 12V DC Chemical Transfer Pump, Bung Mount

**FILL-RITE**

The SS415B model is a 12V DC chemical transfer system. This Sotera bundle includes a metal bung mount and additional chemical fittings.

- **Consistent & Reliable Performance** — engineered with double diaphragms, the Sotera 400 series delivers reliable performance by maintaining constant output pressure regardless of load
- **Fluid Flexibility** — santoprene diaphragms are compatible with a wide range of fluids including but not limited to agricultural pesticides, herbicides, fertilizers, mild acids, soaps, and water
- **Durable Design** — pump can run dry without causing any internal damage, giving you peace of mind with your investment
- **Long Life** – thermally-protected motor prevents overheating, ensuring your pump withstands the test of time
- **Convenient Configurations** — conveniently available in six core configurations for your application including the portable Chemtraveller, recirculating Mix-N-Go, mobile Pump-N-Go, sturdy IBC tote bracket, steel drum mount, and plastic straight flange
- **5-Year Warranty**



Part Number	Description
WSESS415B	12V DC Chemical Transfer Pump, Bung Mount

### **WSESS435BX675** 12V DC Chemical Transfer Pump, Chemtraveller with Meter & Hose

The SS435BX675 model is a 12V DC Chemtraveller® chemical transfer system. This Sotera Chemtraveller bundle includes an air-sensing meter, suction hose, polypropylene nozzle, Norwesco® anti-drip nozzle tip, and additional chemical fittings.

- **Consistent & Reliable Performance** — engineered with double diaphragms, the Sotera 400 series delivers reliable performance by maintaining constant output pressure regardless of load
- **Fluid Flexibility** — santoprene diaphragms are compatible with a wide range of fluids including but not limited to agricultural pesticides, herbicides, fertilizers, mild acids, soaps, and water
- **Durable Design** — pump can run dry without causing any internal damage, giving you peace of mind with your investment
- **Long Life** – thermally-protected motor prevents overheating, ensuring your pump withstands the test of time
- **Convenient Configurations** — conveniently available in six core configurations for your application including the portable Chemtraveller, recirculating Mix-N-Go, mobile Pump-N-Go, sturdy IBC tote bracket, steel drum mount, and plastic straight flange
- **5-Year Warranty**



Part Number	Description
WSESS435BX675	12V DC Chemical Transfer Pump, Chemtraveller with Meter & Hose



# Ag Chemical Pumps

**WSESS465BX713** 115V AC Chemical Transfer Pump, Chemtraveller, No Meter



The SS465BX713 model is a 115V AC Chemtraveller® chemical transfer system. This Sotera Chemtraveller bundle includes a portable frame, polypropylene nozzle, Norwesco® anti-drip nozzle tip, and additional chemical fittings.

- Consistent & Reliable Performance — engineered with double diaphragms, the Sotera 400 series delivers reliable performance by maintaining constant output pressure regardless of load
- Fluid Flexibility — santoprene diaphragms are compatible with a wide range of fluids including but not limited to agricultural pesticides, herbicides, fertilizers, mild acids, soaps, and water
- Durable Design — pump can run dry without causing any internal damage, giving you peace of mind with your investment
- Long Life – thermally-protected motor prevents overheating, ensuring your pump withstands the test of time
- Convenient Configurations — conveniently available in six core configurations for your application including the portable Chemtraveller, recirculating Mix-N-Go, mobile Pump-N-Go, sturdy IBC tote bracket, steel drum mount, and plastic straight flange
- 5-Year Warranty



Part Number	Description
WSESS465BX713	115 VAC Chemtraveller® Bottom, top suction kits, no meter

# Meters

**WSETT10PN** 2-35 GPM 4-Digit Digital Chemical Transfer Meter



The TT10PN model is a 4-digit, digital, low-viscosity chemical transfer meter. This meter is equipped with NPT threads and is designed to register 2-35 gallons per minute at +/- 1% accuracy.

- Versatile Construction – models available in aluminum, polypropylene, and nickel-plated aluminum for varying fluid compatibility
- Extreme Accuracy – measures fluids within +/- 1% accuracy, ensuring your record-keeping is precise as possible
- Flexible Use – in-line design allows for installation at the pump or at the end of the discharge hose, with an LCD display that rotates 180° for your convenience
- Complete Customization – track fluids in any user-created unit in addition to preset measurements like gallons, litres, ounces, pints, and quarts
- Ready Out of Box – factory calibrated for over 20 different fluids makes installation quick, saving you time and eliminating frustration
- Impact Resistant – external rubber boot provides maximum protection and impact resistance for tougher applications



Part Number	Description
WSETT10PN	2-35 GPM 4-Digit Digital Chemical Transfer Meter

## Meters

### **WSE807CMK** 5-20 GPM, 3-Digit Mechanical Fuel Transfer Meter

**FILL-RITE**

The 807CMK is a 3-digit mechanical fuel transfer meter. This meter is equipped with NPT threads and is designed to register 5-20 gallons per minute at +/- 1% accuracy. This model includes additional installation components.

**Versatile Technology** – designed with nutating disc technology that is capable of moving rust and small debris that jam and cause damage to other meters

**Cast-Aluminum Construction** – built to last with rugged cast-aluminum construction, designed for maximum durability and lifetime corrosion resistance

**Extreme Accuracy** – measures fuel within +/- 1% accuracy, ensuring your record-keeping is precise as possible

**Low-Volume Applications** – 3-digit counter registers flow rates between 5-20 GPM and up to 99.9 gallons or liters per batch, perfect for equipment with small fuel tanks

**Lifetime Tracking** – 5-digit non-resettable counter tracks total volume transferred over lifetime of meter



#### STANDARD FEATURES

- 5 - 20 GPM
- Large, easy-to-read display
- Robust construction to withstand your harsh applications
- 3/4" inlet and outlet

Part Number	Description
WSE807CMK	3-Wheel Mechanical, 3/4 In Meter

### **WSETT10AN** 2-35 GPM, 4-Digit Digital Fuel Transfer Meter

Accurate within 1%, the Fill-Rite TT10AN In-line Digital Turbine Meter sets the standard for accuracy, ease of use, and safety. It has factory presets for 18 fluids and more safety approvals than any other meter in its class. Replaceable (2) AA batteries.

#### STANDARD FEATURES

- Highly accurate to +/- 1%
- Installation flexibility; can be installed at the pump or at the nozzle for convenient and accurate flow rate visibility
- Protective rubber boot absorbs impact to minimize meter and electronic damage in harsh environments
- Rugged cast aluminum construction; lightweight, durable material offers corrosion resistance and protection from degradation in extreme heat and frigid temperatures (-40° to 176°)
- Instant measurement conversions; measures fluid in ounces, pints, gallons, liters, and quarts at the touch of a button
- Long battery life; powered by included AA batteries that measure up to 300,000 gallons on one charge



*Comes with port adapters for 3/4" NPT hose lines plus batteries.*

Part Number	Description
WSETT10AN	In-Line Digital Turbine Meter



# Meters

**FILL-RITE**

**WSE901CL1.5** 23-151 LPM 4-Digit Mechanical Fuel Transfer Meter, Liters

Fill-Rite's 900 Series of mechanical fuel transfer meters are ideal for high-volume applications, registering up to 999 liters per batch.

The 901CL1.5 is a 4-digit mechanical fuel transfer meter. This meter is equipped with NPT threads and is designed to register 23-151 liters per minute at +/- 2% accuracy. This model does not include additional installation components.

**STANDARD FEATURES**

- **Versatile Technology** — designed with nutating disc technology that is capable of moving rust and small debris that jam and cause damage to other meters
- **Cast-Aluminum Construction** — built to last with rugged cast-aluminum construction, designed for maximum durability and lifetime corrosion resistance
- **Extreme Accuracy** — measures fuel within +/- 2% accuracy, ensuring your record-keeping is precise as possible
- **Low-Volume Applications** – 4-digit counter registers flow rates between 23-151 LPM and up to 999.9 liters per batch, perfect for heavy equipment with large fuel tanks
- **Lifetime Tracking** — 7-digit non-resettable counter tracks total volume transferred over lifetime of meter
- **Fluid Compatibility** — designed for daily use with diesel, gasoline, kerosene, mineral Spirits, heptane, hexane



Part Number	Description
WSE901CL1.5	3-151 LPM 4-Digit Mechanical Fuel Transfer Meter, Liters

## Nozzles

### Automatic Shut-off Nozzle with Red Boot, 3/4" Inlet

Fill-Rite Automatic Nozzles with built-in automatic shut-off fits unleaded fuel vehicles. This nozzle is uniquely designed to meet the requirements of the automotive industry. Heavy-duty aluminum cast construction and red weather-resistant boot ensure this nozzle can handle the toughest environments. Includes grip spring on the spout and angled inlet to reduce hose wear. Compatible with gasoline, diesel, E15, biodiesel, and kerosene. This nozzle is UL/cUL.



- Rugged cast aluminum construction withstands the toughest environments
- Adjustable latch settings help you dial in the flow
- Automatic shutoff reduces the chance for spills

Part Number	Description
WSEN075UAU10	Automatic Shut-Off Nozzle w/ Red Boot, 3/4" Inlet

### Automatic Shut-Off Nozzle with Green Boot, 1" Inlet

Fill-Rite Automatic Nozzles with built-in automatic shut-off are ideal for higher volume truck and equipment refueling operations. Heavy-duty aluminum cast construction and green weather-resistant boot ensure this nozzle can handle the toughest environments. Includes grip spring on the spout and angled inlet to reduce hose wear. Compatible with gasoline, diesel, E15, biodiesel, and kerosene. This nozzle is UL/cUL.



- Rugged cast aluminum construction withstands the toughest environments
- Adjustable latch settings help you dial in the flow
- Automatic shutoff reduces the chance for spills
- Multiple color options available

Part Number	Description
WSEN100DAU12G	Automatic Shut-Off Nozzle w/ Green Boot, 1" Inlet

## FILL-RITE

### Manual Nozzle, 3/4" Inlet

Fill-Rite aluminum manual nozzle with integral hanging hook. Designed for gasoline and diesel. Includes Viton seals and O-rings for smooth valve operation. This nozzle is UL/cUL.



- Durable construction
- Simple operation

Part Number	Description
WSEFRHMN075S	Manual Nozzle, 3/4" Inlet
WSE5200F1790	Replacement Discharge Spout

### Arctic Weather Automatic Shut-Off Nozzle with Blue Boot, 1" Inlet

Fill-Rite Arctic Weather Automatic Nozzles with built-in automatic shut-off are ideal for automotive diesel fuel applications. This nozzle is uniquely designed to meet the requirements of the automotive industry. Heavy-duty aluminum cast construction and blue weather-resistant boot ensure this nozzle can handle the coldest environments down to -40° F. Compatible with gasoline, diesel, E15, biodiesel, and kerosene. One-year warranty. UL/cUL.



- Rugged cast aluminum construction withstands the toughest environments
- Adjustable latch settings help you dial in the flow
- Automatic shutoff reduces the chance for spills
- Multiple color options available
- Designed to operate in temperatures as low as 40°F

Part Number	Description
WSEFRNA100DAU00	Arctic Weather Automatic Shut-Off Nozzle w/ Blue Boot, 1" Inlet





# Nozzles

**FILL-RITE**

## 3/4" Automatic Gasoline Spout Nozzle (Red)

The SDN075RAN is a 3/4" automatic shutoff nozzle designed for fuel transfer. This model is designed for gasoline applications with a 13/16" spout size and red jacket. The SD Series nozzles from Fill-Rite usher in a new era of both value and performance. These nozzles are graded standard-duty and are offered at competitive prices, yet still feature the trusted Fill-Rite reliability and durability customers expect.

- Cast-Aluminum Construction – engineered with rugged cast-aluminum construction, built to last through the most demanding applications
- Easy to Use – included spout spring on automatic nozzles ensure optimal nozzle placement each time you fill, eliminating opportunity for damage
- Adjustable Latching – three separate latch positions on automatic nozzles allow you to quickly and easily tailor flow rates for different equipment
- Automatic Shut-Off – automatic shut-off reduces mess by preventing overfilling and spilling, keeping you safe and efficient



Part Number	Description
WSESDN075RAN	3/4" Automatic Gasoline Spout Nozzle (Red)

## Automatic Diesel Spout Nozzles (Green)

These models are an automatic shutoff nozzle designed for fuel transfer. They are designed for diesel applications with a 15/16" (SDN075GAN) or 1-1/8" (SDN100GAN) large spout size and green jacket. The SD Series nozzles from Fill-Rite usher in a new era of both value and performance. These nozzles are graded standard-duty and are offered at competitive prices, yet still feature the trusted Fill-Rite reliability and durability customers expect.

- Cast-Aluminum Construction – engineered with rugged cast-aluminum construction, built to last through the most demanding applications
- Easy to Use – included spout spring on automatic nozzles ensure optimal nozzle placement each time you fill, eliminating opportunity for damage
- Adjustable Latching – three separate latch positions on automatic nozzles allow you to quickly and easily tailor flow rates for different equipment
- Automatic Shut-Off – automatic shut-off reduces mess by preventing overfilling and spilling, keeping you safe and efficient



Part Number	Description
WSESDN075GAN	3/4" Automatic Diesel Spout Nozzle (Green)
WSESDN100GAN	1" Automatic Diesel Spout Nozzle (Green)

## Nozzles

**FILL-RITE**

### Manual 3/4" Polypropylene DEF Nozzle

The FRDFM075C is a 3/4" non-metallic manual nozzle designed for DEF transfer. This model is equipped with a stainless steel diesel-sized spout and an integrated swivel.

- Nonmetallic & Stainless Steel Construction – engineered with a rugged nonmetallic and stainless steel construction to built to last through the most demanding DEF applications
- Ease of Use – integrated swivel improves maneuverability of nozzle when filling your vehicle, especially in cold temperatures



Part Number	Description
WSEFRDFM075C	3/4" Polypropylene Manual DEF Nozzle

### Automatic 3/4" Polypropylene DEF Nozzle

The FRDFA075B is a 0.75" stainless steel automatic shutoff nozzle designed for DEF transfer. This model is equipped with a stainless steel diesel-sized spout and an integrated swivel.

Please note: Fill-Rite auto shut off nozzles are not intended to be used for gravity flow systems.

- Cast-Aluminum Construction – engineered with rugged cast-aluminum construction, built to last through the most demanding applications
- Easy to Use – included spout spring ensures optimal nozzle placement each time you fill, eliminating opportunity for damage
- Adjustable Latching – three separate latch positions allow you to quickly and easily tailor flow rates for different equipment
- Automatic Shut-Off – automatic shut-off reduces mess by preventing overfilling and spilling, keeping you safe and efficient
- Multiple Configurations – available in a variety of configurations to meet your application's temperature, flow, and fluid compatibility requirements



Part Number	Description
WSEFRDFA075B	3/4" Polypropylene Automatic DEF Nozzle

# Hose



## Fuel Transfer Hose, 3/4" x 15'

The Fill-Rite FRH07515 (3/4" x 15', NPT) fuel transfer hose is constructed with an internal spring guard to resist kinking, stainless steel ground wire, fuel-resistant neoprene exterior, and nitrile interior. It is compatible with gasoline, diesel, biodiesel up to B20, ethanol up to E15, and kerosene.

The FRH07514 hose is suitable for all electric fuel transfer pumps.



Part Number	Description
WSEFRH07514	3/4 In X 14 Ft Retail Hose

## Fuel Transfer Hose, 3/4" x 20'

The Fill-Rite FRH07520 (3/4" x 20', NPT) fuel transfer hose is constructed with an internal spring guard to resist kinking, stainless steel ground wire, fuel-resistant neoprene exterior, and nitrile interior. It is compatible with gasoline, diesel, biodiesel up to B20, ethanol up to E15, and kerosene.

The FRH07520 hose is suitable for all electric fuel transfer pumps.



Part Number	Description
WSEFRH07520	3/4 In X 20 Ft Retail Hose

## Fuel Transfer Hose, 1" x 14'

The Fill-Rite FRH10014 (1" x 14', NPT) fuel transfer hose is constructed with an internal spring guard to resist kinking, stainless steel ground wire, fuel-resistant neoprene exterior, and nitrile interior. It is compatible with gasoline, diesel, biodiesel up to B20, ethanol up to E15, and kerosene.

The FRH10014 hose is suitable for all electric fuel transfer pumps.



Part Number	Description
WSEFRH10014	1 In X 14 Ft Retail Hose

## Arctic Fuel Transfer Hose 3/4" x 15'

The Fill-Rite FRHA07515 (3/4" x 15', NPT) arctic fuel transfer hose is specifically designed for cold weather usage to -40°F/C. The hose is constructed with an internal spring guard to resist kinking, stainless steel ground wire, fuel-resistant neoprene exterior, and nitrile interior. It is compatible with gasoline, diesel, biodiesel up to B20, ethanol up to E15, and kerosene. The FRHA07515 hose is suitable for all electric fuel transfer pumps.

- 3/4" male NPT fittings
- Internal spring guard
- Stainless steel ground wire
- Fuel-resistant neoprene exterior and high-quality nitrile interior



Part Number	Description
WSEARCH07520A	3/4 In X 15 Ft Retail Arctic Fuel Transfer Hose

## Fuel Transfer Hose, 1" x 20'

The Fill-Rite FRH10020 (1" x 20', NPT) fuel transfer hose is constructed with an internal spring guard to resist kinking, stainless steel ground wire, fuel-resistant neoprene exterior, and nitrile interior. It is compatible with gasoline, diesel, biodiesel up to B20, ethanol up to E15, and kerosene.

The FRH10020 hose is suitable for all electric fuel transfer pumps.



Part Number	Description
WSEFRH10020	1 In X 20 Ft Retail Hose

# DEF Fluid Dispensing Pumps

**WSEDF120CAN520-RP** 120v AC DEF Dispensing Pump w/ Auto Nozzle

**FILL-RITE**

## 120V AC 8 GPM DEF Transfer Pump with Auto Nozzle and RPV System

The Fill-Rite DF120CAN520-RP is a 120V AC pump factory mounted to a stainless steel IBC bracket. It is capable of up to 8 GPM and designed with EPDM seals proven specifically for DEF/AdBlue, anti-freeze, and water. Included accessories that are compatible with DEF are a 5' suction and 20' discharge hose, automatic nozzle, Micro Matic RVP, and various 1" BSPP fittings and hose clamps.

### STANDARD FEATURES

- Rugged multi-diaphragm technology specifically designed for DEF/AdBlue
- Integral pulsation dampener for smooth flow at point of use
- 30-minute duty cycle for either voltage
- Self priming to 6'
- Flow rate up to 8 GPM
- EPDM seals and stainless steel exterior hardware



WSEDF120CAN520-RP	
Pump Voltage	120V
Bracket Type	Cage IBC
Nozzle Boot & Bracket	Included
Turbine Meter	-
Nozzle Type	Automatic
Micro Matic® RPV	Included
5' Suction Hose	Included
20' Discharge Hose	Included
Connections	(2) 1" BSPP x 3/4" hose barb 90° elbows, (2) 1" BSPP x 3/4" hose barb straight fittings, (4) Worm gear hose clamps



Part Number	Description
WSEDF120CAN520-RP	120V AC Def Dispensing Pump w/ Auto Nozzle



# DEF Fluid Dispensing Pumps



## **WSEDF012CMN520** 12 Volt DC 8 GPM DEF Dispensing Pump with Manual Nozzle

The Fill-Rite DF012CAN520 is a 12V DC pump factory mounted to a stainless steel IBC bracket. It is capable of up to 8 GPM and designed with EPDM seals proven specifically for DEF/AdBlue, anti-freeze, and water. Included accessories that are compatible with DEF are a 5' suction and 20' discharge hose, manual nozzle, and various 1" BSPP fittings and hose clamps.

- Rugged multi-diaphragm technology specifically designed for DEF/AdBlue
- Integral pulsation dampener for smooth flow at point of use
- 30-minute duty cycle for either voltage
- Self priming to 6'
- Flow rate up to 8 GPM
- EPDM seals and stainless steel exterior hardware



WSEDF012CMN520	
Pump Voltage	12 V DC
Bracket Type	Cage IBC
Nozzle Boot & Bracket	Included
Turbine Meter	-
Nozzle Type	Manual
Micro Matic® RPV	-
5' Suction Hose	Included
20' Discharge Hose	Included
Connections	(2) 1" BSPP x 3/4" hose barb 90° elbows, (2) 1" BSPP x 3/4" hose barb straight fittings, (4) Worm gear hose clamps

Part Number	Description
WSEDF012CMN520	12 Volt DC Def Dispensing w/ Manual Nozzle

## **WSEFRAP32V** Air-Operated DEF Transfer Pump

Fill-Rite's air-operated pump features tough polypropylene construction and is designed for low-volume drum applications.

- Polypropylene Construction – rugged polypropylene body resists corrosion in demanding chemical and industrial applications
- Economical Solution – reliably transfers 6.5 gallons per minute from 55-gallon drums in low-volume transfer applications
- Air-Operated – seamlessly hook up the existing air lines in your garage or shop for a quick fluid transfer solution
- Flexible Fluid Compatibility – compatible with a wide variety of fuel, oil and chemical fluids





Part Number	Description
WSEFRAP32V	Air-Operated DEF Transfer Pump

# Pressure Washer Hose Reels

## HOSE REELS *Heavy Duty Pressure Washer Hose Reels*

### STANDARD FEATURES

- Max. 3000 PSI
- Max. 160°F
- Hose size 3/8"



Part Number	Max Hose	Max Height	Max Width
SPP85.402.050	50'	13"	11.75"
SPP85.402.001	100'	17"	18"
SPP85.402.002	200'	20"	15.75"

***Refer to Ag Catalogue Section 19 for a complete listing of all Shop Supplies & Accessories***




## WESTWARD PARTS

6517 - 67 St.  
Red Deer, AB T4P 1A3  
Fax: 1-800-661-4508

201 Henderson Dr.  
Regina, SK S4N 7E2  
Fax: 1-800-721-2977

1435 St. James St.  
Winnipeg, MB R3H 0W9  
Fax: 1-800-257-8338

Specifications subject to change without notice or obligation.



WESTWARDPARTS.COM



1-888-937-7278

Westward Parts offers the most comprehensive range of products to meet the needs of all agricultural and industrial customers.



## Agriculture Parts

- Bearings, Seals, Flanges, O-Rings
- 3 Point Hitch Parts or Tillage Tools
- PTO Drives, Adapters, Yokes, Crosses
- Canvas, Swather Parts, Canvas Repair
- Combine Repair Parts
- Harrow Parts, Pickup & Harrow Tines
- Pickup Reel Parts
- Cutting Parts & Guards, Ag Accessories

## Sprayer Parts

- Pumps & Couplers
- Valves, Manual & Electric
- Tips, Strainers, Filters
- Nozzle Bodies, Caps, Boom Clamps
- Hose, Fittings, Cam Locks
- Handguns
- Pressure Washer Parts
- Booms, Tanks, Accessories



## Estate Equipment

- Cameras & Accessories
- Fencing Equipment
- Hay & Bale Handling Equipment
- Lawn & Garden
- Material Movement
- Estate Sprayers & Accessories
- Tillage Equipment
- Water, Transfer & Trash Pumps

## Industrial Parts

- Chain, V-Belts, Chain Tools
- Bearings, Seals, Flanges, O-Rings
- Sheaves, Pulleys, Sprockets, Weld-ons
- Hardware, Drawpins, Wire Rope, Lubricants
- PTO Drives, Adapters, Yokes, Crosses
- Hubs, Wheels, Spindles, Casters
- Belting Seals and Shields
- Hydraulic Fittings, Couplers, Cylinders



1-888-937-7278



For over 52 years, Westward Parts continues to be  
the premier provider of Quality Agricultural Parts  
and Equipment in Western Canada.

[www.westwardparts.com](http://www.westwardparts.com)  
**1-888-937-7278**



Scan to view all of our newest catalogues